EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Permit Number 38754 and PSDTX324M14

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities, sources, and related activities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
Routine Emission Caps		CO	1856.46	2890.68
		H_2S	6.79	21.79
		H_2SO_4	49.00	214.63
		NO_X	909.90	1760.99
		PM	188.53	747.93
		PM_{10}	188.53	747.93
		$PM_{2.5}$	188.53	747.93
		SO_2	521.66	1506.78
		VOC	804.08	1014.12
		Benzene	16.33	13.49
MSS Caps		CO	2948.62	53.88
		H_2S	6.59	0.22
		NH_3	4.41	0.17
		NO_X	532.06	11.01
		PM	80.53	1.28
		PM_{10}	80.53	1.28
		$PM_{2.5}$	80.53	1.28
		SO_2	1,019.00	37.24
		VOC	729.30	44.67
		Exempt Solvents	1.76	0.60

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

1	Heater - Crude Heater (01-H-01)	CO	8.10	20.13
		NH_3	0.05	0.17
		NO_X	9.72	19.24
		PM	1.21	4.00
		PM_{10}	1.21	4.00
		$PM_{2.5}$	1.21	4.00
		SO_2	2.50	5.71
		VOC	0.87	2.90
131	Heater - Crude Preflash (01-H-02)	CO	0.62	2.71
		NH_3	<0.01	0.02
		NO_X	1.77	6.29
		PM	0.13	0.49
		PM_{10}	0.13	0.49
		$PM_{2.5}$	0.13	0.49
		SO_2	0.27	0.64
		VOC	0.10	0.35
132	Heater - Crude Stabilizer (01-H-03)	CO	0.17	0.72
		NH_3	<0.01	<0.01

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

		NO_X	0.48	2.06
		PM	0.04	0.15
		PM_{10}	0.04	0.15
		$PM_{2.5}$	0.04	0.15
		SO_2	0.07	0.22
		VOC	0.03	0.11
74	Vacuum Heater	CO	4.99	16.77
		NH_3	0.03	0.14
		NO_X	5.98	26.21
		PM	0.74	3.26
		PM_{10}	0.74	3.26
		$PM_{2.5}$	0.74	3.26
		SO_2	1.37	4.13
		VOC	0.54	2.36
114	Heater - Desalter Heater (11-H-01)	CO	5.00	17.26
		NH_3	0.03	0.11
		NO_X	6.00	20.71
		PM	0.75	2.57

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

		PM_{10}	0.75	2.57
		$PM_{2.5}$	0.75	2.57
		SO_2	1.54	3.67
		VOC	0.54	1.86
115	HDS Heaters	CO	8.08	32.91
		NH_3	0.05	0.22
		NO_X	9.70	42.07
		PM	1.20	5.22
		PM_{10}	1.20	5.22
		$PM_{2.5}$	1.20	5.22
		SO_2	2.49	7.45
		VOC	0.87	3.78
116	Heater - HDS Pre-Heater (12-H-02)	CO	0.31	1.10
		NH_3	<0.01	0.02
		NO_X	2.36	8.28
		PM	0.15	0.51
		PM_{10}	0.15	0.51
		$PM_{2.5}$	0.15	0.51

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

		SO_2	0.30	0.73
		VOC	0.11	0.37
118	Hydrogen Reformer Heater	CO	58.51	220.73
		NH_3	0.37	1.52
		NO_X	70.21	284.40
		PM	8.72	35.80
		PM_{10}	8.72	35.80
		$PM_{2.5}$	8.72	35.80
		SO_2	44.53	122.64
		VOC	9.95	25.91
153	Heater - HR Boiler (30-B-02) (interim limit) (6)	CO	8.46	30.88
		NH_3	0.09	0.33
		NO_X	28.21	102.93
		PM	2.10	7.67
		PM_{10}	2.10	7.67
		$PM_{2.5}$	2.10	7.67
		SO_2	4.34	15.85
		VOC	1.52	5.55

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

153	Heater - HR Boiler (30-B-02) (7)	CO	8.46	28.94
		NH_3	0.09	0.33
		NO_X	22.56	82.34
		PM	2.10	5.51
		PM_{10}	2.10	5.51
		$PM_{2.5}$	2.10	5.51
		SO_2	4.34	10.66
		VOC	1.52	3.99
117	Heater - Alky Frac. Reb. (31-H-01)	CO	2.51	8.83
		NH_3	0.05	0.17
		NO_X	5.64	19.86
		PM	1.17	4.11
		PM_{10}	1.17	4.11
		$PM_{2.5}$	1.17	4.11
		SO_2	2.41	5.86
		VOC	0.85	2.97
120	Heater - Butamer Heater (36-H-01)	CO	0.27	0.98
		NH_3	<0.01	0.02

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

		NO_X	2.00	4.30
		PM	0.12	0.26
		PM_{10}	0.12	0.26
		$PM_{2.5}$	0.12	0.26
		SO_2	0.26	0.41
		VOC	0.09	0.19
162	Oleflex Heater	CO	19.45	69.49
		NH_3	0.12	0.49
		NO_X	23.34	65.75
		PM	2.90	11.62
		PM_{10}	2.90	11.62
		$PM_{2.5}$	2.90	11.62
		SO_2	5.99	16.57
		VOC	2.10	8.41
119	Heater - Sulften Heater (46-H-01)	CO	0.35	1.49
		NH_3	<0.01	0.03
		NO_X	2.17	5.21
		PM	0.13	0.32
		PM_{10}	0.13	0.32
		$PM_{2.5}$	0.13	0.32
		SO_2	0.28	0.63
		VOC	0.10	0.24

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

150	HCU Heater (interm limit) (6)	CO	6.10	24.38
		NH_3	0.06	0.26
		NO_X	20.32	81.27
		PM	1.51	6.06
		PM_{10}	1.51	6.06
		$PM_{2.5}$	1.51	6.06
		SO_2	3.13	12.52
		VOC	1.10	4.38
150	HCU Heater (7)	CO	6.10	24.38
		NH_3	0.06	0.26
		NO_X	12.19	48.76
		PM	1.51	6.06
		PM_{10}	1.51	6.06
		$PM_{2.5}$	1.51	6.06
		SO_2	3.13	8.63
		VOC	1.10	4.38

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

151	Heater - NHU Heater (48-H-01)	CO	1.06	3.82
		NH_3	0.01	0.04
		NO_X	3.52	12.72
		PM	0.26	0.95
		PM_{10}	0.26	0.95
		$PM_{2.5}$	0.26	0.95
		SO_2	0.54	1.35
		VOC	0.19	0.69
152	CRU Heater	CO	16.85	57.02
		NH_3	0.18	0.60
		NO_X	39.31	133.06
		PM	4.18	14.16
		PM_{10}	4.18	14.16
		$PM_{2.5}$	4.18	14.16
		SO_2	9.80	22.69
		VOC	3.03	10.25

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

172	Heater - RSU Heater (49-H-71)	CO	3.30	12.72
		NH_3	0.02	0.08
		NO_X	3.96	15.26
		PM	0.49	1.90
		PM_{10}	0.49	1.90
		$PM_{2.5}$	0.49	1.90
		SO_2	1.02	2.70
		VOC	0.36	1.37
49-H-90	Heater - C7 Splitter Reb. (49-H-90)	CO	5.32	16.82
		NH_3	0.03	0.13
		NO_X	4.25	15.46
		PM	0.79	3.01
		PM_{10}	0.79	3.01
		$PM_{2.5}$	0.79	3.01
		SO_2	1.64	4.29
		VOC	0.57	2.18
195	Heater - GDU Charge Heater (52-H-01)	CO	13.65	34.29
		NH_3	0.05	0.20

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

		NO_X	5.80	14.69
		PM	1.23	4.61
		PM_{10}	1.23	4.61
		$PM_{2.5}$	1.23	4.61
		SO_2	2.55	6.57
		VOC	0.89	3.34
1F	Crude Unit	VOC	See Subcap	See Subcap
2F	Vacuum Unit	H_2S	0.02	0.08
		VOC	See Subcap	See Subcap
4F	LEU Unit	VOC	See Subcap	See Subcap
11F	Desalter Unit	VOC	See Subcap	See Subcap
12F	HDS Unit	H_2S	0.14	0.62
		VOC	See Subcap	See Subcap
13F	H2 Reformer	VOC	See Subcap	See Subcap
18F	LEU -2	VOC	See Subcap	See Subcap
20F	LRU	VOC	See Subcap	See Subcap
21/22F	HOC	H_2S	0.03	0.12
		VOC	See Subcap	See Subcap
30F	Boiler House	VOC	See Subcap	See Subcap
07F	#07 BUP Flare	VOC	See Subcap	See Subcap
31F	Alky Unit	H_2S	0.10	0.43
		HF	0.52	2.29
		VOC	See Subcap	See Subcap
36F	Butamer Unit	VOC	See Subcap	See Subcap

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

37F	Iso-Octene	VOC	See Subcap	See Subcap
38F	Oleflex Unit	VOC	See Subcap	See Subcap
46-24F	SULF-10 Fugitives (5)	H_2S	0.10	0.43
		VOC	See Subcap	See Subcap
41F	SRU Unit Fugitives (5)	H_2S	0.02	0.09
		VOC	See Subcap	See Subcap
47F	HCU Unit	H_2S	0.15	0.67
		VOC	See Subcap	See Subcap
47PSA	PSA Unit	VOC	See Subcap	See Subcap
48F	NHT Unit	H_2S	0.01	0.06
		VOC	See Subcap	See Subcap
49F	CRU Unit	VOC	See Subcap	See Subcap
175	XFU/RFU/C7Split Unit	VOC	See Subcap	See Subcap
52F	GDU Unit	VOC	See Subcap	See Subcap
DOCKS	DK-Docks	VOC	See Subcap	See Subcap
08F	#08FLR/Day Tanks	VOC	See Subcap	See Subcap
LPG STGF	LPG STORAGE	VOC	See Subcap	See Subcap
MVRUF	MVRU	VOC	See Subcap	See Subcap
TERM-F	#TM-Terminal	VOC	See Subcap	See Subcap
TRKRACKFUG	TRUCK RACK (5)	VOC	See Subcap	See Subcap
83F	Wastewater Treatment Plant	VOC	See Subcap	See Subcap
54F	Selective Hydrogenation Unit	VOC	See Subcap	See Subcap
42F	Sour Water Stripper	H_2S	<0.01	0.02
		VOC	See Subcap	See Subcap
168	Oleflex CCR	Cl_2	<0.01	0.04

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

		H_2SO_4	<0.01	0.01
		HCl	0.06	0.28
		SO_2	0.04	0.19
69	Tank - 9	VOC	3.10	0.49
122	Cooling Tower - HOC	PM	17.71	65.86
		PM_{10}	16.82	62.58
		$PM_{2.5}$	2.63	9.78
		VOC	5.67	21.09
123	Cooling Tower - Alky	PM	0.71	2.00
		PM_{10}	0.70	1.98
		$PM_{2.5}$	0.19	0.55
		VOC	1.26	3.55
167-CT	Cooling Tower - BUP	PM	4.52	19.26
		PM_{10}	4.30	18.33
		$PM_{2.5}$	0.67	2.88
		VOC	1.47	6.27
1CT	Cooling Tower - Crude	PM	0.34	1.13
		PM_{10}	0.34	1.11
		$PM_{2.5}$	0.06	0.21
		VOC	0.17	0.55
73-P-3	Engine - 73-P-3	CO	3.21	4.23
		NO_X	11.63	15.35
		PM	1.06	1.39
		PM_{10}	1.06	1.39

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

		$PM_{2.5}$	1.06	1.39
		SO_2	0.98	1.30
		VOC	1.21	1.59
73-P-4	Engine - 73-P-4	CO	2.87	4.99
		NO_X	10.42	18.09
		PM	0.95	1.64
		PM_{10}	0.95	1.64
		$PM_{2.5}$	0.95	1.64
		SO_2	0.88	1.53
		VOC	1.08	1.88
73-P-5	Engine - 73-P-5	CO	3.21	8.03
		NO_X	11.63	29.12
		PM	1.06	2.64
		PM_{10}	1.06	2.64
		$PM_{2.5}$	1.06	2.64
		SO_2	0.98	2.46
		VOC	1.21	3.02
72-P-6	Engine - 72-P-6	CO	3.21	3.21
		NO_X	11.63	11.64
		PM	1.06	1.06

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

		PM_{10}	1.06	1.06
		$PM_{2.5}$	1.06	1.06
		SO_2	0.98	0.98
		VOC	1.21	1.21
72-P-7	Engine - 72-P-7	CO	3.21	0.62
		NO_X	11.63	2.25
		PM	1.06	0.20
		PM_{10}	1.06	0.20
		$PM_{2.5}$	1.06	0.20
		SO_2	0.98	0.19
		VOC	1.21	0.23
72-P-8	Engine - 72-P-8	CO	3.21	0.77
		NO_X	11.63	2.79
		PM	1.06	0.25
		PM_{10}	1.06	0.25
		$PM_{2.5}$	1.06	0.25
		SO_2	0.98	0.24
		VOC	1.21	0.29
72-P-9	Engine - 72-P-9	CO	3.21	4.77
		NO_X	11.63	17.32
		PM	1.06	1.57
		PM_{10}	1.06	1.57
		$PM_{2.5}$	1.06	1.57

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

		SO_2	0.98	1.47
		VOC	1.21	1.80
72-P-10	Engine - 72-P-10	CO	2.30	7.25
		NO_X	8.36	26.31
		PM	0.76	2.39
		PM_{10}	0.76	2.39
		$PM_{2.5}$	0.76	2.39
		SO_2	0.71	2.23
		VOC	0.87	2.73
72-P-11	Engine - 72-P-11	CO	3.24	6.43
		NO_X	11.75	23.34
		PM	1.07	2.12
		PM_{10}	1.07	2.12
		$PM_{2.5}$	1.07	2.12
		SO_2	0.99	1.97
		VOC	1.22	2.42
72-P-14A	Engine - 72-P-14A	CO	3.21	3.91
		NO_X	11.63	14.17
		PM	1.06	1.29
		PM_{10}	1.06	1.29
		$PM_{2.5}$	1.06	1.29
		SO_2	0.98	1.20
		VOC	1.21	1.47

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

72-P-14B	Engine - 72-P-14B	CO	2.85	4.74
		NO_X	10.32	17.20
		PM	0.94	1.56
		PM_{10}	0.94	1.56
		$PM_{2.5}$	0.94	1.56
		SO_2	0.87	1.45
		VOC	1.07	1.78
50-P-16	Engine - 50-P-16	CO	3.01	1.31
		NO_X	10.90	4.74
		PM	0.99	0.43
		PM_{10}	0.99	0.43
		$PM_{2.5}$	0.99	0.43
		SO_2	0.92	0.40
		VOC	1.13	0.49
50-P-20	Engine - 50-P-20	CO	3.01	2.65
		NO_X	10.90	9.61
		PM	0.99	0.87
		PM_{10}	0.99	0.87
		$PM_{2.5}$	0.99	0.87
		SO_2	0.92	0.81
		VOC	1.13	1.00
16-P-04	Engine - 16-P-04	CO	2.20	0.06
		NO_X	8.00	0.21

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

		PM	0.73	0.02
		PM_{10}	0.73	0.02
		$PM_{2.5}$	0.73	0.02
		SO_2	0.68	0.02
		VOC	0.83	0.02
16-P-07	Engine - 16-P-07	CO	2.67	0.04
		NO_X	9.69	0.15
		PM	0.88	0.01
		PM_{10}	0.88	0.01
		$PM_{2.5}$	0.88	0.01
		SO_2	0.82	0.01
		VOC	1.01	0.02
126	Main Flare	CO	See Subcap Below	See Subcap Below
		H_2S	See Subcap Below	See Subcap Below
		NO_X	See Subcap Below	See Subcap Below
		SO_2	See Subcap Below	See Subcap Below
		VOC	See Subcap Below	See Subcap Below
158	Ground Flare	CO	See Subcap Below	See Subcap Below
		H_2S	See Subcap Below	See Subcap Below
		NO_X	See Subcap Below	See Subcap Below
		SO_2	See Subcap Below	See Subcap Below
		VOC	See Subcap Below	See Subcap Below

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

127	BUP Flare	CO	See Subcap Below	See Subcap Below
		H_2S	See Subcap Below	See Subcap Below
		NO_X	See Subcap Below	See Subcap Below
		SO_2	See Subcap Below	See Subcap Below
		VOC	See Subcap Below	See Subcap Below
135	Acid Gas Flare (pilot only)	CO	See Subcap Below	See Subcap Below
		H_2S	See Subcap Below	See Subcap Below
		NO_X	See Subcap Below	See Subcap Below
		SO_2	See Subcap Below	See Subcap Below
		VOC	See Subcap Below	See Subcap Below
Various	Flares Subcap	CO	516.23	92.94
		H_2S	0.28	0.07
		NO_X	84.29	19.34
		SO_2	26.30	6.51
		VOC	228.27	49.55
31	Loading - Heavy Oil	VOC	14.96	4.72
SHIP FUG	Loading - Ships Fugitives (5)	VOC	237.46	91.74
VRU	Loading - MVRU	VOC	61.33	23.13
TRUCKFUG	Loading - Truck Fugitives (5)	VOC	11.88	13.48

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

TRUCKCOMB	Loading - Truck Combustor	CO	15.19	17.10
		NO_X	6.75	7.43
		SO_2	<0.01	0.02
		VOC	8.19	11.77
AE-49601A/B	AE-49601A/B Analyzer Vent	VOC	0.01	0.01
AE-49900A/B	AE-49900A/B Analyzer Vent	VOC	0.01	0.01
AE-49901A/B	AE-49901A/B Analyzer Vent	VOC	0.01	0.01
121	HOC Belco Scrubber	CO	889.96	1,470.33
		H_2SO_4	49.00	214.62
		NO_X	356.20	473.81
		PM	120.32	527.00
		PM_{10}	120.32	527.00
		$PM_{2.5}$	120.32	527.00
		SO_2	203.53	420.09
		VOC	28.02	115.53
121	SRU Incinerators Cap	CO	220.75	678.85
		H_2S	5.82	18.73
		NO_X	54.64	239.31
		PM	24.72	98.38
		PM_{10}	24.72	98.38
		$PM_{2.5}$	24.72	98.38
		SO_2	191.32	837.99
		VOC	0.96	3.46
Various	Fugitives Subcap (5)	VOC	125.36	484.66

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

155	CRU CCR	HCl	0.07	0.29
118	SMR Condenser Vent	VOC	3.64	15.94
21 BH	MAGNACAT Unit	PM	0.18	0.60
		PM_{10}	0.18	0.60
		$PM_{2.5}$	0.18	0.60
187	Tank 25	H_2S	0.02	0.04
		NH_3	<0.01	<0.01
		VOC	1.43	5.33
83-P-136A	Engine 83-P-136A-EN	CO	2.48	0.06
		NO_X	7.43	0.19
		PM	0.38	<0.01
		PM_{10}	0.38	<0.01
		$PM_{2.5}$	0.38	<0.01
		SO2	0.88	0.02
		VOC	7.43	0.19
83-P-136B	Engine 83-P-136B-EN	CO	2.48	0.06
		NO_X	7.43	0.19
		PM	0.38	<0.01
		PM_{10}	0.38	<0.01
		$PM_{2.5}$	0.38	<0.01
		SO2	0.88	0.02
		VOC	7.43	0.19
WWTP-OWS	WW collection system	VOC	8.62	37.77
83-TK-26	Tank 26	VOC	0.12	0.45
83-TK-159	Tank 159	VOC	0.15	0.39

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

83-TK-160	Tank 160	VOC	0.15	0.39
83-V-97	Tank 97	VOC	0.18	0.40
83-V-58	Tank 58	VOC	0.11	0.44
83-V-59	Tank 59	VOC	0.11	0.44
83-TK-162	Tank 162	VOC	0.39	1.77
83-TK-155	Tank 155	VOC	0.39	1.77
124	API/DGF Combustor	CO	1.65	7.22
		NO_X	0.45	1.76
		SO_2	0.03	0.13
		VOC	2.94	12.88
83-TK-23	Equalization Tank	VOC	0.81	3.51
83-TK27	Bio Oxidation Reactor Tank	VOC	0.51	2.22
WWTP-AERB	Aeration Basin	VOC	0.25	1.09
WWTP-CLRF	Clarifier	VOC	<0.01	0.04
WWTP-SLB	Saline Basin	VOC	<0.01	<0.01
01-01	Crude/Vacuum Unit Pump Alley	VOC	<0.01	0.02
01-02	North Side of Vacuum Unit	VOC	<0.01	0.02
01-03	North Side of Vacuum Unit	VOC	<0.01	0.02
01-04	Northwest Side of Vacuum Unit - Main Sump	VOC	<0.01	0.03
03-01	N of Tanks 156/161	VOC	0.02	0.08
98-02	WP MSAT Rail Rack	VOC	0.02	0.08
11-01	Desalter Pump Alley	VOC	<0.01	0.02
41-01	North of 43-TK-08 (Amine Tank)	VOC	<0.01	0.02
41-02	W of 41-V-05 (Acid Gas K.O. Drum)	VOC	<0.01	0.02

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

49-01	Northwest of XFU	VOC	<0.01	0.02
49-02	North Side of NHT (Unit 48)	VOC	<0.01	0.02
49-03	NHT (Unit 48) Pump Alley	VOC	<0.01	0.02
50-01	East of Tank 62	VOC	<0.01	0.02
52-01	NW of GDU MCC Room	VOC	<0.01	0.02
70-01	East of Tank 55	VOC	<0.01	0.02
70-02	Northwest of Tank 106	VOC	<0.01	0.02
70-03	West of Tank 94 (S&D Main Sump)	VOC	<0.01	0.03
72-01	East of Tank 111	VOC	<0.01	0.02
73-01	North of Tank 152 (Terminal 2A)	VOC	<0.01	0.02
73-02	Between TK 8 & TK 164 (Terminal 2)	VOC	<0.01	0.02
83-01	WWT (Hydroblast Pad)	VOC	0.02	0.07
83-02	WWT (Desalter Lift Station)	VOC	0.01	0.05
83-03	WWT (East of KOH Treater)	VOC	0.02	0.07
83-04	WWT (Northeast of Tank 159)	VOC	<0.01	0.02
83-05	WWT (North Lift Station)	VOC	<0.01	0.03
83-06	WWT (North of V-68)	VOC	<0.01	0.02
83-07	WWT (South of V-55)	VOC	<0.01	0.02
83-09	WWT (BSRP)	VOC	<0.01	0.02
83-10	WWT 83-V-99 (Diversion Box)	VOC	0.02	0.07
83-12	WWT 83-V-28 (SE of Catalyst Pad)	VOC	0.02	0.07
V-201	WP MSAT Rail Rack	VOC	0.51	2.23
124a	WP WWT API Combustor Back up	VOC	0.02	0.08

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

(1) Emission point identification – either specific equipment designation or emission point number from plot plan.
(2) Specific point source name. For fugitive sources, use area name or fugitive source name.
(3) Cl_2 - chlorine
CO - carbon monoxide
H_2S - hydrogen sulfide
H_2SO_4 - sulfuric acid
MSS - Maintenance, Startup and Shutdown
NH_3 - ammonia
NO_X - total oxides of nitrogen
PM - total particulate matter, suspended in the atmosphere, including PM_{10} and $PM_{2.5}$, as represented
PM_{10} - total particulate matter equal to or less than 10 microns in diameter, including $PM_{2.5}$, as represented
$PM_{2.5}$ - particulate matter equal to or less than 2.5 microns in diameter
SO_2 - sulfur dioxide
VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
(4) Compliance with annual emission limits (tons per year) is based on a 12-month rolling period.
(5) Emission rate is an estimate and is enforceable through compliance with the applicable special condition(s) and permit application representations.
(6) These interim limits are in effect until the earlier of completion of installation of low-NO_X burners or December 31, 2014.
(7) These limits become effective on the earlier of completion of installation of low-NO_X burners being installed or January 1, 2015.

Date: September 28, 2015