

Emission Sources - Maximum Allowable Emission Rates

Permit Number 7715

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities, sources, and related activities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

Air Contaminants Data

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates (7)	
			lbs/hour	TPY (4)
01	Low Purity Storage Stock Pile (5)	PM	--	1.09
		PM ₁₀	--	0.54
		PM _{2.5}	--	0.54
02	Secondary Crusher Baghouse Stack	PM	0.69	3.00
		PM ₁₀	0.69	3.00
		PM _{2.5}	0.69	3.00
03	No. 4 Raymond Mill Baghouse Stack	PM	0.77	3.38
		PM ₁₀	0.77	3.38
		PM _{2.5}	0.77	3.38
		SO ₂	<0.01	0.01
		NO _x	0.49	2.15
		CO	0.41	1.80
		VOC	0.03	0.12
		Formaldehyde (6)	<0.01	<0.01
04	No. 2 Raymond Mill Baghouse Stack	PM	0.73	3.19
		PM ₁₀	0.73	3.19
		PM _{2.5}	0.73	3.19
		SO ₂	<0.01	0.01
		NO _x	0.20	0.86
		CO	0.16	0.72
		VOC	0.01	0.05
		Formaldehyde (6)	<0.01	<0.01

Emission Sources - Maximum Allowable Emission Rates

05	No. 3 Raymond Mill Baghouse Stack	PM	1.03	4.51
		PM ₁₀	1.03	4.51
		PM _{2.5}	1.03	4.51
		SO ₂	<0.01	0.01
		NO _x	0.20	0.86
		CO	0.16	0.72
		VOC	0.01	0.05
		Formaldehyde (6)	<0.01	<0.01
06A	No. 5 Raymond Mill Baghouse Stack	PM	0.77	3.38
		PM ₁₀	0.77	3.38
		PM _{2.5}	0.77	3.38
		SO ₂	<0.01	0.01
		NO _x	0.49	2.15
		CO	0.41	1.80
		VOC	0.03	0.12
		Formaldehyde (6)	<0.01	<0.01
06B	Williams Mill Baghouse Stack	PM	1.05	4.59
		PM ₁₀	1.05	4.59
		PM _{2.5}	1.05	4.59
		SO ₂	<0.01	0.03
		NO _x	1.18	5.15
		CO	0.99	4.33
		VOC	0.06	0.28
		Formaldehyde (6)	<0.01	<0.01

07	No. 1 Calcining Kettle Baghouse Stack	PM	0.60	2.63
		PM ₁₀	0.60	2.63
		PM _{2.5}	0.60	2.63

Emission Sources - Maximum Allowable Emission Rates

		SO ₂	<0.01	0.03
		NO _x	1.29	5.67
		CO	1.09	4.76
		VOC	0.07	0.31
		Formaldehyde (6)	<0.01	<0.01
07A	No. 2 Calcining Kettle Baghouse Stack	PM	0.60	2.63
		PM ₁₀	0.60	2.63
		PM _{2.5}	0.60	2.63
		SO ₂	<0.01	0.03
		NO _x	1.18	5.15
		CO	0.99	4.33
		VOC	0.06	0.28
		Formaldehyde (6)	<0.01	<0.01
08	No. 3 Calcining Kettle Baghouse Stack	PM	0.60	2.63
		PM ₁₀	0.60	2.63
		PM _{2.5}	0.60	2.63
		SO ₂	<0.01	0.03
		NO _x	1.18	5.15
		CO	0.99	4.33
		VOC	0.06	0.28
		Formaldehyde (6)	<0.01	<0.01

09	No. 4 Calcining Kettle Baghouse Stack	PM	0.60	2.63
		PM ₁₀	0.60	2.63
		PM _{2.5}	0.60	2.63
		SO ₂	<0.01	0.03
		NO _x	1.18	5.15
		CO	0.99	4.33

Emission Sources - Maximum Allowable Emission Rates

10	Multi-Burner Refractory (MBR) Kettle Baghouse Stack	VOC	0.06	0.28
		Formaldehyde (6)	<0.01	<0.01
		PM	0.99	4.32
		PM ₁₀	0.99	4.32
		PM _{2.5}	0.99	4.32
		SO ₂	<0.01	0.06
		NO _x	2.21	9.66
		CO	1.85	8.12
		VOC	0.12	0.53
11	No. 6 Calcining Kettle Baghouse Stack	Formaldehyde (6)	<0.01	<0.01
		PM	0.94	4.13
		PM ₁₀	0.94	4.13
		PM _{2.5}	0.94	4.13
		SO ₂	<0.01	0.04
		NO _x	1.47	6.44
		CO	1.24	5.41
		VOC	0.08	0.35
		Formaldehyde (6)	<0.01	<0.01

12	No. 7 Calcining Kettle Baghouse Stack	PM	0.60	2.63
		PM ₁₀	0.60	2.63
		PM _{2.5}	0.60	2.63
		SO ₂	<0.01	0.03
		NO _x	1.29	5.67
		CO	1.09	4.76
		VOC	0.07	0.31
		Formaldehyde (6)	<0.01	<0.01
21	No. 2 Drying Kiln Exhaust Stack	PM	7.54	46.58

Emission Sources - Maximum Allowable Emission Rates

		PM ₁₀	7.54	46.58
		PM _{2.5}	7.54	46.58
		SO ₂	0.02	0.11
		NO _x	4.12	18.04
		CO	3.46	15.15
		VOC	12.44	65.57
		Formaldehyde (6)	3.04	9.73
66	No. 3 Drying Kiln Exhaust Stack	PM	29.72	46.58
		PM ₁₀	29.72	46.58
		PM _{2.5}	29.72	46.58
		SO ₂	0.09	0.38
		NO _x	14.31	62.69
		CO	12.02	52.66
		VOC	49.25	65.57
21 & 66	Total Annual Emissions from Nos. 2 and 3 Drying Kilns	Formaldehyde (6)	12.16	9.73
		PM	--	46.58
		PM ₁₀	--	46.58
		PM _{2.5}	--	46.58
		VOC	--	65.57
27	No. 2 Silo Baghouse Stack	Formaldehyde (6)	--	9.73
		PM	0.26	1.13
		PM ₁₀	0.26	1.13
28	No. 2 End Sawing Equipment Baghouse Stack	PM _{2.5}	0.26	1.13
		PM	0.43	1.88
		PM ₁₀	0.43	1.88
31	Primary Crushing/Screening (5)	PM _{2.5}	0.43	1.88
		PM	0.05	0.47
		PM ₁₀	0.05	0.22
40	Rock Loading (5)	PM _{2.5}	0.05	0.22
		PM	0.01	0.06
		PM ₁₀	0.01	0.03

Emission Sources - Maximum Allowable Emission Rates

		PM _{2.5}	0.01	0.03
43	Cut Back Saw Baghouse Stack	PM	0.26	1.13
		PM ₁₀	0.26	1.13
		PM _{2.5}	0.26	1.13
47	Sluter Machine Baghouse Stack	PM	0.51	2.25
		PM ₁₀	0.51	2.25
		PM _{2.5}	0.51	2.25
59	Primary Storage Pile (5)	PM	0.03	0.30
		PM ₁₀	0.03	0.15
		PM _{2.5}	0.03	0.15
60	Gypsum Storage Pile (5)	PM	0.03	0.29
		PM ₁₀	0.03	0.14
		PM _{2.5}	0.03	0.14
62	Calcined Gypsum Storage Silo Baghouse Stack	PM	0.44	1.93
		PM ₁₀	0.44	1.93
		PM _{2.5}	0.44	1.93

63B	Starch Silo Baghouse Stack	PM	0.10	0.45
		PM ₁₀	0.10	0.45
		PM _{2.5}	0.10	0.45
65	No. 3 End Sawing Equipment Baghouse Stack	PM	0.86	3.75
		PM ₁₀	0.86	3.75
		PM _{2.5}	0.86	3.75
67	Stucco System Baghouse Stack	PM	0.43	1.88
		PM ₁₀	0.43	1.88
		PM _{2.5}	0.43	1.88
69	Plant Liquified Petroleum Gas (LPG) Tank (1,000 gallon capacity)	VOC	<0.01	<0.01
70	Plant Diesel Tank (1,000 gallon capacity)	VOC	0.03	<0.01
71	Quarry Gasoline Tank (1,000 gallon capacity)	VOC	9.26	0.22
72	Quarry Small Diesel Tank (300 gallon capacity)	VOC	0.02	<0.01

Emission Sources - Maximum Allowable Emission Rates

73	Quarry Bulk Diesel Tank (15,200 gallon capacity)	VOC	0.38	<0.01
74	Plant Gasoline Tank (1,000 gallon capacity)	VOC	9.26	0.18
75	No. 2 Heat Resistant Accelerator (HRA) Ball Mill Baghouse Stack	PM	0.09	0.38
		PM ₁₀	0.09	0.38
		PM _{2.5}	0.09	0.38
76	No. 2 Ball Mill Landplaster Bin Baghouse Stack	PM	0.05	0.23
		PM ₁₀	0.05	0.23
		PM _{2.5}	0.05	0.23
77	Starch Bulk Hopper Baghouse Stack	PM	0.04	0.19
		PM ₁₀	0.04	0.19
		PM _{2.5}	0.04	0.19
78	Starch Bulk Storage Silo Baghouse Stack	PM	0.12	0.53
		PM ₁₀	0.12	0.53
		PM _{2.5}	0.12	0.53
79	Semi-Bulk Flyash Receiver Baghouse Stack	PM	0.03	0.13
		PM ₁₀	0.03	0.13
		PM _{2.5}	0.03	0.13
80	Glass Mat Tile Backer Dryer Oven Exhaust Stack	PM	0.03	0.15
		PM ₁₀	0.03	0.15
		PM _{2.5}	0.03	0.15
		SO ₂	<0.01	0.01
		NO _x	0.54	2.37
		CO	0.68	2.96
		VOC	0.29	1.28
		Formaldehyde (6)	<0.01	<0.01
81	Flyash Storage Bin Baghouse Stack	PM	0.01	0.06
		PM ₁₀	0.01	0.06
		PM _{2.5}	0.01	0.06
82	Dry Fiber System Baghouse Stack	PM	0.26	1.13
		PM ₁₀	0.26	1.13

Emission Sources - Maximum Allowable Emission Rates

		PM _{2.5}	0.26	1.13
--	--	-------------------	------	------

- (1) Emission point identification - either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources, use area name or fugitive source name.
- (3) VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
 - NO_x - total oxides of nitrogen
 - SO₂ - sulfur dioxide
 - PM - total particulate matter, suspended in the atmosphere, including PM₁₀ and PM_{2.5}, as represented
 - PM₁₀ - total particulate matter equal to or less than 10 microns in diameter, including PM_{2.5}, as represented
 - PM_{2.5} - particulate matter equal to or less than 2.5 microns in diameter
 - CO - carbon monoxide
- (4) Compliance with annual emission limits (tons per year) is based on a 12 month rolling period.
- (5) Emission rate is an estimate and is enforceable through compliance with the applicable special condition(s) and permit application representations.

Emission Sources - Maximum Allowable Emission Rates

- (6) The combination of all Hazardous Air Pollutants (HAPs) shall not exceed 25 tons per year (tpy) and the facility shall emit less than 10 tpy of a single HAP.
- (7) Planned startup and shutdown emissions are included for all sources, as well as planned maintenance activities identified as part of permit application dated July 2013.

Date: February 24, 2014