

Emission Sources - Maximum Allowable Emission Rates

Permit Number 43652

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities, sources, and related activities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

Air Contaminants Data

| Emission Point No. (1) | Source Name (2) | Air Contaminant Name (3) | Emission Rates | |
|---|--|--|----------------|---------|
| | | | lbs/hour | TPY (4) |
| DC1 | Product Finishing Dust Collector # 1 | PM/PM ₁₀ /PM _{2.5} | 0.11 | 0.35 |
| DC3 | Product Finishing Dust Collector # 3 | PM/PM ₁₀ /PM _{2.5} | 2.14 | 7.02 |
| DC4 | Product Finishing Dust Collector # 4 | PM/PM ₁₀ /PM _{2.5} | 0.72 | 2.36 |
| DC5 | Product Finishing Dust Collector # 5 | PM/PM ₁₀ /PM _{2.5} | 2.14 | 7.02 |
| DC6 | Phthalic Anhydride/ Alicyclic Anhydride Dust Collector # 6 | Phthalic Anhydride PM/PM ₁₀ /PM _{2.5} | < 0.01 | 0.02 |
| | | Alicyclic Anhydride (VOC) | < 0.01 | < 0.01 |
| DC7 | Silica Silo # 1 Dust Collector # 7 | PM/PM ₁₀ /PM _{2.5} | 0.16 | 0.52 |
| DC8 | Silica Silo # 2 Dust Collector # 8 | PM/PM ₁₀ /PM _{2.5} | 0.09 | 0.28 |
| DC11 | Silica Silo # 3 Dust Collector # 11 | PM/PM ₁₀ | 0.12 | 0.08 |
| | | PM _{2.5} | 0.02 | 0.01 |
| DC12 | Silica Silo # 4 Dust Collector # 12 | PM/PM ₁₀ | 0.12 | 0.08 |
| | | PM _{2.5} | < 0.01 | < 0.01 |
| FUG1 | Building Fugitives | VOC | 19.80 | 40.64 |
| | | Exempt Solvent | 7.63 | 14.84 |
| S3 - S5, S12, S16 - S20, and S23 - S24 | Gel Ovens #1-15 | VOC | 0.53 | 2.11 |
| | | Phthalic Anhydride (PM) | 0.27 | 1.07 |

Emission Sources - Maximum Allowable Emission Rates

| | | | | |
|-------------------------|--|--|--------|---------|
| S3 - S20, and S23 - S25 | Gel Ovens #1-15, Cure Ovens #1-9, Sink Ovens #1-7, Small Parts Ovens, and Trough Ovens | NO _x (combustion) | 0.61 | 2.45 |
| | | CO (combustion) | 0.51 | 2.06 |
| | | SO ₂ (combustion) | < 0.01 | 0.01 |
| | | VOC (combustion) | 0.03 | 0.13 |
| | | PM/PM ₁₀ /PM _{2.5} (combustion) | 0.05 | 0.19 |
| All | Site-Wide | Single HAP | | < 10.00 |
| | | Total HAPs | | < 25.00 |

- (1) Emission point identification - either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources, use area name or fugitive source name.
- (3) Exempt Solvent - Those carbon compounds or mixtures of carbon compounds used as solvents which have been excluded from the definition of volatile organic compound
- VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
 - NO_x - total oxides of nitrogen
 - SO₂ - sulfur dioxide
 - PM - total particulate matter, suspended in the atmosphere, including PM₁₀ and PM_{2.5},
 - PM₁₀ - total particulate matter equal to or less than 10 microns in diameter, including PM_{2.5},
 - PM_{2.5} - particulate matter equal to or less than 2.5 microns in diameter
 - CO - carbon monoxide
 - HAP - hazardous air pollutant as listed in § 112(b) of the Federal Clean Air Act or Title 40 Code of Federal Regulations Part 63, Subpart C
- (4) Compliance with annual emission limits (tons per year) is based on a 12 month rolling period.

Date: April 4, 2012