

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Permit Number 23271

[419705] Draft!!!!

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
16STK-001	Hydrogen Reformer Stack	CO	14.40	63.07
		NH ₃	0.55	2.40
		NO _x	10.80	47.30
		PM	1.30	5.71
		SO ₂	0.03	0.11
		VOC	0.94	4.13
16VNT-002	Amine Stripper Vent	CO	7.17	29.88
04FUG	Fugitives (4)	Boric Acid	0.01	0.01
		CO	0.01	0.01
		NH ₃	0.36	1.59
		VOC	9.74	42.09
04LRC-006	Railcar Loading Scrubber Emissions Scrubber	VOC	2.88	0.17
04LRC-006F	Railcar Loading Uncaptured Emissions	VOC	2.88	0.17
04VNT-013	Refining System Vent	NH ₃	1.14	5.01
		VOC	0.35	1.55
04LTR-018	Truck Loading Scrubber Emissions	NH ₃	5.36	0.34
		VOC	10.28	0.50
04LTR-018F	Truck Loading Uncaptured Emissions	NH ₃	1.39	0.09
		VOC	2.03	0.12
04TFX-020	North DCH Tanks Breather Pot	NH ₃	0.06	0.01
		VOC	15.19	2.17
04TFX-021	South DCH Tank Breather Pot	VOC	1.40	0.08

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
04TVS-023	HMD Blend Tanks A-D Breather Pots	VOC	0.22	0.08
04TFX-025	"F" Crude DCH Tank Breather Pot	NH ₃	0.08	0.02
		VOC	15.19	3.55
04TFX-028	"A" Refined Tank Breather Pot	VOC	0.10	0.01
04TFX-029	"B" Refined Tank Breather Pot	VOC	0.10	0.01
Combined emissions from EPNs 04TFX-028 and 04TFX-029 shall not exceed		VOC	0.16	0.02
04FLR-032	Diamine Flare (HMD Flare) (Normal Operation Only)	CO	71.77	67.93
		H ₂ S	0.19	0.01
		NH ₃	19.48	31.55
		NO _x	14.58	17.18
		SO ₂	17.56	0.11
		VOC	12.03	6.75
04FLR-032	Diamine Flare (HMD Flare) (Maintenance, Startup, and Shutdown [MSS] Activities Only)	CO	10.53	0.27
		NH₃	1.79	0.03
		NO_x	3.74	0.09
		VOC	20.87	0.55
04TVS-033	Co-Product Storage Tanks A - E Breather Pot	VOC	13.41	0.73
04TVS-034	Crude HMD Tanks A and B	NH ₃	3.53	23.99
		VOC	1.18	4.37
04CWA-035	Cooling Basin (4)	NH ₃	0.34	1.49
		VOC	1.84	8.08
04TFX-508	HMD Permeate Tank	NH ₃	0.16	0.09
		VOC	0.01	0.01

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
04TFX-506	Aqueous Waste Tank	NH ₃	6.96	0.02
		VOC	0.01	0.01
04LBA-006A	Barge Loading Scrubber Emissions	VOC	0.06	0.09
04LBA-006F	Barge Loading Uncaptured Emissions	VOC	0.06	0.09
16TFX006	MDEA Tank	VOC	0.16	0.01
16TFX005	MDEA Tank	VOC	0.13	0.01
04LDR022C	Drum loading of crude HMI	NH ₃	0.11	0.01
		VOC	0.10	0.01
04DGR001	HMD Maintenance Degreaser Area	VOC	0.36	0.33
16VNT-004	Hydrogen Plant Vent (MSS)	CO	466.88	10.55
		VOC	106.54	3.41
04VNT-007	Synthesis Process Vent	NH ₃	0.02	0.01
04VNT-007	Synthesis Process Vent (MSS)	NH ₃	6.75	0.01
		VOC	0.02	0.01
04VNT-009	Refining Process Vent (MSS)	NH ₃	0.38	0.01
		VOC	0.01	0.01
04VNT-010	Foreshots Column Vent (MSS)	NH ₃	1.32	0.09
		VOC	0.37	0.03
04FLR-032	Diamine Flare (HMD Flare) (MSS)	CO	0.25	0.01
		NH ₃	1.19	0.01
		NO _x	0.33	0.01

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
04TANKOPEN	Tank Depressure (MSS)	NH ₃	6.31	0.01
		VOC	2.24	0.02
04FUG-MSS	Fugitive Emissions (MSS)	NH ₃	2.87	0.09
		PM/PM ₁₀	0.20	0.01
		VOC	17.84	1.35
04SWT-002	Flushing N112 Unloading Line to Sump	VOC	0.01	0.01
11LTR-067F	WOTL Uncaptured Emissions	VOC	0.47	0.01
10LRC-074F	ADN LBW Loading Uncaptured Emissions	NH ₃	0.01	0.01
		VOC	0.29	0.26
04LDR-022D	Drum Loading Refined HMI	VOC	0.09	0.01
04LDR-036B	Drum Loading Crude MGN	VOC	0.01	0.01
04LDR-037B	Drum Loading Refined MGN	VOC	0.01	0.01
04LDR-025B	Drum Loading Crude DCH	NH ₃	0.01	0.01
		VOC	0.07	0.01
04LDR-020B	Drum Loading Refined DCH	VOC	0.01	0.01
04LDR-028B	Drum Loading Refined HMD	VOC	0.02	0.01
04LDR-033D	Drum Loading BHMT	VOC	0.03	0.01

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
04SEP-001	Oil/Sand Separator	NH ₃	3.14	3.28
		VOC	0.01	0.01
11TFX-354	SELF Leachate Tank A	NH ₃	0.01	0.01
		VOC	0.01	0.01
11TFX-355	SELF Leachate Tank B	NH ₃	0.01	0.01
		VOC	0.01	0.01
11TFX-356	SELF Leachate Tank C	NH ₃	0.01	0.01
		VOC	0.01	0.01
11TFX-357	SELF Leachate Loading	NH ₃	0.01	0.01
		VOC	0.01	0.01

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

- (1) Emission point identification - either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources use area name or fugitive source name.
- (3)
 - CO - carbon monoxide
 - H₂S - hydrogen sulfide
 - NH₃ - ammonia
 - NO_x - total oxides of nitrogen
 - PM - particulate matter, suspended in the atmosphere, including PM₁₀
 - PM₁₀ - particulate matter equal to or less than 10 microns in diameter
 - SO₂ - sulfur dioxide
 - VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
- (4) Emission rate is an estimate and compliance is demonstrated by meeting the requirements of the applicable special conditions and permit application representations.

* Emission rates are based on and the facilities are limited by the following maximum operating schedule:

Hrs/day___Days/week___Weeks/year___or Hrs/year 8,760

** Compliance with annual emission limits is based on a rolling 12-month period.

Dated: