EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Permit No. 19641

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

AIR CONTAMINANTS DATA

Emission *	Source	Air Contaminant	<u>Emission</u>	Rates
Point No. (1)	Name (2)	Name (3)1b/hr	-	TPY
FE37	Scrubber (T-E-107)	VOC	0.15	0.02
FE35	Scrubber (T-E-15)	VOC	0.04	0.03
FE41	Scrubber (T-E-15/24)	VOC	0.48	0.14
FE42	Scrubber (T-E-74/75/11	6) VOC	0.82	0.30
TB1	T-B-1	VOC	0.30	0.017
TB7	T-B-7	VOC	0.30	0.017
TB21	T-B-21	VOC	<0.01	<0.01
TB22	T-B-22	VOC	<0.01	<0.01
TC5	T-C-5	VOC	<0.01	<0.01
TC42	T-C-42	VOC	0.50	0.50
TC43	T-C-43	VOC	0.05	0.05
TE10	T-E-10	VOC	0.07	0.07
TE16	T-E-16	VOC	0.07	0.07
TE17	T-E-17	VOC	0.10	0.10

Permit No. 19641 Page 2

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES AIR CONTAMINANTS DATA

Emission	Source	Air Contaminant	<u>Emission Rates</u>
<u>*</u> Point No. (1)	Name (2)	Name (3)1b/hr	TPY
TE21	T-E-21	VOC	0.10 0.10
TE29	T-E-29	VOC	0.02 0.02
TE55	T-E-55	VOC	0.01 0.01
TE56	T-E-56	VOC	0.02 0.02
TE62	T-E-62	VOC	0.01 0.01
TE76	T-E-76	VOC	0.01 0.01
TE113	T-E-113	VOC	0.09 0.09
TE114	T-E-114	VOC	0.01 0.01
TE115	T-E-115	VOC	0.01 0.01
TE117	T-E-117	VOC	0.11 0.01
TE118	T-E-118	VOC	0.17 0.17
TE126	T-E-126	VOC	0.85 0.24
HC1	H-C-1 CO	NO _x 0.30	0.90 3.90 1.30
EA/EDA	Fugitives (4)	VOC	0.84 3.70
TK3	Fugitives (4)	VOC	0.41 1.80
TK9	Fugitives (4)	VOC	0.41 1.80
TK10	Fugitives (T-E-126) (4)) VOC	0.07 0.30

Permit No. 19641 Page 3

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES AIR CONTAMINANTS DATA

Emission	Source	Air Contaminant	<u>Emiss</u>	ion Rates
* Point No. (1)	Name (2)	Name (3)1b/hr		TPY
JAU3	Fugitives (4)	VOC NH₃	0.83 0.20	0.36 0.88
TB16	Rundown Tank	VOC	<0.01	<0.01
TB18	Rundown Tank	VOC	<0.01	<0.01
TB19	Carbonate Catalyst Tan	k VOC	0.01	0.01
TB20	Carbonate Catalyst Tan	k VOC	0.01	0.01
TE11	Product Storage Tank	VOC	0.09	0.01
TE12	Product Storage Tank	VOC	0.09	0.01
TE25	Product Storage Tank	VOC	0.03	<0.01
TE26	Product Storage Tank	VOC	0.03	<0.01
LD1	Product Loading (5)	VOC	0.15	0.13
LD2	Product Loading (5)	VOC	0.15	0.13
LD3	Product Loading (5)	VOC	0.15	0.13
TRUCK	Truck Loading Rack (8)	VOC	0.26	0.03
RAIL	Rail Loading Rack (8)	VOC	0.26	0.03
AMU	Process Fugitives (4)	VOC	0.86	3.77
CARB	Process Fugitives (4)	VOC	0.45	1.98
	Process Fugitives (4,	6) VOC	0.47	2.06

Permit No. 19641 Page 4

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

AIR CONTAMINANTS DATA

Emission *	Source	Air Contaminant	<u>Emissic</u>	on Rates
Point No. (1)	Name (2)	Name (3)1b/hr		TPY
CARB2	Process Fugitives (4)	PO PC	0.03 0.21	0.13 0.94
TK1	TE-11, 12 Fugitives (4	·) VOC	0.10	0.42
TK3 UC1	TE-25, 26 Fugitives (4 Cooling Tower (7)	VOC VOC NH ₃	0.08 1.53 1.00	0.37 6.00 4.38
UC678	Cooling Tower	VOC	3.00	2.21
RA22	Plant Flare	VOC VOC (6) NH_3 NO_x CO CO (6)	1.49 1.51 0.58 0.11 0.94 0.94	2.34 2.42 0.26 0.26 2.26 2.27
RF60	Flare	VOC NO _x CO HBr	0.41 0.09 0.77 0.29	0.72 0.35 3.02 0.65
RE22	Loading Incinerator	VOC NOx CO PM SO ₂	0.93 0.58 0.12 0.07 <0.01	0.21 2.60 0.53 0.30 0.02

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

(1)	Emission point identification - either specific equipment
(2)	designation or emission point number from plot plan. Specific point source name. For fugitive sources use
` '	name or fugitive source name.
(3)	VOC - volatile organic compounds
as def	fined in General Rule 101.1
NO_{\times}	- total oxides of nitrogen
CO	- carbon monoxide
PM	- particulate matter
NH ₃	- anhydrous ammonia

- propylene oxide - propylene carbonate PC HBr - hydrogen bromide
- sulfur dioxide SO₂

P0

- (4) Fugitive emissions are an estimate only and should not be considered as a maximum allowable emission rate.
- Maximum combined annual emissions from Emission Point Nos. LD1, LD2, and LD3 shall not exceed 0.13 TPY.
- Maximum allowable emission rate after FB-47 and FB-34 Evaporator (6) Overheads are routed to the Plant Flare (EPN RA-22) as required by Special Condition No. 15.
- Maximum allowable emission rate prior to routing FB-47 and FB-34 (7) Evaporator Overheads to the Plant Flare (EPN RA-22) as required by Special Condition No. 15. This will not be an emission point after that date.
- (8) The combined emission rates from these two emission points shall not exceed 0.26 lb/hr or 0.03 TPY.

*	Emission	rates	are	based	on	and	the	facilities	are	limited	by	the
follo	owing maxi	imum op	erat	ing sc	hed	ule:						

Hrs/day		Days/week	Weeks/year
or Hrs/vear	8.760		

Permit No. 19641 Page 5

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

	_	
D^{-}	ted	
אנו	160	