

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Permit Number 556A

[392150] DRAFT!!!

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

AIR CONTAMINANTS DATA

| Emission Point No. (1) | Source Name (2) | Air Contaminant Name (3) | Emission Rates * | |
|----------------------------|-------------------------------------|---------------------------------|------------------|-------------|
| | | | lb/hr | TPY** |
| HYP-DRY 01-09 | Basement Exhaust Stacks (5) | VOC | 67.41 | 68.80 |
| | | VOC (5) | 50.00 | |
| HYP-DRY 01-09 (MSS) | MSS Basement Exhaust Stacks | VOC | 25.00 | 0.93 |
| HYP-ADS 112 | Carbon Adsorption System | Cl ₂ | 2.10 | 3.10 |
| | | CO | 24.42 | 54.40 |
| | | HCl | 3.60 | 5.30 |
| | | VOC | 60.00 | 159.00 |
| HYP-ADS 112 (MSS) | MSS Carbon Adsorption System | Cl₂ | 0.01 | 0.09 |
| | | CO | 24.79 | 1.48 |
| | | HCl | 0.03 | 0.17 |
| | | VOC | 35.06 | 1.45 |
| HYP-FUG | Fugitives (4) | Cl ₂ | 0.29 | 1.31 |
| | | HCl | 0.19 | 0.81 |
| | | SO ₂ | 0.30 | 1.32 |
| | | SO ₂ Cl ₂ | 0.48 | 2.11 |
| | | VOC | 3.21 | 14.03 |
| HYP-CLT117 | Cooling Tower (6) | PM | 0.23 | 0.61 |
| | | VOC | 0.54 | 1.57 |
| HYP-LABDD | Lab Drum Dryer (6) | VOC | 3.00 | 4.51 |
| HYP-RXVNT | Reactor Cyclone Vents | VOC | 5.91 | 14.16 |
| HYP-BLW338 | Acid Waste Treatment Vent | Cl ₂ | 0.10 | 0.45 |
| | | SO ₂ | 0.01 | 0.01 |

Permit Number 556A

Page 2

| | | | | |
|----------------|---------------------------------------|-------------------------------------|-------------|-------------|
| HYP-STK401 | Propylene Glycol Tank | VOC | 0.08 | 0.01 |
| HYP-MSS | Hypalon Maintenance Activities | Cl₂ | 0.04 | 0.01 |
| | | SO₂ | 0.02 | 0.01 |
| | | SO₂Cl₂ | 0.03 | 0.01 |
| | | VOC | 2.50 | 0.14 |

- (1) Emission point identification - either specific equipment designation or emission point number (EPN) from plot plan.
- (2) Specific point source names. For fugitive sources use area name or fugitive source name.
- (3) Cl₂ - chlorine
CO - carbon monoxide
HCl - hydrogen chloride
PM - particulate matter, suspended in the atmosphere, including PM₁₀
PM₁₀ - particulate matter equal to or less than 10 microns in diameter. Where PM is not listed, it shall be assumed that no PM greater than 10 microns is emitted.
SO₂ - sulfur dioxide
SO₂Cl₂ - sulfuryl chloride
VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
- (4) Emission rate is an estimate and is enforceable through compliance with the applicable special condition(s) and permit application representations.
- (5) The Basement Exhaust Stacks (EPN HYP-DRY 01-09) shall be limited to 50.0 pounds per hour of VOC averaged over a 24-hour period.
- (6) The permit by rule (PBR) which originally authorized this source and these emissions is consolidated by reference into this permit. The PBR will remain in effect. The emissions shown here have been evaluated for health effects. The source has not been evaluated for conformance with best available control technology guidelines.

* Emission rates are based on and the facilities are limited by the following maximum operating schedule:

___ Hrs/day ___ Days/week ___ Weeks/year or 8,760 Hrs/year

** Compliance with annual emission limits is based on a rolling 12-month period.