

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Permit Number 23279

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY
1	Baghouse Stack	PM ₁₀	15.28	10.59
		VOC (a)	12.60	7.00
		VOC (b)	250.00	25.00
		VOC (c)	20.00	1.47
		NO _x	16.20	9.00
		SO ₂	19.17	12.15
		CO	17.10	9.50
2	Stockpile Fugitives (4)	PM	---	4.12
		PM ₁₀	---	1.99
		VOC (b)	4.20	5.00
3	Material Handling (4)	PM	36.19	24.02
		PM ₁₀	1.39	0.93
4	Lime Storage Silo Baghouse	PM ₁₀	0.05	0.01
5	Hot Mix Storage Silo (4)	PM ₁₀	0.24	0.13
		VOC	4.48	2.49
		CO	0.43	0.24
6	Truck Load Out (4)	PM ₁₀	0.21	0.11
		VOC	1.44	0.80
		CO	0.50	0.28

(1) Emission point identification - either specific equipment designation or emission point number from a plot plan.

(2) Specific point source names. For fugitive sources use area name or fugitive source names.

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

- (3) PM - particulate matter, suspended in the atmosphere, including PM₁₀
PM₁₀ - particulate matter equal to or less than 10 microns in diameter. Where PM is not listed, it shall be assumed that no particulate matter greater than 10 microns is emitted.
VOC (a) - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1, mainly asphalt vapors
VOC (b) - primarily diesel or kerosene vapors
VOC (c) - additional VOC due to the use of crumb rubber
NO_x - total oxides of nitrogen
SO₂ - sulfur dioxide
CO - carbon monoxide
(4) Fugitive emissions are an estimate only.

- * Emission rates are based on and the facilities are limited by the following maximum operating schedule and production rates:

24 Hrs/day 7 Days/week 52 Weeks/year or 8,736 Hrs/year

Standard Hot Mix: Tons/hour 450, Tons/year 500,000

Standard Hot Mix w/Rubber: Tons/hour 170, Tons/year 25,000

Emulsion Cold Mix: Tons/hour 270, Tons/year 20,000

Cold Mix w/Cutback: Tons/hour 250, Tons/day 2,000, Tons/year 50,000

Dated August 8, 2002