Permit Number 169574

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities, sources, and related activities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

Air Contaminants Data

| Emission Point No. (1) | | Air Contaminant Name (3) | Emission Rates (6) | |
|-------------------------|---|--------------------------|--------------------|---------|
| Limbolon Follit No. (1) | | | lbs/hour | TPY (4) |
| FTP-1 (Routine) | Melt Shop Electric Arc Furnace Baghouse (Routine Emissions) | NO _X | 14.91 | 53.00 |
| | | со | 196.91 | 700.00 |
| | | SO ₂ | 29.54 | 105.00 |
| | | voc | 14.77 | 52.50 |
| | | РМ | 5.91 | 21.00 |
| | | PM ₁₀ | 9.28 | 33.00 |
| | | PM _{2.5} | 9.28 | 33.00 |
| | | Pb | 0.02 | 0.08 |
| | | F | 2.90 | 10.33 |
| FTP-1 (MSS) | Melt Shop Electric Arc Furnace Baghouse | NO _X | 18.99 | - |
| | (MSS Emissions) | СО | 221.52 | - |
| | | SO ₂ | 31.79 | - |
| | | voc | 18.99 | - |
| | | РМ | 5.91 | - |
| | | PM ₁₀ | 9.28 | - |
| | | PM _{2.5} | 9.28 | - |
| | | Pb | 0.02 | - |
| | | F | 2.90 | - |
| MELTGEN | Melt Shop General | NO _X | 0.05 | 0.17 |
| | | СО | 0.26 | 0.92 |
| | | SO ₂ | 0.03 | 0.09 |
| | | voc | 0.02 | 0.08 |
| | | РМ | 0.25 | 0.87 |
| | | PM ₁₀ | 0.23 | 0.83 |

| | | PM _{2.5} | 0.23 | 0.83 |
|-------------|-------------------------------|-------------------|-------|-------|
| | | Pb | <0.01 | 0.01 |
| | | F | <0.01 | 0.01 |
| CASTVENT | Caster Vent Emissions | PM | 4.92 | 17.50 |
| | | PM ₁₀ | 3.89 | 13.85 |
| | | PM _{2.5} | 3.05 | 10.86 |
| CASTSPRAY | Caster Spray Chamber | РМ | 0.50 | 1.78 |
| | | PM ₁₀ | 0.14 | 0.48 |
| | | PM _{2.5} | 0.02 | 0.06 |
| ROLLING | Rolling Mill | РМ | 1.07 | 3.80 |
| | | PM ₁₀ | 1.13 | 4.01 |
| | | PM _{2.5} | 0.44 | 1.56 |
| | | Pb | <0.01 | <0.01 |
| | | F | <0.01 | 0.01 |
| SCRAPLOAD | Scrap Loading and Handling | РМ | 1.73 | 24.64 |
| | Hariding | PM ₁₀ | 0.85 | 12.04 |
| | | PM _{2.5} | 0.32 | 4.48 |
| SLAG | Slag Disposal | РМ | 0.22 | 0.96 |
| | | PM ₁₀ | 0.13 | 0.57 |
| | | PM _{2.5} | 0.32 | 4.48 |
| LADLEHEAT | Ladle Horizontal Preheater | NOx | 2.50 | 6.39 |
| | Preneater | со | 2.06 | 5.26 |
| | | SO2 | 0.02 | 0.04 |
| | | voc | 0.14 | 0.34 |
| | | РМ | 0.05 | 0.12 |
| | | PM ₁₀ | 0.05 | 0.12 |
| | | PM _{2.5} | 0.05 | 0.12 |
| Ladle Dryer | Ladle Vertical Dryer | NOx | 2.50 | 6.39 |
| | | со | 2.06 | 5.26 |

| 1 | ı | | | 1 |
|-----------|-------------------------------|-------------------|-------|-------|
| | | SO2 | 0.02 | 0.04 |
| | | voc | 0.14 | 0.34 |
| | | РМ | 0.05 | 0.12 |
| | | PM ₁₀ | 0.05 | 0.12 |
| | | PM _{2.5} | 0.05 | 0.12 |
| CCMEXIT | Service Cutting Torches | NOx | 0.13 | 0.10 |
| | Torches | со | 0.11 | 0.08 |
| | | SO2 | <0.01 | <0.01 |
| | | voc | <0.01 | <0.01 |
| | | PM | <0.01 | <0.01 |
| | | PM ₁₀ | <0.01 | <0.01 |
| | | PM _{2.5} | <0.01 | <0.01 |
| TUNDDRYER | Tundish Drying Station | NOx | 0.47 | 0.55 |
| | | со | 0.38 | 0.45 |
| | | SO2 | <0.01 | <0.01 |
| | | VOC | 0.03 | 0.03 |
| | | РМ | 0.01 | 0.01 |
| | | PM ₁₀ | 0.01 | 0.01 |
| | | PM _{2.5} | 0.01 | 0.01 |
| TUNDHEAT | Tundish Preheating Station | NOx | 0.93 | 0.51 |
| | Station | со | 0.77 | 0.42 |
| | | SO2 | <0.01 | <0.01 |
| | | VOC | 0.05 | 0.03 |
| | | PM | 0.02 | 0.01 |
| | | PM ₁₀ | 0.02 | 0.01 |
| | | PM _{2.5} | 0.02 | 0.01 |
| ENG-1 | Emergency Generator | NOx | 8.50 | 0.43 |
| | | СО | 2.85 | 0.14 |
| | | SO2 | 1.03 | 0.05 |

| | | VOC | 8.50 | 0.43 |
|---------------------------------|-------------------------|-------------------|------|-------|
| | | РМ | 0.17 | <0.01 |
| | | PM ₁₀ | 0.17 | <0.01 |
| | | PM _{2.5} | 0.17 | <0.01 |
| COOLTOWER | Cooling Tower | voc | 0.24 | 1.05 |
| | | РМ | 0.02 | 0.07 |
| | | PM ₁₀ | 0.02 | 0.07 |
| | | PM _{2.5} | 0.02 | 0.07 |
| All Emission Points at the Site | All Sources at the Site | Individual HAP | | <10 |
| | | Total HAPs | | <25 |

(1) Emission point identification - either specific equipment designation or emission point number from plot plan.

(2) Specific point source name. For fugitive sources, use area name or fugitive source name.

(3) VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1

NO_x - total oxides of nitrogen

SO₂ - sulfur dioxide

PM - total particulate matter, suspended in the atmosphere, including PM₁₀ and PM_{2.5}, as represented

PM₁₀ - total particulate matter equal to or less than 10 microns in diameter, including PM_{2.5}, as

represented

PM_{2.5} - particulate matter equal to or less than 2.5 microns in diameter

CO - carbon monoxide

Pb - lead F - fluorides

HAP - hazardous air pollutant as listed in § 112(b) of the Federal Clean Air Act or Title 40 Code of

Federal Regulations Part 63, Subpart C

(4) Compliance with annual emission limits (tons per year) is based on a 12 month rolling period.

(5) Emission rate is an estimate and is enforceable through compliance with the applicable special condition(s) and permit application representations.

(6) The allowable emission rates include planned maintenance, startup, and shutdown activities.

| Date: | Juna 28 2023 | |
|-------|--------------|--|