Permit No. 4196

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

AIR CONTAMINANTS DATA

Emission *	Source	Air Contaminant	<u>Emissio</u>	n Rates
Point No. (1)	Name (2)	Name (3)	lb/hr	<u>TPY</u>
251AV93	VA Tank	VOC	0.55	1.02
251AV93	VA Tank (5)	VOC	0.55	1.06
251AV199	VA Tank	VOC	0.81	0.49
251AV199	VA Tank (5)	VOC	0.81	0.55
251AV200	VA Tank	VOC	0.55	0.95
251AV200	VA Tank (5)	VOC	0.55	1.06
251AV644	VA Tank	VOC	0.55	0.98
251AV644	VA Tank (5)	VOC	0.55	1.06
251CV810	Acetic Acid Tank	VOC	24.00	12.80
251CV810	Acetic Acid Tank (5)	VOC	0.32	0.38
251CV812	VA Tank	VOC	0.83	1.65
251CV812	VA Tank (5)	VOC	0.53	1.01
110V212	VA Mix Tank (6)	VOC	8.59	0.82
110V212	VA Mix Tank (5)	VOC	2.86	0.93

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES AIR CONTAMINANTS DATA

Emission *	Source Ai	r Contaminant	<u>Emissi</u>	on Rates
Point No. (1)	Name (2)	Name (3)	1b/hr	TPY
110V240	VA Mix Tank (6)	VOC	5.89	0.18
110V240	VA Mix Tank (5)	VOC	1.96	0.25
110V806	VA Hold Tank (6)	VOC	4.80	0.73
110V806	VA Hold Tank (5)	VOC	1.60	0.84
110V807	VA Hold Tank (6)	VOC	4.80	0.03
110V807	VA Hold Tank (5)	VOC	1.60	0.03
251V809	Acetic Acid Seal Pot (6	5) VOC	13.97	3.56
251V809	Acetic Acid Seal Pot (5) VOC	0.97	0.40
110T22	VA Process Vent Scrubber	VOC	0.87	3.45
110T122	VA Hat Tray (7)	VOC	4.30	17.51
Area 7	API Separator (8)	VOC	56.72	229.29
110V905/6	Methane Guard (9) (10) Beds	VOC Benzene Toluene	13.37 0.44 0.59	13.04 0.43 0.57
303M1239	Ethylene Flare (11) Methane Guard Beds Inerts Purge (12) Acetaldehyde Vents (1	13)		
110F	Equipment Fugitives (4)) VOC	1.88	8.28
301M150	VA Cooling Tower (4)	VOC	0.31	1.36
251DTC	Wash Rack (14)	VOC	115.33	63.23

AIR CONTAMINANTS DATA

Emission	Source	Air Contaminant	<u>Emissio</u>	n Rates
<u>*</u> Point No. (1)	Name (2)	Name (3)	lb/hr	TPY
251DTC	Railcar Stingers	VOC	3.08	2.87
251DTC	Railcar Stingers (5)) VOC	1.53	0.23
251DM1205	Shipping Flare (15) Railcar Loading Tank Truck Loading Wash Rack	9		
251DBL	Barge Loading (16) Incinerator			
302M330/331/460	Plant Boilers (17) T-25, T-30, V903, T-29 OH/Residue I	nerts Purge		
110A0549	Vinyl Acetate Unit R29 Feed/Product Analyzer Vent	VOC	<0.01	0.03
110A6214	Vinyl Acetate Unit R29 Feed Analyzer Vent	VOC	<0.01	0.01
110A6479A	Vinyl Acetate Unit R29 Feed Analyzer Vent	VOC	0.03	0.12
110A6479B	Vinyl Acetate Unit R29 Feed Analyzer Vent	VOC	0.03	0.12
110A6479C	Vinyl Acetate Unit R29 Feed Analyzer Vent	VOC	0.03	0.12

AIR CONTAMINANTS DATA

Emission	Source	Air Contaminant	<u>Emissior</u>	n Rates
<u>*</u> Point No. (1)	Name (2)	Name (3)	lb/hr	TPY
110A6486A	Vinyl Acetate Unit R29 Product Analyzer Vent	VOC	0.03	0.11
110A6486B	Vinyl Acetate Unit R29 Product Analyzer Vent	VOC	0.03	0.11
110A8652	Vinyl Acetate Unit T123 Overhead Analyzer Vent	VOC	0.02	0.07
110A8654	Vinyl Acetate Unit T123 Overhead Analyzer Vent	VOC	0.03	0.14
110A10354	Vinyl Acetate Unit V801 Recycle Analyzer Vent	VOC	<0.01	0.02
110ABLDG2	Vinyl Acetate Unit Building 2 Analyzer Vent	VOC	0.14	0.61

(1)	Emission point identification - either specific equipment designation or emission point number (EPN) from plot plan.
(2)	Specific point source name. For fugitive sources, use
(2)	area name or fugitive source name.
(3)	VOC - volatile organic compounds as defined in TNRCC Rule 101.1
	Fugitive emissions are an estimate only and should not be
(4)	considered as a maximum allowable emission rate.
(5)	Emission allowables after all actions required in Special
	Condition Nos. 7, 8, 9, 10, 11, 12, 13, and 14 are completed.
(6)	Emissions from EPNs 110V212, 110V240, 110V806, 110V807,
	and 251V809 shall be reduced or controlled prior to the
	production increase authorized in Special Condition No. 5 or
	no later than November 1, 1995, whichever occurs first.
(7)	Emissions from EPN 110T122 (Vinyl Acetate Hat Tray) shall
	be eliminated by June 1, 1996.
(8)	Emissions from EPN Area 7 (API Separator) shall be
	eliminated no later than June 1, 1996.
(9)	Emissions from EPN 110V905/6 (Methane Guard Beds) shall
	be routed to the Ethylene Flare, EPN 303M1239, (Permit No.
	2447) prior to the production increase authorized by Special
44.65	Condition No. 5 or by March 1, 1995, whichever occurs first.
(10)	VOC emissions represent total VOC emissions; therefore,
(11)	speciated and VOC limits are not additive.
(11)	Emissions from EPN 303M1239 (Ethylene Flare) are in
(12)	Permit No. 2447.
(12)	The inerts purge stream which currently vents to EPN 303M1239 (Ethylene Flare) shall be routed to the plant boilers
	in Permit No. 2175 prior to the production increase authorized
	by Special Condition No. 5 or no later than March 1, 1995,
	whichever occurs first.
(13)	Vinyl Acetate emissions from Acetaldehyde Sphere Vents
(=3)	V89, V90, V91, and V92, T-25 Overhead Receiver V-874 and T-29
	Overhead Receiver V-698 vent to the Ethylene Flare (EPN
	303M1239) in Permit No. 2447.
(14)	Uncontrolled Vinyl Acetate emissions from the Wash Rack
	(EPN 251DTC) shall be routed to the Shipping Flare, EPN
	251DM1205 (Permit No. 4449), prior to the production increase
	authorized by Special Condition No. 5 or by March 1, 1995,
	whichever occurs first.
(15)	Railcar, tank truck, and wash rack emissions are routed
	to the Shipping Flare (EPN 251DM1205) in Permit No. 4449.

EMISSION	SOURCES	_	MAXTMIM	ALLOWABLE	EMISSION	RATES
LIJI J J T OI I	JUUNCEJ		I.IVVXTI.IOI.I		LIJTOJION	$1 \times 7 \times 2$

(16	
(17	Incinerator (EPN 251DBL) in Permit No. 4449.) Emissions from the Plant Boilers are in Permit No. 2175.
*	Emission rates are based on and the facilities are limited by the following maximum operating schedule:
	<u>24</u> Hrs/day <u>7</u> Days/week <u>52</u> Weeks/year orHrs/year
	Dated