EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Permit No. 27359C

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

AIR CONTAMINANTS DATA

Emission	Source	Air Contaminant	<u>Emissior</u>	n Rates *
Point No. (1)	Name (2)	Name (3)	lb/hr	TPY
, ,	. ,	. ,		
	Baghouse Stack	PM	11.40	7.30
	-	PM_{10}	11.40	7.30
		VOC(a)	15.05	9.63
		VOC(b)	59.85	38.30
		VOC(c)	700.00	70.00
		NO_x	12.60	8.06
		SO_2	17.13	10.96
		CO	13.30	8.51
	Lime Silo Baghouse	PM	3.11	< 0.01
	•	PM_{10}	0.51	<0.01
	Stockpiles (4)	PM	-	0.29
	- · · · · · · · · · · · · · · · · · · ·	PM_{10}	-	0.14
	Raw Aggregate Process (4)	PM	24.34	15.56
		PM_{10}	0.72	0.43

- (1) Emission point identification either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources use area name or fugitive source name.
- (3) PM particulate matter, suspended in the atmosphere, including PM_{10}
 - PM₁₀ particulate matter equal to or less than 10 microns in diameter. Where PM is not listed, it shall be assumed that no particulate matter greater than 10 microns is emitted.
 - VOC volatile organic compounds as defined in 30 Texas Administrative Code Section 101.1
 - VOC(a) VOC consisting mainly of asphalt vapor
 - VOC(b) VOC consisting mainly of diesel or kerosene vapor
 - VOC(c) additional VOC resulting from the use of crumb rubber
 - NO_x total oxides of nitrogen

 SO_2

- sulfur dioxide

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

	CO Fugitive		carbon			only s	and o	chould	not ho	consido	od a	c a ma	avimum	allowabl	^
(4)	emiss	_		are arr	estimate	Offiny 6	anu s	Siloulu	not be	Consider	eu a	s a IIId	axiiiiuiii	allowabli	C

Emission rates are based on and the facilities are limited by the following maximum operating

schedule and production rates:
Hrs/day <u>8</u> Days/week <u>5</u> up to Hrs/year <u>1,280</u>
Standard Hot-Mix Asphalt Concrete: Tons/hour_350_ Tons/year_488,000_
Cold-Mix Asphalt Concrete (produced with emulsions): Tons/hour_200_Tons/year_40,000
Standard Hot-Mix with Crumb Rubber: Tons/hour_200 Tons/year_40,000

|--|