EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Permit No. 17692

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

AIR CONTAMINANTS DATA

Emission	Source	Air Contaminant	Emiss	ion Rates		
Point No. (1)	Name (2)	Name (3)	#/hr	TPY*		
DT-1		DynaTest Stack No. 1		NO_x	368.6	39.2
				CO	344.7	31.7
				VOC	91.5	8.5
				SO_2	6.3	8.0
				PM	5.0	0.7
DT-2	J	DynaTest Stack No. 2		NO _x	368.6	39.2
				CO	344.7	31.7
				VOC	91.5	8.5
				SO_2	6.3	8.0
				PM	5.0	0.7
TEST-1		Turbine Testline		NO _x	698.0	25.7
				CO	375.0	3.1
				VOC	103.0	0.7
				SO_2	111.0	2.6
				PM	11.1	0.5
E-3(a-d)		Paint Shop		VOC	34.6	5.5
				PM	1.0	0.2
E-4(a-d)		Paint/Tear down Shop		VOC	28.4	5.0
_ (a a)	'	rame roar down onep		PM	1.0	0.2
E-4FUG	I	Paint/Tear down Shop		VOC	6.3	0.6
	ugitives	i ainii reai down Shop		VOC	0.5	0.0
COMP-1		Testline Compressor		NOx	31.7	11.2
(Exemption No		•		CO	1.8	0.7

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

	VOC	1.8 SO ₂ PM	0.7 0.2 3.0	<0.1 1.0
E-2FUG	Fabrication shop/ Maintenance Building	VOC PM	15.1 24.3	0.2 0.4
(Exemption No. 75	· · · · · · · · · · · · · · · · · · ·	⊢ IVI	24.3	0.4

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

- (1) Emission point identification either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources, area name or fugitive source name.
- (3) NO_x Nitrogen oxides

CO - carbon monoxide

VOC - volatile organic compounds as defined in General Rule 101.1

SO₂ - sulfur dioxide

PM - particulate matter

* Annual emission rates are based on, and the facilities are limited by, the following maximum operating schedule:

180 hrs/year at each of three load levels or 540 hrs/year total for the DynaTest stacks. Levels are no load, any load (computed at maximum load), and maximum load. DynaTest testing is additionally limited to 90 turbines tested per year, with periods averaging 6 hours/test. Emission factors are based on a composite of GE data for LM2500, LM5000, and LM6000 turbines.

705 hrs/year for Emission Point COMP-1, based on 120 hrs/year supporting TEST-1 operations, and 585 hrs/year supporting DynaTest operations.

_		
Г)ated	
	altu	

1