Emission Sources - Maximum Allowable Emission Rates

Permit Number 142504

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities, sources, and related activities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

Air Contaminants Data

Emission Point No.	Source Name (2)	Air Contaminant Name (3)	Emission Rates (6)	
(1)			lbs/hour	TPY (4)
LD-1	Drum Debarker (5)	PM	0.24	0.38
		PM ₁₀	0.11	0.18
		PM _{2.5}	0.06	0.10
LD-2	Ring Debarker (5)	PM	0.28	0.35
		PM ₁₀	0.13	0.16
		PM _{2.5}	0.07	0.09
SM-1	Pine Sawmill 1 (5)	PM	3.50	1.75
		PM ₁₀	2.00	1.00
		PM _{2.5}	1.00	0.50
SM-2	Pine Sawmill 2 (5)	PM	1.21	1.36
		PM ₁₀	0.69	0.78
		PM _{2.5}	0.35	0.39
PM-1	Planer Mill Cyclone Stack	PM	0.26	1.13
		PM ₁₀	0.11	0.45
		PM _{2.5}	0.05	0.23
CM-1	Chip Mill (5)	PM	0.24	0.29
		PM ₁₀	0.12	0.15
		PM _{2.5}	0.06	0.07
K-1	Dual Path Lumber Drying Kiln Vent	VOC	22.44	99.40
		NO _X	4.66	20.39
		SO ₂	0.53	2.32
		PM	0.16	0.70
		PM ₁₀	0.16	0.70

Emission Sources - Maximum Allowable Emission Rates

		PM _{2.5}	0.16	0.70
		СО	3.60	15.75
		HCI	0.41	1.77
		Cl ₂	0.02	0.07
		НСНО	0.82	3.61
		MeOH	1.28	5.64
		Total HAPs	3.26	14.39
SP-1	Storage Pile – Hard	PM	0.01	0.02
	Wood (HW)/Soft Wood (SW) Bark (5)	PM ₁₀	<0.01	0.01
		PM _{2.5}	<0.01	<0.01
SP-2	Storage Pile – SW	PM	0.03	0.02
	Bark (5)	PM ₁₀	0.01	0.01
		PM _{2.5}	<0.01	<0.01
SP-3	Storage Pile –	PM	0.03	0.01
	HW/SW Sawdust (5)	PM ₁₀	0.02	<0.01
		PM _{2.5}	<0.01	<0.01
SP-4	Storage Pile –	PM	0.03	0.01
	HW/SW Sawdust (5)	PM ₁₀	0.02	<0.01
		PM _{2.5}	<0.01	<0.01
SP-5	Storage Pile –	PM	0.03	0.01
	HW/SW Sawdust (5)	PM ₁₀	0.02	<0.01
		PM _{2.5}	<0.01	<0.01
SP-6	Storage Pile –	PM	0.03	0.01
	HW/SW Sawdust (5)	PM ₁₀	0.02	<0.01
		PM _{2.5}	<0.01	<0.01
SP-7	Storage Pile – SW	PM	0.04	0.02
	Sawdust (5)	PM ₁₀	0.02	0.01
		PM _{2.5}	<0.01	<0.01
SP-8	Storage Pile – HW	PM	0.05	0.06

Emission Sources - Maximum Allowable Emission Rates

		PM ₁₀	0.02	0.03
		PM _{2.5}	<0.01	<0.01
SP-9	Storage Pile – SW Chips (5)	РМ	0.09	0.11
		PM ₁₀	0.04	0.05
		PM _{2.5}	0.01	0.01
SP-10	Storage Pile – SW Chips (5)	РМ	0.09	0.11
		PM ₁₀	0.04	0.05
		PM _{2.5}	0.01	0.01
SP-11	Storage Pile – SW Shavings (5)	PM	0.03	0.02
		PM ₁₀	0.02	0.01
		PM _{2.5}	<0.01	<0.01

(1) Emission point identification - either specific equipment designation or emission point number from plot plan.

(2) Specific point source name. For fugitive sources, use area name or fugitive source name.

(3) VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1

NO_x - total oxides of nitrogen

SO₂ - sulfur dioxide

PM - total particulate matter, suspended in the atmosphere, including PM_{10} and $PM_{2.5}$, as

represented

 PM_{10} - total particulate matter equal to or less than 10 microns in diameter, including $PM_{2.5}$, as

represented

PM_{2.5} - particulate matter equal to or less than 2.5 microns in diameter

CO - carbon monoxide HCI - hydrochloric acid

Cl₂ - chlorine HCHO - formaldehyde MeOH - methanol

HAP - hazardous air pollutant as listed in § 112(b) of the Federal Clean Air Act or Title 40

Code of Federal Regulations Part 63, Subpart C

(4) Compliance with annual emission limits (tons per year) is based on a 12 month rolling period.

(5) Emission rate is an estimate and is enforceable through compliance with the applicable special condition(s) and permit application representations.

(6) Planned startup and shutdown emissions are included for all sources. Any other maintenance activities are not authorized by this permit, but will be authorized separately

Date:	August 29, 2017	
Daic.	Audusi 23. 2011	

Permit Number 142504 Page

Emission Sources - Maximum Allowable Emission Rates