

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Permit Number 47560A

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

Emission Point No. (1)	Source Name (2)	AIR CONTAMINANTS DATA Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY
19	Baghouse Stack	PM ₁₀	14.29	11.61
		VOC(a)	12.80	10.40
		VOC(c)	50.00	11.30
		NO _x	22.00	20.90
		SO ₂	23.20	18.85
		CO	52.00	42.25
10	Asphalt Heater Vent (4)	PM ₁₀	0.02	0.06
		VOC	<0.01	<0.01
		NO _x	0.10	0.15
		SO ₂	0.30	0.45
		CO	0.03	0.04
15	Lime Storage Silo (4)	PM ₁₀	0.05	0.01
17	Surge Bin Filling (4)	PM ₁₀	0.17	0.14
		VOC	1.10	0.89
		CO	0.38	0.31
20	Truck Loadout	PM ₁₀	0.17	0.14
		VOC	1.10	0.89
		CO	0.38	0.31
STK	Aggregate Stockpiles (4)	PM	---	0.47
		PM ₁₀	---	0.24
Various	Material Handling (4)	PM	1.93	1.59
		PM ₁₀	0.92	0.75

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

- (1) Emission point identification - either specific equipment designation or emission point number from a plot plan.
- (2) Specific point source names. For fugitive sources use area name or fugitive source name.
- (3) PM - particulate matter, suspended in the atmosphere, including PM₁₀
PM₁₀ - particulate matter equal to or less than less than 10 microns in diameter. Where PM is not listed, it shall be assumed that no particulate matter greater than 10 microns is emitted.
VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
VOC(a) - mainly asphalt vapors from standard mix
VOC(c) - total VOCs due to the use of a rubber modified mix
NO_x - total oxides of nitrogen
SO₂ - sulfur dioxide
CO - carbon monoxide
- (4) Fugitive emissions are an estimate only.

* Emission rates are based on and the facilities are limited by the following maximum operating schedule and production rates:

12 Hrs/day 5 Days/week 52 Weeks/year or 3,000 Hrs/year

Standard Hot Mix: Tons/hour 400 Tons/year 650,000

Rubber Modified Mix: Tons/hour 220
Tons/year 100,000

Dated _____