#### Permit Number 18978, PSDTX752M5, N162M1

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities, sources, and related activities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

Air Contaminants Data

<b>Emission Point No. (1)</b>		Air Contaminant Name (3)	Emissio	Emission Rates		
			lbs/hour	TPY (4)		
QE1001B	Furnace 1	NO <sub>X</sub>	30.30	121.26		
		со	24.71	31.34		
		SO <sub>2</sub>	0.30	1.31		
		VOC	0.70	3.00		
		PM	1.00	3.50		
		PM <sub>10</sub>	1.00	3.50		
		PM <sub>2.5</sub>	1.00	3.50		
QE1002B	Furnace 2	NO <sub>X</sub>	30.30	121.26		
		со	24.71	31.34		
		SO <sub>2</sub>	0.30	1.31		
		VOC	0.70	3.00		
		PM	1.00	3.50		
		PM <sub>10</sub>	1.00	3.50		
		PM <sub>2.5</sub>	1.00	3.50		
QE1003B	Furnace 3	NO <sub>x</sub>	30.30	121.26		
		со	24.71	31.34		
		SO <sub>2</sub>	0.30	1.31		
		VOC	0.70	3.00		
		PM	1.00	3.50		
		PM <sub>10</sub>	1.00	3.50		
		PM <sub>2.5</sub>	1.00	3.50		

Emission Sources - Maximum Allowable Emission Rates

QE1004B	Furnace 4	NO <sub>x</sub>	30.30	121.26
		СО	24.71	31.34
		SO <sub>2</sub>	0.30	1.31
		voc	0.70	3.00
		PM	1.00	3.50
		PM <sub>10</sub>	1.00	3.50
		PM <sub>2.5</sub>	1.00	3.50
QE1005B	Furnace 5	NO <sub>X</sub>	30.30	121.26
		со	24.71	31.34
		SO <sub>2</sub>	0.30	1.31
		VOC	0.70	3.00
		PM	1.00	3.50
		PM <sub>10</sub>	1.00	3.50
		PM <sub>2.5</sub>	1.00	3.50
QE1006B	Furnace 6	NO <sub>X</sub>	30.30	121.26
		со	24.71	31.34
		SO <sub>2</sub>	0.30	1.31
		VOC	0.70	3.00
		PM	1.00	3.50
		PM <sub>10</sub>	1.00	3.50
		PM <sub>2.5</sub>	1.00	3.50
QE1007B	Furnace 7	NO <sub>X</sub>	30.30	121.26
		со	24.71	31.34
		SO <sub>2</sub>	0.30	1.31
		voc	0.70	3.00
		PM	1.00	3.50
		PM <sub>10</sub>	1.00	3.50
		PM <sub>2.5</sub>	1.00	3.50
QE1008B	Furnace 8	NOx	30.30	121.26

Emission Sources - Maximum Allowable Emission Rates

		со	24.71	31.34
		SO <sub>2</sub>	0.30	1.31
		VOC	0.70	3.00
		РМ	1.00	3.50
		PM <sub>10</sub>	1.00	3.50
		PM <sub>2.5</sub>	1.00	3.50
QE1009B	Furnace 9	NO <sub>X</sub>	31.75	126.58
		СО	33.92	34.45
		SO <sub>2</sub>	0.36	1.56
		voc	0.83	3.63
		РМ	2.10	6.57
		PM <sub>10</sub>	2.10	6.57
		PM <sub>2.5</sub>	2.10	6.57
QE1010B	Furnace 10	NO <sub>x</sub> (Routine)	9.00	24.09
		NO <sub>x</sub> (Decoke / Hot stand by)	12.50	
		NO <sub>x</sub> (MSS)	14.00	
		со	20.36	81.76
		SO <sub>2</sub>	0.35	1.42
		voc	0.60	2.41
		РМ	4.30	17.25
		PM <sub>10</sub>	4.30	17.25
		PM <sub>2.5</sub>	4.30	17.25
		NH <sub>3</sub>	3.11	13.62
QE1011B	Furnace 11	NO <sub>x</sub> (Routine)	9.00	24.09
		NO <sub>x</sub> (Decoke / Hot stand by)	12.50	
		NO <sub>x</sub> (MSS)	14.00	
		со	20.36	81.76
		SO <sub>2</sub>	0.35	1.42
		voc	0.60	2.41

1	ı			
		PM	4.30	17.25
		PM <sub>10</sub>	4.30	17.25
		PM <sub>2.5</sub>	4.30	17.25
		NH <sub>3</sub>	3.11	13.62
QE5802UA	Boiler A	NO <sub>X</sub>	22.50	89.70
		со	20.14	30.27
		SO <sub>2</sub>	0.14	0.61
		voc	1.43	1.91
		PM	0.34	1.49
		PM <sub>10</sub>	0.34	1.49
		PM <sub>2.5</sub>	0.34	1.49
QE5802UB	Boiler B	NO <sub>X</sub>	22.50	89.70
		со	20.14	30.27
		SO <sub>2</sub>	0.14	0.61
		voc	1.43	1.91
		PM	0.34	1.49
		PM <sub>10</sub>	0.34	1.49
		PM <sub>2.5</sub>	0.34	1.49
QE6410F	Pyrolysis Gasoline IFR Tank	VOC	2.12	5.95
QE2410F	Wash Oil Drum	voc	0.52	0.02
QE1416F	Decoking Drum	CO (PSD)	877.90	_
		PM	16.90	_
		PM <sub>10</sub> (PSD)	16.90	_
		PM <sub>2.5</sub> (PSD)	14.03	_
		VOC	2.05	_
QE1423F	Decoking Drum	со	877.90	_
		PM	16.90	_
		PM <sub>10</sub>	16.90	_
		PM <sub>2.5</sub>	14.03	_

		VOC	2.05	_
QE1416F and QE1423F		СО	_	388.47
	QE1423F	PM	_	7.36
		PM <sub>10</sub>	_	7.36
		PM <sub>2.5</sub>	_	4.98
		VOC	_	3.78
QE7801U	Cooling Tower (5)	VOC	7.88	5.34
		PM	2.67	11.69
		PM <sub>10</sub>	1.31	5.73
		PM <sub>2.5</sub>	0.01	0.02
QE3418F	MAPD Decoke Pot	со	17.30	0.31
QE3050B	ARU Flare	CO (PSD)	21.00	8.98
		NO <sub>x</sub> (PSD)	4.04	1.73
		SO <sub>2</sub>	0.10	0.10
		VOC	15.02	1.38
QE3050MAINT	ARU Flare Maintenance	СО	50.65	1.27
		NO <sub>X</sub>	9.74	0.24
		SO <sub>2</sub>	0.10	0.10
		VOC	78.63	1.97
QE8050B	Elevated Flare	CO (PSD)	266.80	87.66
		NO <sub>x</sub> (PSD)	85.21	30.11
		SO <sub>2</sub>	81.32	4.25
		VOC	50.83	11.89
QE8050MAINT	Elevated Flare	СО	82.50	0.30
	Maintenance	NO <sub>x</sub>	16.16	0.10
		SO <sub>2</sub>	101.78	0.06
		VOC	58.18	0.15
QEH2FLARE	Hydrogen Flare	СО	59.16	35.50
		NO <sub>X</sub>	34.87	20.92

		VOC	5.99	3.59
		SO <sub>2</sub>	0.01	0.01
QE7412F	Wash Oil Tank	voc	0.70	0.08
QELOAD	Organic Loading	VOC	0.06	0.03
QESTORE	Organic Storage	VOC	1.33	1.01
QE8001A	Wastewater System	VOC	0.35	1.55
QELAB	Sampling	VOC	7.04	2.25
QEFUG	Process Fugitives (6)	VOC	19.67	86.07
		NH <sub>3</sub>	0.12	0.54
		Chlorine	0.04	0.17
QEANALYZ2	Main Flare HRVOC	NO <sub>X</sub>	0.01	0.01
	Analyzer	СО	0.01	0.01
		VOC	0.01	0.01
QE1ANLYZR4	Furnace 10-11 Analyzers	NO <sub>X</sub>	0.01	0.01
		СО	0.01	0.01
		VOC	0.04	0.17
QEUNIT	Dock Thermal Oxidizer	NO <sub>x</sub> (PSD)	14.68	4.70
	(7)	CO (PSD)	17.73	6.25
		VOC	23.77	7.22
		РМ	0.01	0.02
		PM <sub>10</sub>	0.01	0.02
		PM <sub>2.5</sub>	0.01	0.02
PW7614JA	Emergency Engine	NO <sub>X</sub>	15.10	1.70
		СО	3.25	0.37
		VOC	1.22	0.14
		SO <sub>2</sub>	1.00	0.11
		РМ	1.07	0.12
		PM <sub>10</sub>	1.07	0.12
		PM <sub>2.5</sub>	1.07	0.12

PW7605JB	Emergency Engine	NO <sub>X</sub>	15.84	6.94
		СО	3.63	1.59
		VOC	0.47	0.20
		SO <sub>2</sub>	5.34	2.34
		РМ	0.46	0.20
		PM <sub>10</sub>	0.46	0.20
		PM <sub>2.5</sub>	0.46	0.20
PW7605JC	Emergency Engine	NOx	15.84	6.94
		СО	3.63	1.59
		VOC	0.47	0.20
		SO <sub>2</sub>	5.34	2.34
		РМ	0.46	0.20
		PM <sub>10</sub>	0.46	0.20
		PM <sub>2.5</sub>	0.46	0.20
7407F	Sulfuric Acid Tank	H <sub>2</sub> SO <sub>4</sub>	0.01	0.01
7701LL3F	Sulfuric Acid Tank	H <sub>2</sub> SO <sub>4</sub>	0.01	0.01
QEPGCIN	PGC Seal Oil/Lube Oil	VOC	0.32	1.38
QENH3SC	Ammonia Clearing	NH <sub>3</sub>	1.00	0.01

(1) Emission point identification - either specific equipment designation or emission point number from plot plan.

(2) Specific point source name. For fugitive sources, use area name or fugitive source name.

(3) VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1

NO<sub>x</sub> - total oxides of nitrogen

SO<sub>2</sub> - sulfur dioxide

PM - total particulate matter, suspended in the atmosphere, including PM<sub>10</sub> and PM<sub>2.5</sub>, as represented

PM<sub>10</sub> - total particulate matter equal to or less than 10 microns in diameter, including PM<sub>2.5</sub>, as

represented

PM<sub>2.5</sub> - particulate matter equal to or less than 2.5 microns in diameter

CO - carbon monoxide

 $NH_3$  - ammonia  $H_2SO_4$  - sulfuric acid

- (4) Compliance with annual emission limits (tons per year) is based on a 12 month rolling period.
- (5) Emission rate is an estimate only and is enforceable through compliance with the permit Special Conditions applicable to the cooling tower and with cooling water circulation flow rates represented in the permit application.
- (6) Emission rate is an estimate only and is enforceable through compliance with the permit Special Conditions applicable to fugitives and with representations in the permit application.
- (7) The dock thermal oxidizer is owned and operated by LyondellBasell Acetyls, LLC, under Permit Number 4751.

Permit Number	18978,	PSDTX	752M5,	N162M1
Page				

Emiccion	Sources -	Maximum	Allowable	Emiccion	Dates
	- 2011110 -	IVIAXIIIIIIII	AIIUWAIIIE		RAIES

Date:	February 4, 2021