Permit Number 40299

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

Emission	Source	Air Contaminant	Emission Rates	
Point No. (1)	Name (2)	Name (3)	lb/hr	TPY
D1	Blood Dryer (b) 8.7 MMBtu Burner (Natural Gas-Fired)	PM/PM_{10} VOC NO_x CO SO_2	0.06 0.05 0.83 0.70 0.12	0.28 0.20 3.63 3.05 0.54
S1	Blood Dryer Scrubber (b)	PM/PM ₁₀	1.57	6.87
	Blood Silo Bagfilter (b)	PM/PM ₁₀	0.02	0.09
S2	Plant Air Scrubber Stack (e)	PM/PM_{10} VOC NO_x CO SO_2	0.62 2.71 0.13 0.09 0.24	2.72 11.88 0.55 0.38 1.05
12	Meat and Bone Meal Bagfilter (b)	PM/PM ₁₀	0.15	0.66
72	Dried Blood Bin Bagfilter (b)	PM/PM ₁₀	0.03	0.15
30	Hi-Pro Shaker Bagfilter (b)	PM/PM ₁₀	0.28	1.24
42	Lo-Pro Shaker Bagfilter (b)	PM/PM ₁₀	0.08	1.24
76A	Loadout Bagfilter (b)	PM/PM ₁₀	0.07	0.30

Emission	Source	Air	Contaminant	Emission	<u>Rates</u>
Point No. (1)	Name (2)		Name (3)	lb/hr	TPY
4	Hi-Pro Cooler Cyclone (b)		PM/PM ₁₀	2.14	9.39
	Dried Blood Loadout (c)		PM PM ₁₀	2.25 1.13	0.18 0.09
	Gel Bone Loadout (d)		PM PM ₁₀	2.79 1.40	0.30 0.15
	Bone Meal Loadout (e)		PM PM ₁₀	4.95 2.48	2.66 1.33
B1	21 MMBtu Boiler (b) Boiler No. 1 (Natural Gas/Biogas)		PM/PM ₁₀ VOC NO _x CO SO ₂	0.23 0.17 3.00 2.52 13.41	
	ŀ	H ₂ S	0.06		
	21MMBtu/hr Boiler (b) Boiler No. 1 (Tallow Fired)		PM/PM_{10} VOC NO_x CO SO_2	1.02 0.03 3.21 0.23 0.04	
	21MMBtu/hr Boiler (b) Boiler No. 1 (Natural Gas, BioGas and Tallow Fired)	H2S	PM/PM ₁₀ VOC NO _x CO SO ₂	 0.30	4.49 0.70 14.05 11.00 58.70

Emission	Source	Air Contaminant		Emission Rates	
Point No. (1)	Name (2)		Name (3)	lb/hr	TPY
	• •		, ,		
B2	21 MMBtu Boiler (b) Boiler No. 2 (Natural Gas/Biogas)	H₂S	PM/PM ₁₀ VOC NO _x CO SO ₂ 0.06	0.23 0.17 3.00 2.52 13.41 0.3	1.0 0.7 13.1 11.0 58.7
B3	21 MMBtu Boiler (b) Boiler No. 3 (Natural Gas/Biogas)	H ₂ S	PM/PM_{10} VOC NO_x CO SO_2 0.06	0.23 0.17 3.00 2.52 13.41 0.3	1.0 0.7 13.1 11.0 58.7
B4	21 MMBtu Boiler (b) Boiler No. 4 (Natural Gas/Biogas)	H₂S	$\begin{array}{c} PM/PM_{10} \\ VOC \\ NO_x \\ CO \\ SO_2 \\ 0.06 \end{array}$	0.23 0.17 3.00 2.52 13.41 0.3	1.0 0.7 13.1 11.0 58.7
B5	25.2 MMBtu Boiler (b) Boiler No. 5 (Natural Gas-Fired)		PM/PM_{10} VOC NO_x CO SO_2	0.18 0.13 2.40 2.02 0.36	
	25.2MMBtu/hr Boiler (b) Boiler No. 1 (Tallow Fired)		PM/PM_{10} VOC NO_x CO SO_2	1.23 0.03 3.85 0.27 0.04	

Source	Air Contaminant	Emission	<u>Rates</u>
Name (2)	Name (3)	lb/hr	TPY
			_
25.2MMBtu/hr Boiler (b)	PM/PM ₁₀		5.39 0.58
			16.87
,	CO		8.83
	SO ₂		1.58
42 MMBtu Boiler (b)	PM/PM ₁₀	0.30	
(Natural Gas-Fired)			
	SO_2	0.60	
42 MMBtu/hr Boiler (b)	PM/PM ₁₀	2.05	
(Tallow Fired)			
	SO_2	0.07	
42 MMBtu/hr Boiler (b)	PM/PM ₁₀		8.98
			0.96
(Natural Gas and Tallow)			28.11
			14.72
	SO ₂		2.63
Bone Dryer Cyclone (b)	PM/PM ₁₀	3.50	15.33
30 MMBtu Burner	VOC	0.16	0.69
(Natural Gas-Fired)	NO_x	2.86	12.51
	CO	2.40	10.51
	SO_2	0.43	1.88
	25.2MMBtu/hr Boiler (b) Boiler No. 1 (Natural Gas and Tallow) 42 MMBtu Boiler (b) Boiler No. 6 (Natural Gas-Fired) 42 MMBtu/hr Boiler (b) Boiler No. 1 (Tallow Fired) 42 MMBtu/hr Boiler (b) Boiler No. 1 (Natural Gas and Tallow) Bone Dryer Cyclone (b) 30 MMBtu Burner	Name (2) 25.2MMBtu/hr Boiler (b) PM/PM ₁₀ Boiler No. 1 VOC (Natural Gas and Tallow) NO _x CO SO ₂ 42 MMBtu Boiler (b) PM/PM ₁₀ Boiler No. 6 VOC (Natural Gas-Fired) NO _x CO SO ₂ 42 MMBtu/hr Boiler (b) PM/PM ₁₀ Boiler No. 1 VOC (Tallow Fired) NO _x CO SO ₂ 42 MMBtu/hr Boiler (b) PM/PM ₁₀ Boiler No. 1 VOC (Natural Gas and Tallow) NO _x CO SO ₂ 42 MMBtu/hr Boiler (b) PM/PM ₁₀ CO SO ₂ 42 MMBtu/hr Boiler (b) PM/PM ₁₀ VOC (Natural Gas and Tallow) NO _x CO SO ₂	Name (2) Name (3)

Permit Number 40299 Page 5

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Emission	Source	Air Contaminant		Emission Rates	
Point No. (1)	Name (2)	Name (3)		lb/ <u>hr</u>	<u>TPY</u>
F1	Process Flare (a)		PM/PM ₁₀ VOC 3.24 17.61 12.89 0.07	0.46 6.66 1.42 7.71 5.64 0.03	0.20 2.92

- (1) Emission point identification either specific equipment designation or emission point number from a plot plan.
- (2) Specific point source names. For fugitive sources use area name or fugitive source name.
- (3) PM particulate matter, suspended in the atmosphere, including PM₁₀
 - PM₁₀ particulate matter equal to or less than 10 microns in diameter. Where PM is not listed, it shall be assumed that no particulate matter greater than 10 microns is emitted.
 - VOC volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
 - NO_x total oxides of nitrogen
 - CO carbon monoxide
 - SO₂ sulfur dioxide
 - H₂S hydrogen sulfide
- (a) Emission rates are based on and the facilities are limited to an operating schedule of 876 hours/year.
- (b) Emission rates are based on and the facilities are limited to an operating schedule of 8,760

hours/year.

- (c) Emission rates are based on and the facilities are limited to an hourly throughput of 50 tons and an annual throughput of 7,990 tons of dried blood.
- (d) Emission rates are based on and the facilities are limited to an hourly throughput of 62 tons and an annual throughput of 13,500 tons of processed gel bone.
- (e) Emission rates are based on and the facilities are limited to an hourly throughput of 55 tons and an annual throughput of 59,000 tons of bone meal.

Dated <u>June 13, 2006</u>