

Emission Sources - Maximum Allowable Emission Rates

Permit Number 21878

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities, sources, and related activities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

Air Contaminants Data

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
PSA-FUG	Pressure Swing Adsorption Unit Fugitives (5)	CO	0.95	4.20
A	Fired Gas Preheater A (7)	NOx	1.92	8.40
		PM	0.48	2.10
		PM ₁₀	0.48	2.10
		PM _{2.5}	0.48	2.10
		SO ₂	0.81	3.60
		CO	1.15	5.10
		VOC	0.09	0.40
		Ammonia	0.01	0.03
		Cyanide	0.01	0.01
B	Fired Gas Preheater B (7)	NOx	1.92	8.40
		PM	0.48	2.10
		PM ₁₀	0.48	2.10
		PM _{2.5}	0.48	2.10
		SO ₂	0.81	3.60
		CO	1.15	5.10
		VOC	0.09	0.40
		Ammonia	0.01	0.03
		Cyanide	0.01	0.01
101	POX Startup Burner A (7)	NOx	0.78	3.44

Emission Sources - Maximum Allowable Emission Rates

		PM	0.06	0.27
		PM ₁₀	0.06	0.27
		PM _{2.5}	0.06	0.27
		SO ₂	0.11	0.49
		CO	0.70	2.90
		VOC	0.04	0.19
201	POX Startup Burner B (7)	NOx	0.78	3.44
		PM	0.06	0.27
		PM ₁₀	0.06	0.27
		PM _{2.5}	0.06	0.27
		SO ₂	0.11	0.49
		CO	0.70	2.90
		VOC	0.04	0.19
D	Warm Flare, Routine Operations (8)	CO	1,047.80	60.16
		NOx	22.44	2.86
		SO ₂	1.09	0.50
	Warm Flare, MSS Operations (9)	CO	685.01	9.34
		NOx	32.41	0.40
		SO ₂	0.04	0.01
		VOC	0.73	0.01
E	Cold Flare, Routine Operations	CO	25.38	0.37
		NOx	0.39	0.04
	Cold Flare, MSS Operations (9)	CO	761.24	56.25
		NOx	15.03	2.88
		SO ₂	0.01	0.01

Emission Sources - Maximum Allowable Emission Rates

		VOC	0.62	0.01
F	Plant Fugitives (5)	CO	13.41	58.21
		VOC	0.28	1.20
		PM	13.02	0.98
		PM ₁₀	13.02	0.98
		PM _{2.5}	13.02	0.98
		Argon	0.75	3.25
		Fe(CO) ₅	0.01	0.01
G	Liquid Oxygen Vaporizers	NO _x (6)	2.03	8.63
		NO _x	1.22	5.17
		PM	0.24	1.02
		PM ₁₀	0.24	1.02
		PM _{2.5}	0.24	1.02
		SO ₂	0.22	0.95
		CO	0.55	2.31
		VOC	0.05	0.20
H	Wastewater Equalization Tank	VOC	0.01	0.01
		Cyanide	0.01	0.01
		Ammonia	0.02	0.09
		CO	0.14	0.61
I	Temperature Swing Adsorption Driers	CO	0.29	1.26
		Fe(CO) ₅	0.06	0.01
J	MEA Storage Tank	VOC	0.02	0.07
K	HyCO-3 Cooling Tower	PM	2.39	10.45

Emission Sources - Maximum Allowable Emission Rates

		PM ₁₀	2.39	10.45
		PM _{2.5}	2.39	10.45
L	ASU-GOX Cooling Water Tower	PM	2.79	12.20
		PM ₁₀	2.79	12.20
		PM _{2.5}	2.79	12.20
M	ASU Cooling Water Tower	PM	7.62	33.37
		PM ₁₀	7.62	33.37
		PM _{2.5}	7.62	33.37
N1, N2	HYCO Deaerator Vents	MEA	0.03	0.12
O	Vacuum Pump	CO	5.10	0.94
P1, P2, P3, P4, P5, and P6	Emergency Generators	NOx	153.63	3.99
		CO	34.77	0.90
		SO ₂	22.65	0.59
		PM	5.81	0.15
		PM ₁₀	5.81	0.15
		PM _{2.5}	5.81	0.15
		VOC	5.84	0.15
P7	Emergency Diesel Generator	NOx	2.84	0.14
		CO	0.60	0.03
		VOC	0.12	0.01
		PM	0.10	0.01
		PM ₁₀	0.10	0.01
		PM _{2.5}	0.10	0.01
		SO ₂	1.00	0.05
FUG_DEGAS	Fugitive Degassing for Maintenance (Annual & Turnaround) and Pump,	CO	1.02	0.01
		VOC	1.61	0.01

Emission Sources - Maximum Allowable Emission Rates

	Valve and Piping Maintenance and Repair (9)			
INS	Fuel Vent, Calibration & Maintenance of Instrumentation and Meters (9)	VOC	0.28	0.08

- (1) Emission point identification - either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources, use area name or fugitive source name.
- (3) VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
 - NO_x - total oxides of nitrogen
 - SO₂ - sulfur dioxide
 - PM - total particulate matter, including PM₁₀ and PM_{2.5}, as represented
 - PM₁₀ - total particulate matter equal to or less than 10 microns in diameter, including PM_{2.5}, as represented
 - PM_{2.5} - total particulate matter equal to or less than 2.5 microns in diameter
 - CO - carbon monoxide
 - Fe (CO)₅ - iron penta-carbonyl
 - MEA - mono-ethanolamine
- (4) Compliance with annual emission limits (tons per year) is based on a 12-month rolling period.
- (5) Emission rate is an estimate and is enforceable through compliance with the applicable special condition(s) and permit application representations.
- (6) Firing propane (only used during upset or routine maintenance periods).
- (7) Includes emissions during startup and shutdown.
- (8) Includes product flaring emissions during and attributable to demand reduction periods in which equipment maintenance is also conducted (e.g., product gas compressor outages).
- (9) Emissions attributable to MSS activities.

Date: September 10, 2021