Emission Sources - Maximum Allowable Emission Rates

Permit Number 80166

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities, sources, and related activities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

Emission Point No.	Source Name (2)	Air Contaminant Name (3)	Emission Rates (5) Ibs/hour TPY	ates (5)
(1)			lbs/hour	TPY (4)
Operating Scenario 1. Emissions when RTO online and the source is operating under normal operating conditions:				ating
1	RTO-1	Butane	1.22	4.10
		РМ	<0.01	<0.01
	RTO-1 Products of Combustion	NO _X	0.28	1.24
		со	0.24	1.04
		SO ₂	<0.01	<0.01
		PM ₁₀	0.42	1.85
7	Regrind Silos (Each)	Butane	0.00	0.00
		PM	0.00	0.00
authorized planned i maintenance, start-u	maintenance, start-up, p, and shutdown autho	operating conditions author and shutdown activities, who prized in this permit. These outlets of the regrind silos:	en RTO is off-line o	due to planne
authorized planned i maintenance, start-u	maintenance, start-up, p, and shutdown autho	and shutdown activities, whorized in this permit. These	en RTO is off-line o	due to planne
authorized planned i maintenance, start-u RTO, are diverted ar	maintenance, start-up, ip, and shutdown authonder the fabric filter o	and shutdown activities, whorized in this permit. These utlets of the regrind silos:	en RTO is off-line (emissions, normall	due to planned y routed to the
authorized planned i maintenance, start-u RTO, are diverted ar	maintenance, start-up, ip, and shutdown authord exit the fabric filter or RTO-1	and shutdown activities, whorized in this permit. These utlets of the regrind silos:	en RTO is off-line of emissions, normall 0.00	due to planned y routed to the 0.00
authorized planned i maintenance, start-u RTO, are diverted ar	maintenance, start-up, ip, and shutdown authond exit the fabric filter o	and shutdown activities, whorized in this permit. These utlets of the regrind silos: Butane PM	en RTO is off-line of emissions, normall 0.00	o.00
authorized planned i maintenance, start-u RTO, are diverted ar	maintenance, start-up, ip, and shutdown authord exit the fabric filter or RTO-1	and shutdown activities, whorized in this permit. These utlets of the regrind silos: Butane PM NO _x	en RTO is off-line of emissions, normall 0.00 0.00 0.28	0.00 0.00 <0.02
authorized planned i maintenance, start-u RTO, are diverted ar	maintenance, start-up, ip, and shutdown authord exit the fabric filter or RTO-1	and shutdown activities, whorized in this permit. These utlets of the regrind silos: Butane PM NO _x CO	en RTO is off-line of emissions, normall 0.00 0.00 0.28 0.24	0.00 0.00 <0.02 <0.02
authorized planned i maintenance, start-u RTO, are diverted ar	maintenance, start-up, ip, and shutdown authord exit the fabric filter or RTO-1	and shutdown activities, whorized in this permit. These utlets of the regrind silos: Butane PM NO _X CO SO ₂	en RTO is off-line of emissions, normally 0.00 0.00 0.28 0.24 < 0.01	0.00 0.00 <0.02 <0.02 <0.01

Project Number: 196504

Emission Sources - Maximum Allowable Emission Rates

2	EXTR-1, Extrusion Area Fan	Butane	10.06	33.90
		Styrene	1.15	3.83
		Ethyl Benzene	0.16	0.54
3	PRINT-1, Print Area Fan	voc	1.04	3.50
4	FIN-1, Finished Product Storage Fan 1	Butane	3.70	12.50
5	FIN-2, Finished Product Storage Fan 2	Butane	3.70	12.50
6	FIN-3, Finished Product Storage Fan 3	Butane	3.70	12.50
All Sources	All Sources at Site	Individual HAP		<10.00
		Total HAPs		<25.00

- (1) Emission point identification either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources, use area name or fugitive source name.
- (3) Exempt Solvent Those carbon compounds or mixtures of carbon compounds used as solvents which have been excluded from the definition of volatile organic compound.

VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1

NO_x - total oxides of nitrogen

SO₂ - sulfur dioxide

PM - total particulate matter, suspended in the atmosphere, including PM₁₀ and PM_{2.5}, as

represented

PM₁₀ - total particulate matter equal to or less than 10 microns in diameter, including PM_{2.5}, as

represented

PM_{2.5} - particulate matter equal to or less than 2.5 microns in diameter

CO - carbon monoxide

HAP - hazardous air pollutant as listed in § 112(b) of the Federal Clean Air Act or Title 40

Code of Federal Regulations Part 63, Subpart C

(4) Compliance with annual emission limits (tons per year) is based on a 12 month rolling period.

(5) The allowable emission rates include planned maintenance, startup, and shutdown activities.

Date:	November	19.	2013	