

Emission Sources - Maximum Allowable Emission Rates

Permit Numbers 3611D and PSDTX194M5

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities, sources, and related activities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

Air Contaminants Data

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates (5)	
			lb/hour	TPY (4)
DC-1A	Raw Crusher	PM	3.24	14.16
		PM ₁₀	3.24	14.16
DC-1B	Belt 104/105	PM	0.24	1.10
		PM ₁₀	0.24	1.10
DC-1C	Belt 202B/213	PM	0.16	0.71
		PM ₁₀	0.16	0.71
DC-2 and DC-9	Kiln Exhaust	NO _x (30-day rolling average lb/hr)	600	2628
		SO ₂ (24-hour rolling average) (7)	416	1822
		PM (front half) (8)	27.69	118.29
		PM (front half + back half) (9)	80.99	299.99
		CO	5298.00	5528.00
		VOC	64.54	229.63
		H ₂ SO ₄	33.95	148.69
		Pb	0.03	0.13
		HCl	2.07	9.09
DC-3A	Blend Silo Nos. 1 and 2	PM	2.43	10.60
		PM ₁₀	2.43	10.60
DC-3B	Kiln Feed System	PM	0.71	3.10
		PM ₁₀	0.71	3.10
DC-3C	Blend Silo No. 3	PM	2.43	10.60
		PM ₁₀	2.43	10.60
DC-3D1	Kiln Feed Pump	PM	0.16	0.71
		PM ₁₀	0.16	0.71
DC-3D2	Kiln Feed Pump	PM	0.16	0.71
		PM ₁₀	0.16	0.71

Emission Sources - Maximum Allowable Emission Rates

DC-3D3	Kiln Feed Pump	PM	0.16	0.71
		PM ₁₀	0.16	0.71
DC-4	Clinker Cooler (6)	PM	10.00	43.80
		PM ₁₀	10.00	43.80
DC-4A-1	Conveyor 413/448	PM	0.45	2.00
		PM ₁₀	0.45	2.00
DC-5	Finish Mill No. 1	PM	7.8	34.2
		PM ₁₀	7.8	34.2
DC-5A-1	Finish Feed No. 1 Feed Belt 806	PM	0.81	3.5
		PM ₁₀	0.81	3.5
DC-6A	Finish Cement Silos A 1-9	PM	1.43	6.3
		PM ₁₀	1.43	6.3
DC-6B	Rail Bulk Loadout - A Silos	PM	0.32	1.4
		PM ₁₀	0.32	1.4
DC-6C	Truck Bulk Loadout - A Silos	PM	0.32	1.4
		PM ₁₀	0.32	1.4
DC-6D	Masonry Cement Loading	PM	0.32	1.4
		PM ₁₀	0.32	1.4
DC-7B	Finish Mill No. 1 Feed Silos	PM	3.0	13.0
		PM ₁₀	3.0	13.0
DC-8	Cement Bag Packhouse No. 1	PM	1.84	8.1
		PM ₁₀	1.84	8.1
DC-10A	Finish Mill No. 2	PM	1.5	6.6
		PM ₁₀	1.5	6.6
DC-10B	Finish Mill No. 2	PM	5.3	23.0
		PM ₁₀	5.3	23.0
DC-10C-1	Finish Mill No. 2 Feed Belt 806B	PM	0.81	3.5
		PM ₁₀	0.81	3.5
DC-11A	Finish Cement Silos B 4-7	PM	1.43	6.3
		PM ₁₀	1.43	6.3
DC-11B	Finish Cement Silos B 1, 2, 3, and 8	PM	1.43	6.3
		PM ₁₀	1.43	6.3
DC-11C	Truck Bulk Loadout No. 1 B Silos	PM	0.32	1.4
		PM ₁₀	0.32	1.4

Emission Sources - Maximum Allowable Emission Rates

DC-11D	Truck Bulk Loadout No. 2 B Silos	PM	0.32	1.4
		PM ₁₀	0.32	1.4
DC-11E	Clinker Loadout Silos	PM	1.0	4.3
		PM ₁₀	1.0	4.3
DC-11F	Clinker Loadout	PM	0.73	3.2
		PM ₁₀	0.73	3.2
DC-13	Clinker Storage Building	PM	3.0	13.0
		PM ₁₀	3.0	13.0
DC-13A	Fringe Bin	PM	0.65	2.8
		PM ₁₀	0.65	2.8
DC-20	Clinker Fines Dust Bin	PM	0.22	0.95
		PM ₁₀	0.22	0.95
FUG-1	Coal Stockpile and Material Handling (10)	PM	-	1.82
		PM ₁₀	-	0.91
FUG-2	Iron Stockpile and Material Handling (10)	PM	-	0.84
		PM ₁₀	-	0.44
FUG-3	Sand Stockpile and Material Handling (10)	PM	-	1.39
		PM ₁₀	-	0.70
FUG-4	Road Emissions (10)	PM	-	2.43
		PM ₁₀	-	2.43
FUG-5	Street Sweeper Dump and Material Handling (10)	PM	-	0.40
		PM ₁₀	-	0.20
MSSFUG	ILE Maintenance Fugitives (10)	NO _x	0.13	<0.01
		CO	1.84	0.02
		VOC	0.36	<0.01
		PM	0.68	0.17
		PM ₁₀	0.31	0.09
		PM _{2.5}	0.06	0.03
		SO ₂	<0.01	<0.01

- (1) Emission point identification - either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources, use area name or fugitive source name.
- (3) VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
NO_x - total oxides of nitrogen
SO₂ - sulfur dioxide

Emission Sources - Maximum Allowable Emission Rates

- PM - total particulate matter, suspended in the atmosphere, including PM₁₀ and PM_{2.5}, as represented
 - PM₁₀ - total particulate matter equal to or less than 10 microns in diameter, including PM_{2.5}, as represented
 - PM_{2.5} - particulate matter equal to or less than 2.5 microns in diameter
 - CO - carbon monoxide
 - HCl - hydrogen chloride
 - Pb - lead or lead compounds
 - H₂SO₄ - sulfuric acid
- (4) Compliance with annual emission limits (tons per year) is based on a 12 month rolling period.
 - (5) Planned maintenance, startup, and shutdown emissions are included.
 - (6) Emissions from DC-4 must comply with New Source Performance Standard, Subpart F. Combined emissions from DC-2 and DC-9 must also comply with New Source Performance Standard, Subpart F.
 - (7) The permit holder has committed to achieve a SO₂ limitation of 416 lbs/hr based on a 24-hour rolling average as measured by CEMS no later than May 1, 2001.
 - (8) PM allowables for prevention of significant deterioration permit, based on front-half PM emissions only as measured by the U.S. Environmental Protection Agency Method 5.
 - (9) PM allowables for state permit, for PM emissions as defined in 30 TAC § 101.1.
 - (10) Emission rate is an estimate and is enforceable through compliance with the applicable special condition(s) and permit application representations.

Date: February 13, 2014