#### EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

## Permit No. 38389

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

### AIR CONTAMINANTS DATA

Emission *	Source Ai	r Contaminant	<u>Emission</u>	Rates
Point No. (1)	Name (2)	Name (3)	1b/hr	TPY
1	Zinc Kettle Baghouse Stack	$PM_{10}$ (5) $NH_4C1$ ZnO $ZnC1_2$ Zn $NH_3$	0.090 0.061 0.014 0.004 0.005 0.001	0.29 0.20 0.05 0.01 0.02 <0.01
BLDG1-FUG	Building 1 Fugitives (4 0.81 Pickle Tanks 1, 2, & 3, Caustic and Preflux Tanks 0.44	,5, &6) PM/P VOC ,	0.01 CO	0.26 0.03 0.10
	Chromate Conversion Tank, Zinc Kettle Fugitives, and Immersion Heaters	NOx HC1 SO <sub>2</sub> NH <sub>4</sub> C1 ZnO ZnC1 <sub>2</sub> Zn NH <sub>3</sub> CrO <sub>3</sub> NaOH Na <sub>2</sub> SiO <sub>3</sub> ·5H <sub>2</sub> O	0.12 0.02 <0.001 0.170 0.040 0.010 0.013 0.003 <0.01 <0.01	0.52 0.08 <0.01 0.52 0.12 0.03 0.04 0.01 <0.02 <0.01 <0.01
5	Kettle Burner Stack	$PM_{10}$ VOC $NO_x$ $SO_2$ CO	0.04 0.03 0.55 <0.01 0.46	0.18 0.13 2.40 <0.01 2.02
SCRUB-1	Pickle Tanks Scrubber Tanks T-HCl-1, T-HCl-2, T-HCl-3, and T-HCl-4	HC1	0.03	0.06

#### EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

BLDG2-FUG	Building 2 Fugitives (4) 0.10	ı	PM/PM10	0.02
	(Caustic Tank, Preflux Tank 0.07	ζ,	VOC	0.02
	Immersion Heater, and	S02	0.002	0.01
	and Pickle Tanks T-HCl-1,	CO	0.25	1.08
	T-HCl-2, T-HCl-3, and T-HCl	l-4)	NOx	0.29
		HC1	0.09	0.16
		NaOH	<0.01	<0.04
		$Na_2SiO_3 \cdot 5H_2$	0 < 0.01	<0.01

- (1) Emission point identification either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources use area name or fugitive source name.
- (3) PM particulate matter, suspended in the atmosphere, including  $PM_{10}$ .
  - $PM_{10}$  particulate matter equal to or less than 10 microns in diameter. Where PM is not listed, it shall be assumed that no particulate matter greater than 10 microns is emitted.
  - VOC volatile organic compounds as defined in General Rule 101.1

 $NO_x$  - total oxides of nitrogen

SO<sub>2</sub> - sulfur dioxide CO - carbon monoxide HCl - hydrogen chloride NH<sub>4</sub>Cl - ammonium chloride

ZnO - zinc oxide ZnCl<sub>2</sub> - zinc chloride

Zn - zinc NH<sub>3</sub> - ammonia CrO<sub>3</sub> - chromate

NaOH - sodium hydroxide

 $Na_2SiO_3 \cdot 5H_2O$  - sodium metasilicate pentahyrate

- (4) Fugitive emissions are an estimate only and should not be considered as a maximum allowable emission rate.
- (5)  $PM/PM_{10}$  includes  $NH_4Cl$ , ZnO,  $ZnCl_2$ , Zn, and  $NH_3$ .
- (6) The caustic tank, HCl acid tanks, preflux tank, and immersion heaters operating in Building No. 1 will be

removed from service when the replacement facilities in Building No. 2

# EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

become ope	erational.						
* Emission rates are based on and the facilities are limited by the following maximum operating schedule:							
Hrs/year	Hrs/day	Days/week	Weeks/year or <u>8,760</u>				
			Dated	k			