EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Permit Number 21258

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

AIR CONTAMINANTS DATA

Emission	Source	Air Contaminant	Emission Rates *	
Point No. (1)	Name (2)	Name (3)	lb/hr	TPY
D-1	Baghouse Stack	PM_{10}	14.67	11.74
		VOC(a)	16.00	12.80
		NO _x	27.50	22.00
		SO ₂	29.00	23.20
		СО	65.00	52.00
H-1	Asphalt Heater Vent (4)	PM_{10}	0.07	0.32
		VOC	0.01	0.03
		NO _x	0.44	1.92
		SO ₂	0.16	0.68
		СО	0.11	0.48
T-1	Diesel Storage Tank (4)	VOC	0.12	0.01
T-2, T-3, T-4	Asphalt Storage Tank (4)	PM_{10}	0.01	<0.01
		VOC	0.65	0.17
		СО	0.06	0.02
T-5	Reclaimed Industrial Fuel Oil Tank (4)	VOC	0.36	0.03
SF-1	Storage Silo Filling (4)	PM_{10}	0.17	0.14
	3 ()	VOC	0.32	0.25
		CO	0.03	0.03
PL-1	Truck Loadout (4)	PM_{10}	0.10	0.08
	,	VOC	0.10	0.08
		СО	0.04	0.03

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

AIR CONTAMINANTS DATA

Emission	Source	Air Contaminant	Emission Rates *	
Point No. (1)	Name (2)	Name (3)	lb/hr	TPY
RAP	RAP Crusher and Screen (4)	PM PM ₁₀	0.30 0.14	0.28 0.14
FUG-1	Material Handling (4)	PM PM ₁₀	2.43 1.15	1.94 0.92
FUG-2	Aggregate Stockpiles (4)	PM PM ₁₀		0.36 0.18

- (1) Emission point identification either specific equipment designation or emission point number from a plot plan.
- (2) Specific point source names. For fugitive sources use area name or fugitive source name.
- (3) PM particulate matter, suspended in the atmosphere, including PM₁₀
 - PM₁₀ particulate matter equal to or less than less than 10 microns in diameter. Where PM is not listed, it shall be assumed that no particulate matter greater than 10 microns is emitted.
 - VOC volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
 - VOC(a) mainly asphalt vapors from standard mix
 - NO_x total oxides of nitrogen
 - SO₂ sulfur dioxide CO - carbon monoxide
- (4) Fugitive emissions are an estimate only.
- * Emission rates are based on and the facilities are limited by the following maximum operating schedule and production rates:
- <u>24</u> Hrs/day <u>7</u> Days/week <u>52</u> Weeks/year or <u>8,760</u> Hrs/year
 - Standard Hot Mix: Tons/hour 500 Tons/year 800,000