

Emission Sources - Maximum Allowable Emission Rates

Permit Numbers 5628 and PSDTX905

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities, sources, and related activities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

Air Contaminants Data

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates (6)	
			lbs/hour	TPY (4)
S-03	Boiler No. 3 Scrubber Stack	VOC	32.00	100.01
		NO _x	44.00	130.85
		SO ₂	1.85	8.11
		PM	44.00	130.85
		PM ₁₀	44.00	130.85
		PM _{2.5}	18.22	79.81
		CO	1062.00	3427.06
RTO/RCO	Regenerative Thermal/Catalytic Oxidizer Stack	VOC*	18.85	64.40
		NO _x	2.05	7.54
		SO ₂	0.01	0.03
		PM	3.74	12.84
		PM ₁₀	3.74	12.84
		PM _{2.5}	3.74	12.84
		CO	7.04	24.70
S-08#	Veneer Dryers Cooling Zone Stacks (No. 1)	VOC**	0.88	3.00
		PM	0.83	2.85
		PM ₁₀	0.83	2.85
		PM _{2.5}	0.83	2.85
		CO	0.66	2.26
S-09#	Veneer Dryers Cooling Zone	VOC**	1.10	3.75

Emission Sources - Maximum Allowable Emission Rates

		PM	1.04	3.56
		PM ₁₀	1.04	3.56
		PM _{2.5}	1.04	3.56
		CO	0.83	2.83
S-10#	Veneer Dryers Cooling Zone Stacks (No. 3)	VOC**	1.10	3.75
		PM	1.04	3.56
		PM ₁₀	1.04	3.56
		PM _{2.5}	1.04	3.56
		CO	0.83	2.83
S-11#	Veneer Dryers Cooling Zone Stacks (No. 4)	VOC**	1.32	4.50
		PM	1.25	4.27
		PM ₁₀	1.25	4.27
		PM _{2.5}	1.25	4.27
		CO	0.99	3.39
S-14	Dry Waste Baghouse Stack	PM	0.89	3.90
		PM ₁₀	0.89	3.90
		PM _{2.5}	0.89	3.90
S-15	Sander Baghouse Stack	PM	0.79	3.46
		PM ₁₀	0.79	3.46
		PM _{2.5}	0.79	3.46
S-16	Dry Waste Cyclone Stack	PM	0.21	0.92
		PM ₁₀	0.21	0.92
		PM _{2.5}	0.21	0.92
S-17	Sander Dust Baghouse on Silo	PM	0.04	0.18
		PM ₁₀	0.04	0.18

Emission Sources - Maximum Allowable Emission Rates

		PM _{2.5}	0.04	0.18
S-18A	Shavings House/Truck Bin Cyclone Stack	PM	2.06	9.03
		PM ₁₀	2.06	9.03
		PM _{2.5}	2.06	9.03
S-19	Fuel House Cyclone Stack	PM	0.30	1.32
		PM ₁₀	0.30	1.32
		PM _{2.5}	0.30	1.32
S-21	Package Boiler Stack	VOC	0.42	0.19
		NO _x	23.50	10.29
		SO ₂	0.35	0.15
		PM	5.55	2.43
		PM ₁₀	5.55	2.43
		PM _{2.5}	5.55	2.43
		CO	8.90	3.67
K-01	Existing Batch Kiln No. 1	VOC	28.80	126.14
		PM	0.71	3.11
		PM ₁₀	0.71	3.11
		PM _{2.5}	0.71	3.11
K-03 and ABRTSTK	Continuous Kiln No. 3 and Burner Abort Stack	VOC	77.75	340.55
		NO _x	5.71	25.02
		SO ₂	1.18	5.15
		PM	3.53	15.47
		PM ₁₀	3.53	15.47
		PM _{2.5}	3.53	15.47
		CO	13.78	60.34

Emission Sources - Maximum Allowable Emission Rates

V-01	Plywood Presses	VOC	31.96	120.61
		PM	10.18	38.42
		PM ₁₀	6.81	25.70
		PM _{2.5}	6.81	25.70
		HCHO	0.89	3.33
V-02	Glue Loft Vent	VOC	1.58	3.53
		PM	3.50	7.67
		PM ₁₀	3.50	7.67
		PM _{2.5}	3.50	7.67
F-01	MTL Sawline (5)	PM	0.01	0.01
		PM ₁₀	0.01	0.01
		PM _{2.5}	0.01	0.01
F-02	Fiber Line (5)	PM	0.01	0.01
		PM ₁₀	0.01	0.01
		PM _{2.5}	0.01	0.01
F-03	Ring Debarker (5)	PM	2.42	10.60
		PM ₁₀	2.42	10.60
		PM _{2.5}	1.00	4.37
F-04	Drum Debarker (5)	PM	0.31	1.36
		PM ₁₀	0.31	1.36
		PM _{2.5}	0.13	0.56
F-05	Even End Saw (5)	PM	0.01	0.01
		PM ₁₀	0.01	0.01
		PM _{2.5}	0.01	0.01
F-08	Stud Mill Trim Saws (5)	PM	0.01	0.01

Emission Sources - Maximum Allowable Emission Rates

		PM ₁₀	0.01	0.01
		PM _{2.5}	0.01	0.01
F-09	Traditional Lathe Log Vats (5)	VOC	14.00	61.32
F-09A	Centerless Lathe Log Vats (5)	VOC	4.20	18.40
F-12	Chip Pad Truck Bin (5)	PM	0.01	0.02
		PM ₁₀	0.01	0.02
		PM _{2.5}	0.01	0.02
F-14	Stud Mill Truck Bin (5)	PM	0.01	0.02
		PM ₁₀	0.01	0.02
		PM _{2.5}	0.01	0.02
F-17	Shavings Truck Bin (5)	PM	0.01	0.02
		PM ₁₀	0.01	0.02
		PM _{2.5}	0.01	0.02
F-18	Sawmill Building (5)	PM	0.01	0.01
		PM ₁₀	0.01	0.01
		PM _{2.5}	0.01	0.01
F-19	Fuel House (5)	PM	0.26	1.14
		PM ₁₀	0.26	1.14
		PM _{2.5}	0.08	0.34
F-20	Lathe/Green End (5)	VOC	0.31	1.36
F-21	Plywood Sander (5)	VOC	10.48	45.89

- (1) Emission point identification - either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources, use area name or fugitive source name.
- (3) VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
NO_x - total oxides of nitrogen
SO₂ - sulfur dioxide

Emission Sources - Maximum Allowable Emission Rates

- PM - total particulate matter, suspended in the atmosphere, including PM₁₀ and PM_{2.5}, as represented
- PM₁₀ - total particulate matter equal to or less than 10 microns in diameter, including PM_{2.5}, as represented
- PM_{2.5} - particulate matter equal to or less than 2.5 microns in diameter
- CO - carbon monoxide
- HCHO - formaldehyde
- (4) Compliance with annual emission limits (tons per year) is based on a 12-month rolling period.
- (5) Emission rate is an estimate and is enforceable through compliance with the applicable special condition(s) and permit application representations.
- (6) Planned startup and shutdown emissions are included. Maintenance activities are not authorized by this permit.
- * VOC presented on a carbon basis.
- ** VOC presented on a WPPI/propane basis
- # For determination of compliance, the emission rates should be summed up for the veneer dryer cooling zones (EPNs S-08, S-09, S-10, and S-11).

Dated: March 26, 2013