EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Permit Number 188K

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

AIR CONTAMINANTS DATA

| Emission | Source | Air Contaminant | Emission Rates * | |
|---------------|-------------------------|-----------------|------------------|--------|
| Point No. (1) | Name (2) | Name (3) | lb/hr | TPY |
| . , | • | • • | | |
| 10 | Wet Scrubber Stack | PM | 45.50 | 45.92 |
| | | VOC(a) | 10.40 | 9.54 |
| | | VOC(b) | 73.45 | 4.52 |
| | | VOC(c) | 612.50 | 35.00 |
| | | NO_x | 17.88 | 18.04 |
| | | SO_2 | 18.85 | 19.02 |
| | | CO | 42.25 | 42.64 |
| | | | | |
| 11 | Lime Storage Silo | PM_{10} | 0.05 | < 0.01 |
| | | | | |
| F1 | Stockpile Fugitives (4) | PM | - | 0.41 |
| | | PM_{10} | - | 0.20 |
| | | VOC(c) | 10.08 | 17.50 |
| | | | | |
| F2 | Material Handling (4) | PM | 0.56 | 0.69 |
| | | PM_{10} | 0.48 | 0.47 |
| | | | | |
| 19 | Hot Oil Heater | PM_{10} | 0.03 | 0.06 |
| | | VOC | 0.01 | 0.02 |
| | | NO_x | 0.28 | 0.61 |
| | | SO_2 | 0.60 | 1.31 |
| | | CO | 0.07 | 0.15 |

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

- (1) Emission point identification either specific equipment designation or emission point number from a plot plan.
- (2) Specific point source names. For fugitive sources use area name or fugitive source name.
- (3) PM particulate matter, suspended in the atmosphere, including PM₁₀
 - PM_{10} particulate matter equal to or less than 10 microns in diameter. Where PM is not listed, it shall be assumed that no particulate matter greater than 10 microns is emitted.
 - VOC volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
 - VOC(a) mainly asphalt vapors
 - VOC(b) additional VOC due to the use of crumb rubber
 - VOC(c) primarily diesel or kerosene vapors
 - NO_x total oxides of nitrogen
 - SO₂ sulfur dioxide
 - CO carbon monoxide
- (4) Fugitive emissions are an estimate only and should not be considered as a maximum allowable emission rate.
- * Emission rates are based on and the facilities are limited by the following maximum operating schedule and production rates:

Hrs/day 8 Days/week 5 Weeks/year 52

Standard Hot Mix: Tons/hour 325 Tons/year 656,000

Hot Mix w/Crumb Rubber option: Tons/hour 325 Tons/year 40,000

Cutback Cold Mix: Tons/hour 175 Tons/week 2,400 Tons/year 20,000

Total Hot Mix Production: Tons/year <u>656,000</u> from any combination of the above but not to exceed above limits.