EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Permit Number 3149

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	<u>Emissio</u> lb/hr	n Rates * TPY**
1	Scrubber Stack	CO H_2SO_4 NO_x Pb PM_{10} SO_2 (6) SO_2 VOC VOC (5)	18.40 3.54 18.00 0.18 3.60 275.00 400.00 1.02 60.14	80.50 15.51 65.70 0.79 15.90 1005.00 4.48 17.14
2	No. 1 Sulfite Storage Tank	NaHSO ₃ /Na ₂ SO ₃ /SO	2.20	
3	No. 2 Sulfite Storage Tank	² NaHSO ₃ /Na ₂ SO ₃ /SO	2.20	
4	No. 3 Sulfite Storage Tank	² NaHSO ₃ /Na ₂ SO ₃ /SO	2.20	
5	No. 19 Sulfite Storage Tank Annual Tank Emission Cap	NaHSO ₃ /Na ₂ SO ₃ /SO NaHSO ₃ /Na ₂ SO ₃ /SO	2.20	0.81
FUG	Process Piping Fugitives	VOC	1.31	5.73
6	(4) SBS (Sodium Bisulfite) Scrubber	NaHSO ₃ /Na ₂ SO ₃ /SO ₂	0.44	0.08
6MSS	SBS Scrubber MSS Emissions	NaHSO ₃ /Na ₂ SO ₃ /SO	4.40	0.37
MSSFUG	Miscellaneous Ma M tenance Activities	PM ₁₀ VOC	0.13 74.5	0.01 0.23

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

0.1 0.01

7 MSS Tank Vent Scrubber SO_2 0.30 0.85 VOC 0.10 0.28

- (1) Emission point identification either specific equipment designation or emission point number from a plot plan.
- (2) Specific point source names. For fugitive sources, use an area name or fugitive source name.
- (3) VOC volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1

NO_x - total oxides of nitrogen

SO₂ - sulfur dioxide

Pb - lead

PM - particulate matter, suspended in the atmosphere, including PM₁₀ and PM_{2.5}

PM₁₀ - particulate matter equal to or less than 10 microns in diameter PM_{2.5} - particulate matter equal to or less than 2.5 microns in diameter

CO - carbon monoxide
H₂SO₄ - sulfuric acid mist
NaHSO₃ - sodium bisulfite
Na₂SO₃ - sodium sulfite

- (4) Fugitive emissions are an estimate only and should not be considered as a maximum allowable emission rate.
- (5) 6,760 hours per year of VOC emitting from Storage Tank Nos. 7, 8, 11, and 14 without furnace combustion.
- (6) Monthly average SO₂ emissions from this emission point number.
- * Emission rates are based on and the facilities are limited by the following maximum operating schedule:

24 Hrs/day 7 Days/week 52 Weeks/year or 8,760 Hrs/year

** Compliance with annual emission limits is based on a rolling 12-month period.