

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Permit Number 26080

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

### AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	<u>Emission Rates</u>	
			lb/hr	TPY
1	Raw Material Unloading and Storage Baghouse Stack	PM/PM <sub>10</sub>	0.77	3.39
2	Scrap Tile Processing and Material Weigh/Feed Baghouse Stack	PM/PM <sub>10</sub>	1.86	8.15
3	Screening/Pressing Baghouse Stack	PM/PM <sub>10</sub>	2.06	9.04
4	Glaze Prep/Tile Glazing Baghouse Stack	PM/PM <sub>10</sub>	0.57	2.51
5	Tile Dryer Line No. 2 Stack	PM/PM <sub>10</sub>	0.08	0.33
		VOC	0.15	0.65
		NO <sub>x</sub>	0.05	0.22
		CO	0.75	3.26
		SO <sub>2</sub>	<0.01	<0.01
		HF (4)	<0.01	<0.01
		HCl (4)	<0.01	<0.01
6	Tile Dryer Line No. 1 Stack	PM/PM <sub>10</sub>	0.08	0.33
		VOC	0.15	0.65
		NO <sub>x</sub>	0.05	0.22
		CO	0.75	3.26
		SO <sub>2</sub>	<0.01	<0.01
		HF (4)	<0.01	<0.01
		HCl (4)	<0.01	<0.01

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

11	Spray Dryer Scrubber Stack	PM/PM <sub>10</sub>	5.97	26.14
		VOC	0.29	1.26
		NO <sub>x</sub>	2.30	10.05
		CO	0.39	1.69
		SO <sub>2</sub>	0.01	0.03
		HF (4)	0.58	2.53
		HCl (4)	0.04	0.17
13	Body Material Storage Baghouse Stack	PM/PM <sub>10</sub>	0.63	2.75
14	Tile Dryer Line No. 4 Stack	PM/PM <sub>10</sub>	0.08	0.33
		VOC	0.15	0.65
		NO <sub>x</sub>	0.05	0.22
		CO	0.75	3.26
		SO <sub>2</sub>	<0.01	<0.01
		HF (4)	<0.01	<0.01
		HCl (4)	<0.01	<0.01
15	Tile Dryer Line No. 3 Stack	PM/PM <sub>10</sub>	0.08	0.33
		VOC	0.15	0.65
		NO <sub>x</sub>	0.05	0.22
		CO	0.75	3.26
		SO <sub>2</sub>	<0.01	<0.01
		HF (4)	<0.01	<0.01
		HCl (4)	<0.01	<0.01
20	Tile Dryer Line No. 5 Stack	PM/PM <sub>10</sub>	0.08	0.33
		VOC	0.15	0.65
		NO <sub>x</sub>	0.05	0.22
		CO	0.75	3.26
		SO <sub>2</sub>	<0.01	<0.01
		HF (4)	<0.01	<0.01
		HCl (4)	<0.01	<0.01
23	Screening/Pressing Baghouse Stack	PM/PM <sub>10</sub>	0.68	2.96
24	Tile Dryer Line No. 6 Stack	PM/PM <sub>10</sub>	0.07	0.33
		VOC	0.15	0.65
		NO <sub>x</sub>	0.05	0.22
		CO	0.74	3.26

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

		SO <sub>2</sub>	<0.01	<0.01
		HF (4)	<0.01	<0.01
		HCl (4)	<0.01	<0.01
27	Crusher and Screening Baghouse Stack	PM/PM <sub>10</sub>	1.63	7.17
28	Tile Glazing Baghouse Stack	PM/PM <sub>10</sub>	0.13	0.57
29	Common Kiln Stack (12 Kilns)	PM/PM <sub>10</sub>	6.58	28.80
		VOC	0.71	3.13
		NO <sub>x</sub>	11.39	49.91
		CO	7.26	31.80
		SO <sub>2</sub>	47.72	209.03
		HF (4)	24.31	106.47
		HCl (4)	7.48	32.76

- (1) Emission point identification - either specific equipment designation or emission point number from a plot plan.
- (2) Specific point source names. For fugitive sources, use an area name or fugitive source name.
- (3) PM - particulate matter, suspended in the atmosphere, including PM<sub>10</sub> and PM<sub>2.5</sub>  
PM<sub>10</sub> - particulate matter equal to or less than 10 microns in diameter  
VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1  
NO<sub>x</sub> - total oxides of nitrogen  
SO<sub>2</sub> - sulfur dioxide  
CO - carbon monoxide  
HCl - hydrogen chloride  
HF - hydrogen fluoride
- (4) Hazardous Air Pollutant as listed in § 112(b) of the Federal Clean Air Act or Title 40 Code of Federal Regulations Part 63, Subpart C.

Dated May 4, 2009