

# Emission Sources - Maximum Allowable Emission Rates

Permit Numbers 36644, PSDTX903M5, and N007M1

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities, sources, and related activities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

## Air Contaminants Data

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
N-1	Recycle Ethane Cracking Furnace H-0100	NO <sub>x</sub> (7) (10)	48.32	-
		NO <sub>x</sub> (7)	24.16	79.37
		SO <sub>2</sub> (7)	2.21	4.83
		CO (7) (11)	46.50	-
		CO (7)	23.25	101.85
		PM <sub>10</sub> (7)	1.51	6.61
		VOC (7)	0.57	2.51
N-2	Fresh Feed Cracking Furnace H-0200	NO <sub>x</sub> (7) (10)	70.68	-
		NO <sub>x</sub> (7)	35.34	116.08
		SO <sub>2</sub> (7)	3.22	7.07
		CO (7) (11)	68.02	-
		CO (7)	34.01	148.97
		PM <sub>10</sub> (7)	2.21	9.67
		VOC (7)	0.84	3.68
N-3	Fresh Feed Cracking Furnace H-0300	NO <sub>x</sub> (7) (10)	70.68	-
		NO <sub>x</sub> (7)	35.34	116.08
		SO <sub>2</sub> (7)	3.22	7.07
		CO (7) (11)	68.02	-
		CO (7)	34.01	148.97
		PM <sub>10</sub> (7)	2.21	9.67
		VOC (7)	0.84	3.68

Emission Sources - Maximum Allowable Emission Rates

N-4	Fresh Feed Cracking Furnace H-0400	NO <sub>x</sub> (7) (10)	70.68	-
		NO <sub>x</sub> (7)	35.34	116.08
		SO <sub>2</sub> (7)	3.22	7.07
		CO (7) (11)	68.02	-
		CO (7)	34.01	148.97
		PM <sub>10</sub> (7)	2.21	9.67
		VOC (7)	0.84	3.68
N-5	Fresh Feed Cracking Furnace H-0500	NO <sub>x</sub> (7) (10)	70.68	-
		NO <sub>x</sub> (7)	35.34	116.08
		SO <sub>2</sub> (7)	3.22	7.07
		CO (7) (11)	68.02	-
		CO (7)	34.01	148.97
		PM <sub>10</sub> (7)	2.21	9.67
		VOC (7)	0.84	3.68
N-6	Fresh Feed Cracking Furnace H-0600	NO <sub>x</sub> (7) (10)	70.68	-
		NO <sub>x</sub> (7)	35.34	116.08
		SO <sub>2</sub> (7)	3.22	7.07
		CO (7) (11)	68.02	-
		CO (7)	34.01	148.97
		PM <sub>10</sub> (7)	2.21	9.67
		VOC (7)	0.84	3.68
N-7	Fresh Feed Cracking Furnace H-0700	NO <sub>x</sub> (7) (10)	70.68	-
		NO <sub>x</sub> (7)	35.34	116.08
		SO <sub>2</sub> (7)	3.22	7.07
		CO (7) (11)	68.02	-
		CO (7)	34.01	148.97
		PM <sub>10</sub> (7)	2.21	9.67
		VOC (7)	0.84	3.68
N-8	Fresh Feed Cracking Furnace H-0800	NO <sub>x</sub> (7) (10)	70.68	-
		NO <sub>x</sub> (7)	35.34	116.08

Emission Sources - Maximum Allowable Emission Rates

		SO <sub>2</sub> (7)	3.22	7.07
		CO (7) (11)	68.02	-
		CO (7)	34.01	148.97
		PM <sub>10</sub> (7)	2.21	9.67
		VOC (7)	0.84	3.68
N-9	Fresh Feed Cracking Furnace H-0900 (487.5 MMBtu/hr maximum)	NO <sub>x</sub> (7) (10)	48.75	-
		NO <sub>x</sub> (7)	12.19	21.35
		SO <sub>2</sub> (7)	5.60	24.53
		CO (7) (11)	34.13	-
		CO (7)	17.06	74.73
		PM <sub>10</sub> (7)	3.63	15.91
		VOC (7)	2.63	11.51
		NH <sub>3</sub>	1.98	8.68
N-16	Fresh Feed Cracking Furnace H-1000 (498 MMBtu/hr maximum)	NO <sub>x</sub> (7) (10)	49.80	-
		NO <sub>x</sub> (7)	12.45	21.81
		SO <sub>2</sub> (7)	4.48	8.72
		CO (7) (11)	69.72	-
		CO (7)	17.43	76.34
		PM (7)	2.49	10.91
		PM <sub>10</sub> (7)	2.49	(15)
		PM <sub>2.5</sub> (7)	2.49	(15)
		VOC (7)	2.69	11.76
		NH <sub>3</sub>	1.98	8.68
N-10	Catalyst Regeneration Effluent	VOC (7)	15.83	0.08
		CO	373.33	1.89
N-11	Reactor Regeneration Effluent (Startup, Shutdown, and Maintenance)	CO	161.43	135.57
		VOC (7)	0.13	0.11
N-12	DP Reactor Feed Heater	NO <sub>x</sub> (7)	5.01	13.71
		SO <sub>2</sub> (7)	0.44	0.95
		CO (7)	4.40	12.26

Emission Sources - Maximum Allowable Emission Rates

		PM <sub>10</sub> (7)	0.38	1.64
		VOC (7)	0.17	0.74
	DP Reactor Feed Heater Startup Emission Rate	CO (7)	14.50	1.74
N-13	DP Reactor Regeneration Heater	NO <sub>x</sub> (7)	1.73	1.42
		SO <sub>2</sub> (7)	0.14	0.10
		CO (7)	2.37	3.13
		PM <sub>10</sub> (7)	0.13	0.17
		VOC (7)	0.06	0.08
N-14	Auxiliary Boiler	NO <sub>x</sub>	13.60	-
		SO <sub>2</sub>	1.24	-
		CO	15.60	-
		PM <sub>10</sub>	1.58	-
		VOC	1.58	-
N-20A	GTG HRSG Unit 1 GE Frame 6B, 310.4 MMBtu/hr Duct Burner (with SCR)	NO <sub>x</sub>	17.65	-
		SO <sub>2</sub>	4.53	-
		CO	89.51	-
		PM <sub>10</sub>	5.55	-
		PM <sub>2.5</sub>	5.55	-
		VOC	4.09	-
		NH <sub>3</sub>	7.61	28.20
N-20B	GTG HRSG Unit 2 GE Frame 6B, 310.4 MMBtu/hr Duct Burner (with SCR)	NO <sub>x</sub>	17.65	-
		SO <sub>2</sub>	4.53	-
		CO	89.51	-
		PM <sub>10</sub>	5.55	-
		PM <sub>2.5</sub>	5.55	-
		VOC	4.09	-
		NH <sub>3</sub>	7.61	28.20
Emission Point Nos. N-14, N-20A, and N-20B are subject to the following combined annual emission caps for the specified pollutants:				

Emission Sources - Maximum Allowable Emission Rates

N-14, N-20A, and N-20B	Annual Emission Caps	NO <sub>x</sub>	-	102.96
		SO <sub>2</sub>	-	8.27
		CO	-	349.85
		PM <sub>10</sub>	-	46.78
		PM <sub>2.5</sub>	-	(15)
		VOC	-	32.17
N-18	Decoking Drum	CO (7)	3,360.00	204.09
		PM <sub>10</sub> (7)	78.73	3.98
		PM <sub>2.5</sub> (7)	78.73	(15)
N-19	Thermal Oxidizer	NO <sub>x</sub> (7)	0.24	0.89
		SO <sub>2</sub> (7)	0.08	0.28
		CO (7)	0.21	0.78
		PM (7)	0.04	0.13
		PM <sub>10</sub> (7)	0.04	0.13
		PM <sub>2.5</sub> (7)	0.04	0.13
		VOC (7)	0.03	0.14
N-15 and N-15A	Flare System Emission Limits Applicable During Routine Operations exclusive of planned turnarounds	NO <sub>x</sub> (7)	252.70	45.57
		CO (7)	1,046.49	176.01
		SO <sub>2</sub> (7)	0.56	1.32
		H <sub>2</sub> S	<0.01	<0.01
		VOC (7)	631.15	170.37
	Flare System Emission Limits Applicable to MSS Activities, Including Planned Major and Minor Plant Turnarounds	NO <sub>x</sub> (7)	1,069.42	35.83
		CO (7)	5,279.52	174.20
		SO <sub>2</sub> (7)	17.12	1.46
		H <sub>2</sub> S	0.19	0.02
		VOC (7)	6,795.57	169.10
	Acetylene Converter Swaps	NO <sub>x</sub> (7) (16)	364.76	-
		CO (7) (16)	2,634.43	-
		VOC (7) (16)	2,778.73	-
	Flare System Emission Limits Applicable to all operations	VOC	-	241.07

Emission Sources - Maximum Allowable Emission Rates

N-21A	Fire Pump Diesel Engine (6)	NO <sub>x</sub> (7)	15.81	1.23
		SO <sub>2</sub> (7)	1.05	0.08
		CO (7)	3.41	0.27
		PM <sub>10</sub> (7)	1.12	0.09
		VOC (7)	1.26	0.10
N-21B	Fire Pump Diesel Engine (6)	NO <sub>x</sub> (7)	15.81	1.23
		SO <sub>2</sub> (7)	1.05	0.08
		CO (7)	3.41	0.27
		PM <sub>10</sub> (7)	1.12	0.09
		VOC (7)	1.26	0.10
N-22	Carbon Bed Adsorber	VOC (5)	0.31	0.11
		Benzene	0.31	0.11
N-23	Ammonia Scrubber	NH <sub>3</sub>	0.12	0.51
N-24A	Boiler B-7280 (425.4 MMBtu/hr)	VOC (7)	1.70	6.66
		NO <sub>x</sub> (Routine)	4.25	16.64
		NO <sub>x</sub> (Startup)	17.02	1.23
		CO (7)	14.89	18.31
		SO <sub>2</sub>	7.91	16.67
		PM <sub>10</sub> (7)	2.13	8.32
		PM <sub>2.5</sub> (7)	2.13	(15)
		NH <sub>3</sub>	1.87	7.33
N-24B	Boiler B-7290 (425.4 MMBtu/hr)	VOC (7)	1.70	6.66
		NO <sub>x</sub> (Routine)	4.25	16.64
		NO <sub>x</sub> (Startup)	17.02	1.23
		CO (7)	14.89	18.31
		SO <sub>2</sub>	7.91	16.67
		PM <sub>10</sub> (7)	2.13	8.32
		PM <sub>2.5</sub> (7)	2.13	(15)
		NH <sub>3</sub>	1.87	7.33
N-24A and N-24B	Annual Cap - Boilers B-7280 and B-7290	SO <sub>2</sub>	-	23.42

## Emission Sources - Maximum Allowable Emission Rates

N-1 through N-9, N-14, N-15, N-15A, N-16, N-19, N-20A, and N-20B	Fresh Feed Cracking Furnaces, Auxiliary Boiler, Flare System, Cogeneration Facility, and Thermal Oxidizer (9)	Mercury (9)	0.63	0.039
TK-2501	IFR Spent Caustic	VOC (7)	0.32	0.35
TK-2501B	Tank TK-2501B	VOC	0.41	0.37
TK-8001	IFR WW Equalization	VOC (7)	0.39	0.62
TK-8101	EFR Contaminated Storm water	VOC (7)	0.49	0.49
TK-7702	Sulfuric Acid Tank	H <sub>2</sub> SO <sub>4</sub>	0.01	0.01
		SO <sub>3</sub>	0.01	0.01
TK1701	Tank TK1701	VOC	4.97	0.02
TK1702	Tank TK1702	VOC	1.50	< 0.01
TK1703	Tank TK1703	VOC	1.28	< 0.01
TK1704	Tank TK1704	VOC	1.68	< 0.01
TK-CWT	Water Treatment Chemicals Storage	VOC	0.42	1.86
F-1	Fugitives (12)	VOC (7)	11.64	50.99
F-2 and F-2A	Cooling Tower System	PM <sub>10</sub> (7)	2.13	2.76
		VOC (5) (7)	25.00	42.45
		Benzene	0.50	1.99
F-4	Benzene/Toluene Process Fugitives (12)	VOC (7)	0.70	3.07
		H <sub>2</sub> S	0.01	0.02
F-5	C4 Huntsman Pipeline Fugitives (12)	VOC	0.01	0.05
BOIL-AMM	Fugitives: Boilers 7280 and 7290 - Ammonia Injection System (12)	NH <sub>3</sub>	0.01	0.02
COG-AMM-1	Ammonia Fugitives: Storage Tank and Vaporizer (12)	NH <sub>3</sub>	0.01	0.06
COG-AMM-2	Ammonia Fugitives: GTG/HRSG Unit 2 SCR - Ammonia Injection System (12)	NH <sub>3</sub>	0.01	0.01
COG-AMM-3	Ammonia Fugitives: GTG/HRSG Unit 1 SCR - Ammonia Injection System (12)	NH <sub>3</sub>	0.01	0.01
FURN-AMM	Ammonia Fugitives: Fresh Feed Cracking Furnaces H-0900 and H-1000- Ammonia Injection System (12)	NH <sub>3</sub>	0.03	0.11
AH-98002	Analyzer Vent	VOC	< 0.01	< 0.01
		SO <sub>2</sub>	< 0.01	< 0.01

Emission Sources - Maximum Allowable Emission Rates

AH-009A	Analyzer Vent	VOC	< 0.01	< 0.01
AH-009B	Analyzer Vent	VOC	< 0.01	< 0.01
AH-007	Analyzer Vent	VOC	< 0.01	< 0.01
<b>PLANNED TURNAROUND AND MSS CAPs</b>				
TA CAP	Turnaround CAP (Non-Flare)	VOC	16.03	4.61
		PM	0.30	2.08
		PM <sub>10</sub>	0.02	(15)
		PM <sub>2.5</sub>	0.01	(15)
MSS Cap	MSS CAP (Non-Flare)	VOC	26.90	4.76
		PM	0.74	1.43
		PM <sub>10</sub>	0.49	(15)
		PM <sub>2.5</sub>	0.03	(15)
N-1	Recycle Ethane Cracking Furnace H-0100 Startup	NO <sub>x</sub>	48.32	(13)
		CO	93.02	(13)
N-2	Fresh Feed Cracking Furnace H-0200 Startup	NO <sub>x</sub>	70.68	(13)
		CO	136.04	(13)
N-3	Fresh Feed Cracking Furnace H-0300 Startup	NO <sub>x</sub>	70.68	(13)
		CO	136.04	(13)
N-4	Fresh Feed Cracking Furnace H-0400 Startup	NO <sub>x</sub>	70.68	(13)
		CO	136.04	(13)
N-5	Fresh Feed Cracking Furnace H-0500 Startup	NO <sub>x</sub>	70.68	(13)
		CO	136.04	(13)
N-6	Fresh Feed Cracking Furnace H-0600 Startup	NO <sub>x</sub>	70.68	(13)
		CO	136.04	(13)
N-7	Fresh Feed Cracking H-0700 Startup	NO <sub>x</sub>	70.68	(13)
		CO	136.04	(13)
N-8	Fresh Feed Cracking H-0800 Startup	NO <sub>x</sub>	70.68	(13)
		CO	136.04	(13)
N-9	Fresh Feed Cracking H-0900 Startup	NO <sub>x</sub>	48.75	(13)



Emission Sources - Maximum Allowable Emission Rates

		CO	34.13	(13)
N-16	Fresh Feed Cracking H-1900 Startup	NO <sub>x</sub>	49.80	(13)
		CO	69.72	(13)
N-12	DP Reactor Feed Heater Startup	NO <sub>x</sub>	15.02	(13)
		CO	14.52	(13)
N-13	DP Reactor Regeneration Heater	NO <sub>x</sub>	3.45	(13)
		CO	4.74	(13)
N-14	Auxiliary Boiler Startup	NO <sub>x</sub>	27.12	(13)
		CO	31.19	(13)
N-20A	GTG HRSG Unit 1 Startup	NO <sub>x</sub>	123.53	(13)
		CO	716.12	(13)
N-20B	GTG HRSG Unit 2 Startup	NO <sub>x</sub>	123.53	(13)
		CO	716.12	(13)
N-24A	Boiler B-7280 Startup	NO <sub>x</sub>	17.02	(13)
		CO	29.78	(13)
N-24B	Boiler B-7290 Startup	NO <sub>x</sub>	17.02	(13)
		CO	29.78	(13)
GTGENG-1	Cogen Starting Engine Unit #20A (14)	VOC	0.01	0.01
		NO <sub>x</sub>	16.48	0.79
		CO	5.17	0.25
		SO <sub>2</sub>	0.01	0.01
		PM <sub>10</sub>	0.71	0.03
		PM <sub>2.5</sub>	0.71	(15)
GTGENG-2	Cogen Starting Engine Unit #20B (14)	VOC	0.01	0.01
		NO <sub>x</sub>	16.48	0.79
		CO	5.17	0.25
		SO <sub>2</sub>	0.01	0.01
		PM <sub>10</sub>	0.71	0.03
		PM <sub>2.5</sub>	0.71	(15)

Emission Sources - Maximum Allowable Emission Rates

- (1) Emission point identification - either specific equipment designation or EPN from plot plan.
- (2) Specific point source name. For fugitive sources, use area name or fugitive source name.
- (3) VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1  
CO - carbon monoxide  
NO<sub>x</sub> - total oxides of nitrogen  
SO<sub>2</sub> - sulfur dioxide  
SO<sub>3</sub> - sulfur trioxide  
PM - total particulate matter (PM), suspended in the atmosphere, including PM<sub>10</sub> and PM<sub>2.5</sub>, as represented  
PM<sub>10</sub> - total PM equal to or less than 10 microns in diameter, including PM<sub>2.5</sub>, as represented  
PM<sub>2.5</sub> - PM equal to or less than 2.5 microns in diameter  
H<sub>2</sub>S - hydrogen sulfide  
H<sub>2</sub>SO<sub>4</sub> - sulfuric acid  
NH<sub>3</sub> - ammonia
- (4) Compliance with annual emission limits (tons per year) is based on a 12-month rolling period.
- (5) The VOC emission rate is for total VOC, including benzene.
- (6) Emissions from the fire pump diesel engines are based on 156 hours per year operation. Non-emergency fire pump operations shall only occur between the hours of 8:00 a.m. and 5:00 p.m. (one engine at any one time.)
- (7) These emissions are permitted under PSD or Nonattainment review in addition to State.
- (8) Reserved.
- (9) Mercury shall be calculated and expressed as elemental mercury in any form or phase and shall include the mercury contained in any compound.
- (10) Emissions from startups and spikes in the short-term rate are authorized at this rate for up to 150 total hours in any 12-month period during which emissions from one or more furnaces (EPNs N-1 through N-8, N-9, and N-16) exceed the routine lbs/hr emission limit. Annual emissions are included in the rates of normal operations.
- (11) Emissions from startups and spikes in the short-term rate are authorized at this rate for up to 876 total hours in any 12-month period. Annual emissions are included in the rates of normal operations.
- (12) Emission rate is an estimate and compliance is demonstrated by meeting the requirements of the applicable special conditions and permit application representations.
- (13) Annual emission rates are included in each EPN's respective routine emission rates.
- (14) Each engine is authorized to operate for up to 96 total hours in any 12-month period.
- (15) Annual emission rates of PM<sub>10</sub> and PM<sub>2.5</sub> are included in PM annual emissions. Annual emission rates of PM<sub>2.5</sub> are included in PM<sub>10</sub> annual emissions.
- (16) Annual emissions are included in the Flare Systems' annual Emission Limits.

Date: February 15, 2019