Emission Sources - Maximum Allowable Emission Rates

Permit Number 133997

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities, sources, and related activities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

Air Contaminants Data

Emission Point No.	Source Name (2)	Air Contaminant Name (3)	Emission	Rates (5)
(1)			lbs/hour	TPY (4)
FUGREC	Cottonseed Receiving	PM	2.22	0.71
	Building Fugitives (Cottonseed Receiving	PM ₁₀	0.73	0.23
	and Hopper Loading) (6)	PM _{2.5}	0.12	0.04
1		PM	0.23	0.54
	Stack (CYC-1)	PM ₁₀	0.23	0.54
		PM _{2.5}	0.23	0.54
		voc	0.01	0.02
		NO _X	0.10	0.23
		SO ₂	<0.01	<0.01
		со	0.08	0.19
5	Delinting Drum Exhaust Bagfilter and Burner Stack (FTR-2)	РМ	0.22	0.52
		PM ₁₀	0.22	0.52
		PM _{2.5}	0.22	0.52
		NH ₄ CI	0.22	0.52
		VOC	<0.01	0.01
		NO _x	0.05	0.11
		SO ₂	<0.01	<0.01
		СО	0.04	0.09
		NH ₃	0.15	0.28
DEFUG	Delinting Material Transfer Fugitives (6)	РМ	0.12	0.22
	Transier Fugitives (6)	PM ₁₀	0.07	0.12
		PM _{2.5}	0.01	0.02
		HCI	0.06	0.11
7	North and South Buffing Reels and Dry Fuzzy	РМ	0.71	1.64

Project Number: 263502

Emission Sources - Maximum Allowable Emission Rates

		PM ₁₀	0.71	1.64
		PM _{2.5}	0.71	1.64
6	Cull Bin Cyclone Stack	PM	0.42	0.96
	(CYC-9)	PM ₁₀	0.42	0.96
		PM _{2.5}	0.42	0.96
15	Cleaner Cyclone Stack	PM	0.57	1.30
		PM ₁₀	0.57	1.30
		PM _{2.5}	0.57	1.30
16	Primary Gravity Table	PM	1.46	3.36
	Cyclone Stack	PM ₁₀	1.46	3.36
		PM _{2.5}	1.46	3.36
17	Color Sorter Cyclone	PM	0.86	1.97
	Stack	PM ₁₀	0.86	1.97
		PM _{2.5}	0.86	1.97
19	Front Half – Treated Seed	PM	1.60	3.69
	Material Transfer Points and Tertiary Color Sorter	PM ₁₀	1.60	3.69
	Kimbell Cyclone Stack	PM _{2.5}	1.60	3.69
20	Back Half - Bagging and	PM	0.65	1.50
	Seed Handling Material Transfer Points Kice	PM ₁₀	0.65	1.50
	Aspirator Cyclone Stack	PM _{2.5}	0.65	1.50
TBFUG	Seed Treating and	PM	0.18	0.26
	Bagging Fugitives (6)	PM ₁₀	0.10	0.14
		PM _{2.5}	0.02	0.02
11	North Lint Bin Loadout (6)	PM	0.05	0.09
		PM ₁₀	0.02	0.03
		PM _{2.5}	<0.01	0.01
12	South Lint Bin Loadout	PM	0.05	0.09
	(6)	PM ₁₀	0.02	0.03
		PM _{2.5}	<0.01	0.01

Project Number: 263502

Emission Sources - Maximum Allowable Emission Rates

	Total Lint Bin Loadout (6)	РМ		0.09
		PM ₁₀		0.03
		PM _{2.5}		0.01
13	Cull Bin Hopper Loadout (6)	РМ	0.08	0.14
	(0)	PM ₁₀	0.03	0.05
		PM _{2.5}	0.01	0.01
14	Debagging Cyclone Stack	PM	0.34	0.79
		PM ₁₀	0.34	0.79
		PM _{2.5}	0.34	0.79
FUGDEB	Debagging Building Fugitives (6)	PM	0.54	0.05
	i agiaves (o)	PM ₁₀	0.35	0.03
		PM _{2.5}	0.05	0.03

(1) Emission point identification - either specific equipment designation or emission point number from plot plan.

(2) Specific point source name. For fugitive sources, use area name or fugitive source name.

(3) VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1

NO_x - total oxides of nitrogen

SO₂ - sulfur dioxide

PM - total particulate matter, suspended in the atmosphere, including PM₁₀ and PM_{2.5}, as represented

PM₁₀ - total particulate matter equal to or less than 10 microns in diameter, including PM_{2.5}, as

represented

PM_{2.5} - particulate matter equal to or less than 2.5 microns in diameter

CO - carbon monoxide

NH₃ - ammonia

HCI - hydrochloric acid NH₄CI - ammonium chloride

- (4) Compliance with annual emission limits (tons per year) is based on a 12 month rolling period.
- (5) Planned startup and shutdown emissions are included. Maintenance activities are not authorized by this permit.
- (6) Emission rate is an estimate and is enforceable through compliance with the applicable special condition(s) and permit application representations.

Date: February 17, 2017

Project Number: 263502