Permit Nos. 9654A, PSD-TX-684, and PSD-TX-833

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

Emission	Source	Air Contaminant	<u>Emiss</u>	ion Rates
<u>*</u> <u>Point No. (1)</u>	Name (2)	Name (3)	lb/hr	TPY
1A	No. 1 Recovery Furna	ice PM <sub>10</sub> VOC	56.00 50.00	247.00 217.00
		NO <sub>X</sub> SO <sub>2</sub>	90.00 915.70	394.00 1372.00
		CO TRS	1375.00 24.00	6023.00 41.00
1B	No. 2 Recovery Furna	ice VOC NO <sub>x</sub>	50.00 90.00	217.00 394.00
		$SO_2$ $PM_{10}$	915.70 56.00	1372.00 247.00
		CO TRS	1375.00 24.00	6023.00 41.00
2	Bark Boiler	VOC NO <sub>x</sub> SO <sub>2</sub>	20.00 104.00 5.00	88.00 456.00 22.00
		PM <sub>10</sub> CO	33.00 600.00	145.00 2628.00
2A	No. 1 PFI Boiler	$VOC$ $NO_X$ $SO_2$ $PM_{10}$ $CO$	10.00 49.83 5.00 3.00 70.00	44.00 218.26 22.00 13.00 307.00
2B	Package Boiler	VOC	0.67	2.93

Permit Nos. 9654A, PSD-TX-684, and PSD-TX-833 Page 2

Emission <u>*</u>	Source	Air Contaminant	<u>Emiss</u>	ion Rates
Point No. (1)	Name (2)	Name (3)	1b/hr	<u>TPY</u>
		$NO_X$ $SO_2$ $PM_{10}$ $CO$	28.50 0.14 1.20 8.32	124.90 0.61 5.25 36.40
3	No. 1 Dissolving Ta	nk VOC SO <sub>2</sub> PM <sub>10</sub> TRS	17.93 2.10 6.90 0.60	50.12 9.20 30.00 2.50
4	No. 2 Dissolving Ta	nk VOC SO <sub>2</sub> PM <sub>10</sub> TRS	17.93 2.10 6.90 0.60	50.12 9.20 30.00 2.50
9	Lime Silo	$PM_{10}$	3.40	2.00
10	No. 1 Slaker	PM <sub>10</sub> VOC	2.00 0.48	8.60 1.33
11	Lime Kiln	$\begin{array}{c} VOC \\ NO_X \\ SO_2 \\ PM_{10} \\ CO \\ TRS \end{array}$	4.70 42.00 57.80 30.00 337.00 6.40	21.00 182.00 84.30 131.00 1474.00 11.20
12	Tall Oil Reactor	VOC TRS	7.37 0.80	20.61 0.12
13	No. 2 Slaker	PM <sub>10</sub> VOC	2.00 0.48	8.60 1.33
16	Brown Stock Washer	A VOC TRS	16.29 4.00	4.00 17.50

Permit Nos. 9654A, PSD-TX-684, and PSD-TX-833 Page 3

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES AIR CONTAMINANTS DATA

Emission *	Source	Air Contaminant	<u>Emissic</u>	on Rates
Point No. (1)	Name (2)	Name (3)	lb/hr	TPY
17	Brown Stock Washer E	3 VOC TRS	12.29 4.00	34.37 17.50
19	Lime Silo	$PM_{10}$	0.01	0.01
32	Turpentine Storage 1	ank VOC	<0.01	0.02
36	No. 5 White Liquor Tank Vent	TRS	<0.01	0.02
37	No. 6 Fuel Oil Tank	VOC	<0.01	0.02
38	No. 6 Fuel Oil Tank	VOC	<0.01	0.02
39	South Mud Tank	VOC	0.02	0.06
40	North Mud Tank	VOC	0.02	0.06
41	Weak Wash Storage Ta	ink VOC	0.09	0.24
42	Hot Water Storage Ta	ink VOC	0.00	0.00
43	New White Liquor Sto 1.59	orage Tank	VOC	0.57
44	Scrubber Water Clari	fier VOC	0.09	0.24
45	No. 1 White Liquor S 1.59	Storage Tank	VOC	0.57
46	No. 2 White Liquor S 1.59	Storage Tank	VOC	0.57
47	No. 1 Greel Liquor (	Clarifier	VOC	0.02

Permit Nos. 9654A, PSD-TX-684, and PSD-TX-833 Page 4

Emission *	Source Ai	r Contaminant	<u>Emission</u>	Rates
Point No. (1)	Name (2)	Name (3)	lb/hr	TPY
	0.05			
48	No. 1 Green Liquor Stor 0.05	age Tank	VOC	0.02
49	No. 2 Green Liquor Stor 0.05	rage Tank	VOC	0.02
50	Green Liquor Equalizat	ion Tank	VOC	0.03
51	No. 2 Green Liquor Clar 0.05	rifier	VOC	0.02
63	No. 1 Weak Black Liquo Storage Tank	VOC TRS	0.38 1.30	1.34 5.60
64	No. 2 Weak Black Liquo Storage Tank	· VOC TRS	0.38 1.30	1.34 5.60
65	Weak Black Liquor Swing Tank	VOC TRS	0.11 1.30	0.40 5.60
66	No. 1 Heavy Black Liquor Storage Tank	VOC TRS	0.23 <0.01	0.79 0.02
67	No. 2 Heavy Black Liquor Storage Tank	VOC TRS	0.23 <0.01	0.79 0.02
68	Boilout Tank	VOC TRS	0.23 0.50	0.79 2.20
72	Gasoline Tank	VOC	-	0.20

Permit Nos. 9654A, PSD-TX-684, and PSD-TX-833 Page 5

Emission	Source	Air Contaminant	<u>Emissic</u>	on Rates
<u>*</u> Point No. (1)	Name (2)	Name (3)	lb/hr	TPY
73	No. 2 Fuel Oil Tank	VOC	-	0.20
74	Black Liquor Pond	TRS	-	3.20
80	Wood Yard (4)	$PM_{10}$	-	3.80
81	Truck Traffic Fugiti 130.00	ves (4)	$PM_{10}$	-
99	No. 2 PFI Boiler	$\begin{array}{c} PM_{10} \\ VOC \\ NO_X \\ SO_2 \\ CO \end{array}$	1.05 0.59 21.0 0.25 37.8	4.60 2.58 91.98 1.09 165.56
100	Chemi-Washer (4)	VOC TRS	0.09 <0.01	0.40 <0.01

Permit Nos. 9654A, PSD-TX-684, and PSD-TX-833 Page 6

# EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES AIR CONTAMINANTS DATA

Emission	Source	Air	Contaminant	<u>Emissi</u>	on Rates
<u>*</u> Point No. (1)	Name (2)		Name (3)	lb/hr	TPY
101-130	No. 1 Paper Machine		VOC	26.70	117.00
132-158	No. 2 Paper Machine		VOC	32.30	141.60
159-166	Secondary Fiber Syst	tem	VOC	0.34	1.18
168	Black Liquor Pond We	est	VOC TRS	1.10 -	4.80 3.20
192	Lime Kiln Precoat Fi	ilter	VOC	<0.01	0.17
193, 194	Precoat Filter Vacuu 0.01	um Pu	тр	VOC	<0.01
200	Fish Ladder		VOC	9.20	32.22
205	No. 4 White Liquor S 1.59	Stora	ge Tank	VOC	0.57
206	No. 1 Recovery Boile Salt Cake Mix Tank		PM <sub>10</sub>	0.03	0.06
207	No. 2 Recovery Boile Salt Cake Mix Tank		PM <sub>10</sub>	0.03	0.06
210	Black Liquor Storage 1.34	e Eas	t	VOC	0.38
211	Black Liquor Storage 1.34	e Wes	t	VOC	0.38
212	Black Liquor Storage 1.34	e Cen	ter	VOC	0.38
213	Ecofilter Pressure S	Syste	mVOC		

Permit Nos. 9654A, PSD-TX-684, and PSD-TX-833 Page 7  $\,$ 

### EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

### AIR CONTAMINANTS DATA

Emission *	Source	Air Contaminant	<u>Emission Rates</u>
Point No. (1)	Name (2)	Name (3)	<u>lb/hr TPY</u>

0.17 6.48

Permit Nos. 9654A, PSD-TX-684, and PSD-TX-833 Page 8

#### EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

- (1) Emission point identification either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources use area name or fugitive source name.
- (3)  $PM_{10}$  particulate matter (PM) equal to or less than 10 microns in diameter. Where PM is not listed, it shall be assumed that no (PM) greater than 10 microns is emitted

VOC - volatile organic compounds as defined in General Rule 101.1

 $NO_x$  - total oxides of nitrogen

SO<sub>2</sub> - sulfur dioxide

CO - carbon monoxide

TRS - total reduced sulfur

(4) Fugitive emissions are an estimate only.

All annual emissions are based on a rolling 12-month period and a maximum annual averaged throughput of 1.700 tons per day of air dry pulp.

\* Emission rates are based on and the facilities are limited by the following maximum operating schedule:

24	_Hrs/day	7	_Days/week	52	_Weeks/year
----	----------	---	------------	----	-------------

L	)a	te	d