EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Permit No. 7186

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

		AIR CONTAMINANTS DATA		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates * lb/hr	TPY
10FLR-001	No. 1 Converter Start-up Flare**	VOC	83.5	3.47
	(includes start-up and shutdown	NO_x	17.6	1.33
	emissions)	CO	210.4	12.66
		NH_3	89.2	4.56
10FLR-002	No. 2 Converter Start-up Flare**	VOC	83.4	3.44
	(includes start-up and shutdown	NO_x	17.6	1.17
	emissions)	CO	210.4	10.90
		NH_3	89.2	4.46
10FLR-003	No. 3 Converter Start-up Flare**	VOC	83.4	3.44
	(includes start-up and shutdown	NO_x	17.6	1.17
	emissions)	CO	210.4	10.90
		NH_3	89.2	4.46
10FLR-004	Ammonia Start-up Flare (5)			NO_x
5.25	0.50			
	(includes start-up and shutdown	CO		45.0
4.28				
	emissions)	NH_3	78.0	5.33
10FLR-004A	Ammonia Tank Flare	NO_x	0.72	0.02
		CO	3.66	0.10
		NH_3	13.2	0.37

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates * lb/hr	TPY
10FLR-004B	Butadiene Flare	VOC	1.87	0.05
		NO_x	1.01	0.27
		CO	8.68	2.27
10FLR-005	Adiponitrile Flare (6)	VOC	80.58	207.35
		NO_x	30.49	107.67
		CO	265.05	931.66
		NH_3	4.38	9.10
10TFX-010	Fresh Ligand Tank	VOC	<0.01	<0.01
10TFX-025	WFE Feed Tank	VOC	<0.01	<0.01
10TFX-025A	WFE Feed Tank	VOC	<0.01	<0.01
10TFX-025B	WFE Tails Tank	VOC	<0.01	<0.01
10TFX-027	Refined Adiponitrile Tank	VOC	<0.01	<0.01
10TFX-028	Refined Adiponitrile Tank	VOC	<0.01	<0.01
10TFX-029	Refined Adiponitrile Tank	VOC	<0.01	<0.01
10TFX-030	Refined Adiponitrile Tank	VOC	<0.01	<0.01
10TFX-031	Refined Adiponitrile Tank	VOC	<0.01	<0.01
10TFX-032	Refined Adiponitrile Tank	VOC	<0.01	<0.01

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates * lb/hr	TPY
10TFX-032B	Refined Adiponitrile Tank	VOC	<0.01	<0.01
10TFX-033, 10TFX-034A, 10TFX-034B	Multi-Purpose Raffinate Tanks	VOC	16.43	1.61
10TFX-035	REF PN Multi-Purpose 1	VOC	7.60	4.42
10TFX-035B	2PN Multi-Purpose 1A	VOC	3.91	3.58
10TFX-035C	2PN Multi-Purpose 1C	VOC	3.91	1.61
10TFX-035D	Multi-Purpose 2PN 1B Tank	VOC	1.89	2.70
10TFX-036	Refined MGN Tank	VOC	0.02	0.02
10TFX-036A	Promoter PN Tank	VOC	8.54	1.93
10TFX-037	Crude DN or Crude MGN Tank	VOC	0.69	0.10
10TFX-037A	Crude MGN Tank	VOC	0.20	0.44
10TFX-038	Ethylene Glycol Tank	VOC	0.05	<0.01
10TFX-039	Crude Cresol Tank	VOC	0.03	0.05
10CLT-040	Cooling Tower (4)	VOC	3.0	13.1
		NH_3	3.0	13.0
10LRC-041A	ADN Railcar Loading	VOC	0.01	<0.01

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates * lb/hr	TPY
10LRC-041B	ADN Load/Unload	VOC	0.01	<0.01
10LRC-041C	ADN Railcar Loading	VOC	0.01	<0.01
10LRC-041E	MGN Railcar Loading	VOC	0.01	<0.01
10LRC-041F	2PN Railcar Degassing	VOC	6.9	0.06
10TFX-054	W. HCl Tank	HCl	0.27	0.02
10TFX-054A	E. HCl Tank	HCl	0.27	0.02
10TFX-055	DN Tails Tank	VOC	<0.1	<0.1
10LTR-056	DN Tails Loading	VOC	<0.01	<0.01
10TFX-059	Fertilizer Solution Tank		NH_3	3.23
0.01				
10LTR-061	Truck Loading	NH_3	0.03	0.01
10LRC-061A	NH_3 Rail Spot	NH_3	<0.1	0.3
10LBA-061B	ADN Barge Loading	VOC	0.01	0.01
10LBA-061D	NH_3 Barge Unloading	VOC	0.68	0.04
10LTR-062	Misc. Load/Unload	VOC	0.05	<0.01
10FLT-063	Nickel Addition Bag Filter			PM_{10}
<0.1	<0.1			
10FLT-063A	Nickel Powder Vacuum System			PM_{10}
<0.1	<0.1			
10HTR-064	Pyrolyzer Heater	VOC	0.02	0.09

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates * lb/hr	TPY
		NO_x	0.48	2.28
		CO	0.29	0.52
		SO_2	<0.01	0.02
		PM_{10}	0.05	0.20
10FLT-064A	Recovered Nickel Bag Filter			VOC
0.13	0.58			
		PM_{10}	0.02	0.09
10HTR-065	NAW Column Reboiler	VOC	0.87	2.16
	(85 MMBTU/HR, avg)	NO_x (7)	9.00	22.34
	(150 MMBTU/HR, max)	NO_x (8)	41.25	102.38
		CO	5.25	13.03
		SO_2	0.09	0.22
		PM_{10}	1.14	2.83
10HTR-066	NRU Hot Oil Heater	VOC	0.03	0.11
		NO_x	0.52	1.91
		CO	0.44	1.60
		SO_2	<0.01	0.01
		PM_{10}	0.04	0.15
10TFX-067	Produced Water Tank	VOC	<0.01	<0.01
		NH_3	<0.01	<0.01
10LTR-071	HCl Truck Unloading	HCl	0.14	0.04
10TFX-080	Adiponitrile Storage	VOC	0.07	0.01
10FUG	Fugitives (4)	VOC (9)	11.82	51.74
		NH_3	1.51	6.61
		HCN	2.10	9.20
11TFX-036	HCN/HMD AWST	VOC	0.04	0.01

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates * lb/hr	TPY
11TFX-047	HCN/HMD HUT	VOC	0.01	0.01
11TFX-048	Nitrile HUT	VOC	0.01	0.01
11TFX-049	East Vacuum Truck Receiver	VOC	0.01	0.01
11TFX-053	RPF Filtrate Tank	VOC	<0.01	<0.01
11TFX-055	311 Area Wastewater Tank	VOC	0.01	0.02
11SEP-055A	API Decanter	VOC	<0.01	0.01
11ODP-055B	Organics Dumpster	VOC	0.18	0.01
11TFX-064	Neut. Filter Feed Tank	VOC	0.01	0.01
11TFX-070	Neut. Effluent Tank	VOC	0.01	0.01
11TFX-076	Waste Collection Tank	VOC	0.04	<0.01
		NH_3	0.02	<0.01
11TFX-077	Waste Lift Tank	VOC	<0.01	<0.01
		NH_3	<0.01	<0.01
11TFX-153	Nitrile Precoat Tank	VOC	<0.01	<0.01
		NH_3	<0.01	<0.01
11TOX-078A	Thermal Oxidizer	VOC	0.26	0.32
		NO_x	4.89	5.17
		CO	0.40	0.58
		SO_2	1.20	1.75
		PM_{10}	0.10	0.15
		NH_3	0.01	0.01

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates * lb/hr	TPY

(1) Emission point identification - either specific equipment designation or emission point number from plot plan.
(2) Specific point source name. For fugitive sources use area name or fugitive source name.
(3) VOC - volatile organic compounds as defined in General Rule 101.1
NO_x - total oxides of nitrogen
CO - carbon monoxide
SO_2 - sulfur dioxide
PM_{10} - particulate matter equal to or less than 10 microns in diameter
NH_3 - ammonia
HCN - hydrogen cyanide
HCl - hydrogen chloride
(4) Fugitive emissions are an estimate only and should not be considered as a maximum allowable emission rate.
(5) This flare is also used to control upset emissions. When operating in this mode, maximum emission rates are 9.33 lbs/hr for NO_x, 80.0 lbs/hr for CO, and 138.8 lbs/hr for NH_3. Upset emissions contribute 0.06 TPY of NO_x, 0.48 TPY of CO, and 0.83 TPY of NH_3.
(6) This flare is also used to control non-continuous vents. When operating in this mode, maximum emission rates are 619.2 lbs/hr for VOC, 803.0 lbs/hr for NO_x, and 726.8 lbs/hr for CO. Non-continuous emissions contribute 18.77 TPY of VOC, 45.79 TPY of NO_x, and 221.85 TPY of CO. Both continuous and non-continuous emissions are those attributable to these facilities.
(7) Facility is using straight natural gas fuel.
(8) Facility is using process off-gas as fuel.
(9) VOC emission rates for this EPN do not include HCN.

* Emission rates are based on and the facilities are limited by the following maximum operating schedule:

Hrs/year 8,760

** Only one converter can be in start-up mode at a time.

Dated_____