

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Permit No. 29562B

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

AIR CONTAMINANTS DATA

Emission * Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lb/hr	TPY
1	Drum/Dryer Baghouse Stack 19.18	VOC (a)		41.3
		VOC (b)	525.00	65.63
		VOC (c)	56.50	5.65
		NO _x	12.60	6.75
		CO	13.30	7.13
		SO ₂	8.95	10.65
		PM ₁₀	12.55	6.72
2	Material Handling (4)	PM	5.72	3.11
		PM ₁₀	1.45	0.80
3	Stockpiles (4)	PM	*	1.83
		PM ₁₀	*	0.88
		VOC (b)	1.05	6.56
4	Caterpillar D389 Generator (4) 50.45	NO _x		19.8
		CO	4.36	11.12
		SO ₂	2.00	5.10
		PM ₁₀	0.4	1.03
		VOC	0.6	1.53

(1) Emission point identification - either specific equipment designation or emission point number from plot plan.

(2) Specific point source name. For fugitive sources use area name or fugitive source name.

(3) VOC - volatile organic compounds as defined in TNRCC General Rule 101.1

VOC(a) - from standard mix asphalt concrete

VOC(b) - from cold mix asphalt concrete

VOC(c) - total VOCs from recycled rubber modified asphalt concrete mixes

NO_x - nitrogen oxide

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

CO - carbon monoxide
SO₂ - sulfur dioxide
PM - particulate matter, suspended in the atmosphere, including PM₁₀.
PM₁₀ - particulate matter equal to or less than 10 microns in diameter.
Where PM is not listed, it shall be assumed that no particulate matter greater than 10 microns is emitted.

(4) Fugitive emissions are an estimate only.

* Emission rates are based on and the facility is limited to the following asphalt concrete production rates and operating schedule:

	<u>tons/hour</u>	<u>tons/week</u>	<u>tons/year</u>
Standard hot-mix	350		300,000
Recycled rubber modified mixes	250		**50,000
Cold mix asphalt with emulsion	300	10,000	***
Cold mix asphalt with slow cure	262	8,750	***
Cold mix asphalt with rapid cure	210	5,000	***
Cold mix asphalt with medium cure	150	5,000	***

** Included in the standard hot-mix annual limit.

*** Total cold mix production as governed by Special Condition No. 7

14 hours/day 7 days/week 52 weeks/year 3,920
hours/year

Dated_____