

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Permit Number 19618

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY **
901	Initiator Drum	VOC	0.72	0.90
902	Inhibitor Drum	VOC	1.09	0.34
903	Stopper Drum	VOC	1.34	0.08
904	Phosphoric Acid Drum	VOC	0.37	0.14
945	Baghouse (Dry Grinding)	VOC	3.51	0.16
		Methyl Acetate	0.01	0.01
		PM	0.01	0.04
946	Baghouse (Dry Grinding)	VOC	3.51	0.16
		Methyl Acetate	0.01	0.01
		PM	0.01	0.04
947	Baghouse (Dry Grinding)	VOC	0.04	0.05
		Methyl Acetate	0.01	0.01
		PM	0.03	0.17
948	Baghouse (Dry Grinding)	VOC	0.04	0.05
		Methyl Acetate	0.01	0.01
		PM	0.03	0.17
951	Baghouse (Product Silo)	VOC	0.18	0.19
		Methyl Acetate	0.01	0.01
		PM	0.08	0.22
955	Baghouse (House Vacuum Systems)	VOC	0.01	0.01
		Methyl Acetate	0.01	0.01
		PM	0.06	0.21

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY **
956	Baghouse (Product Silo)	VOC	0.26	0.19
		Methyl Acetate	0.01	0.01
		PM	0.19	0.22
957	Baghouse (Product Silo)	VOC	0.26	0.19
		Methyl Acetate	0.01	0.01
		PM	0.19	0.22
982	Storage Tank (Methanol)	VOC	0.25	0.45
		Methyl Acetate	0.01	0.01
983	Storage Tank (Methanol)	VOC	0.29	1.18
		Methyl Acetate	0.01	0.01
984	Storage Tank (Seal Flush)	VOC	0.25	0.76
		Methyl Acetate	0.36	1.22
985	Storage Tank (Mother Liquor)	VOC	0.42	1.57
		Methyl Acetate	1.38	5.73
986	Storage Tank (Mother Liquor)	VOC	0.42	1.57
		Methyl Acetate	1.38	5.73
988	Storage Tank (Caustic)	NaOH	0.01	0.01
989	Storage Tank	VOC	0.25	0.67
		Methyl Acetate	0.01	0.01
1011	Tank (Wastewater)	VOC	0.66	0.86
		Methyl Acetate	1.89	0.76
987	Vent Scrubber	VOC	0.01	0.01
900-FUG	Fugitives(4)	VOC	8.16	35.75
		Methyl Acetate	1.90	8.34
1012	Flare	VOC	14.47	5.42

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY **
		Methyl Acetate	24.68	9.26
		NO _x 1.04	0.39	
		CO	8.93	3.35
		SO ₂	0.01	0.01
900-BOWW	Saponification Boilout Wastewater	VOC	24.10	0.62
		Methyl Acetate	5.40	0.07
900-1070	Tank 10.70	VOC	0.06	0.20
		Methyl Acetate	0.66	2.03
1001	Fugitives (4)	Refrigerant R-404A	1.07	4.70
900-72.01	Cooling Tower	VOC	1.13	5.00
1002	Fugitives (4)	Refrigerant R-22	0.76	3.32
900-PDUMAIN	PDU Maintenance	VOC	0.36	0.09
900-LABHOOD	Lab Hood Vent	VOC	0.01	0.01

(1) Emission point identification - either specific equipment designation or emission point number from plot plan.

(2) Specific point source name. For fugitive sources use area name or fugitive source name.

(3) PM - particulate matter, suspended in the atmosphere, including PM₁₀

PM₁₀ - particulate matter equal to or less than 10 microns in diameter. Where PM is not listed, it shall be assumed that no particulate matter greater than 10 microns is emitted.

VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1

NO_x - total oxides of nitrogen

SO₂ - sulfur dioxide

CO - carbon monoxide

NaOH - sodium hydroxide

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

(4) Fugitive emissions are an estimate only and should not be considered as a maximum allowable emission rate.

(5) 900-BOVNT1 and 900-BOVNT2 shall not have emissions at the same time.

* Emission rates are based on and the facilities are limited by the following maximum operating schedule:

Hrs/day _____ Days/week _____ Weeks/year _____ or Hrs/year 8,760

** Compliance with annual emission limits is based on a rolling 12-month period.

Dated February 22, 2006