## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

### Permit Number 21144

This table lists the maximum allowable emission rates for all sources of air contaminants covered by this permit.

## AIR CONTAMINANTS DATA

Emission	Source	Ai	ir Contaminant	Emission	n Rates	
Point No. (1)	Name (FIN)		Name (2)	lb/hr	TPY (3)	
	UV Finish Line 1					
21A, 21B, 22A, 22B, 23, 24, 25, 26, and 27	Stain Roll Coater (26), Sealer Roll Coaters 1-3 (21A, 21B, 22 Finish Roll Coater (25), and Curing Ovens 1-4 (22A, 22B,	,	VOC 7)	20.88		
20A and 20B	Stain Drying Ovens (20A, 20B)		$NO_x$	0.12	0.53	
	,		CO	0.10	0.44	
		SO <sub>2</sub>	<0.01	< 0.01		
		VOC PM	(4) 0.01	0.01 0.04	0.03	
		LIAI	0.01	0.04		
	UV Finish Line 2					
41, 42, 43, 45, 46, 47, 50, 53, 54, 56, 58, 59, and 61	Stain Roll Coaters (41, 43A, 43 Drying Ovens (42, 45), Sealer Roll Coaters (47, 49, 51, 53, 5 57, 59, 60), UV Lamps 44, 46	55,	VOC VOC (4) PM NO <sub>x</sub> CO	27.49 0.01 0.01 0.16 0.13	0.04 0.05 0.70 0.59	
	50, 52, 54, 56, 58, 61), and Wet Brushes (43C)		SO <sub>2</sub>	< 0.13	0.59 <0.01	
	Wax/Plank Line					
2B	Stain Roll Coater (2B)		VOC	37.20		
4B	Finish Drying Oven (4B)	SO <sub>2</sub>	NO <sub>x</sub> CO <0.01	0.45 0.38 0.01 0.02	1.97 1.66 0.11	
		PM	0.03	0.02	0.11	

# EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

# AIR CONTAMINANTS DATA

Emission	Source	Air Contaminant	Emissio	n Rates			
Point No. (1)	Name (FIN)	Name (2)	lb/hr	TPY (3)			
		Gluing					
PG-05A and PG-05B	Glue Preparation Area (PG-05A) Plywood Glue-Up Press (PG-05		4.29 0.08	0.22			
	Site-Wide Clean-Up						
2B, 4B, 21A, 21B, 23, 25, 26, 41, 43, 47, 53, 59, and F-1		VOC (5)	27.02				
UV Finish Lines, Wax/Plank Line, Gluing, and Site-Wide Clean-Up							
21A, 21B, 22A, 22B, 23-27, 41-61, 2B,4B, PG-05A, PG-05B, and F-1	UV Finish Lines 1 and 2, Wax/Plank Line, Glue Preparati Area, Glue-up Press, and Site-V Clean-Up			80.00			
	Woodworking						
BH-A, BH-B, BH-C, BH-D, and BH-E	UV, Wax/Plank, Oil Specialty, and New Village Plank Sawing, Sanding, and Brushing (SYS 1-	PM 7)	3.61	15.82			
	Veneer Drying						
35, 36, 37, 38, 39, and 40	Veneer Dryers 1 and 2 (VD-20)	VOC PM	1.09 1.32	1.73 2.10			
	Storage Tanks						
F-10	Resin Storage Tanks 1 and 2 (GT-22A and GT-22B)	VOC (6)	<0.01	<0.01			

#### EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

#### AIR CONTAMINANTS DATA

Emission	Source	Air Contaminant	Emission Rates	
Point No. (1)	Name (FIN)	Name (2)	lb/hr	TPY (3)
	В	Boiler Building		
F-9	Wood Dust Fuel Handling/Storag (BFB-21)	e PM (6)	0.32	1.42
		Other		
S-4	Truck Loading Stations and Chipper Hog vented through a Dust Collector (TL-14)	РМ	0.09	0.38

- (1) Emission point number from a plot plan
- (2) VOC volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
  - PM particulate matter, suspended in the atmosphere, including PM<sub>10</sub>
  - PM<sub>10</sub> particulate matter equal to or less than 10 microns in diameter. Where PM is not listed, it shall be assumed that no particulate matter greater than 10 microns is emitted.
  - NO<sub>x</sub> total oxides of nitrogen
  - CO carbon monoxide
  - SO<sub>2</sub> sulfur dioxide
- (3) Rate is for a rolling 12-consecutive months
- (4) Emissions from combustion only
- (5) Emissions from Source IMP-13, EPN F-1 are fugitive
- (6) Fugitive emissions

Date <u>January 19, 2005</u>