EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Permit No. 27359

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

| | | | | AIR COI | NTAMINANTS | DATA |
|---------------|-------------|------------------|-------|-------------|---------------|------------|
| Emission | Source | | Air C | Contaminant | <u>Emissi</u> | on Rates * |
| Point No. (1) | Name (2) | Name (3) | lb/hr | TPY | | |
| | | | | | | |
| | Baghouse | Stack | | TSP | 11.40 | 7.30 |
| | | | | PM_{10} | 11.40 | 7.30 |
| | | | | VOC(a) | 15.05 | 9.63 |
| | | | | VOC(b) | 59.85 | 38.30 |
| | | | | VOC(c) | 700.00 | 70.00 |
| | | | | NO_x | 12.60 | 8.06 |
| | | | | SO_2 | 17.13 | 10.96 |
| | | | | CO | 13.30 | 8.51 |
| | | | | | | |
| | Lime Silo E | Baghouse | | TSP | < 0.01 | < 0.01 |
| | | | | PM_{10} | < 0.01 | < 0.01 |
| | | | | | | |
| | Stockpile F | ugitives (4) | | TSP | - | 0.29 |
| | | | | PM_{10} | - | 0.14 |
| | | | | | | |
| | Raw Aggre | gate Process (4) | TSP | 24.34 | 15.56 | |
| | PM_{10} | | | 0.72 | 0.43 | |

- (1) Emission point identification either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources use area name or fugitive source name.

(3) TSP - total suspended particulate matter (including PM₁₀)

PM₁₀ - particulate matter less than 10 microns

VOC - volatile organic compounds as defined in General Rule 101.1

VOC(a) - mainly asphalt vapors

VOC(b) - additional VOC due to the use of crumb rubber

VOC(c) - primarily diesel or kerosene vapors

NO_x - total oxides of nitrogen

SO₂ - sulfur dioxide CO - carbon monoxide

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

(4) Fugitive emissions are an estimate only and should not be considered as a maximum allowable emission rate.

| MAER | T |
|-------|---|
| 8430H | |
| PAGE | 3 |

| * | Emission rates ar | re based on | and the | facilities | are li | imited | by the | following | maximum | operat | inç |
|---|-------------------|---------------|---------|------------|--------|--------|--------|-----------|---------|--------|-----|
| | schedule and j | production ra | ates: | | | | | | | | |

8 Hrs/day 5 Days/week 32 Weeks/year or 1280 Hrs/year

Standard Hot Mix w/crumb rubber option: Tons/hour 350 Tons/year 488,000 Cutback Cold Mix: Tons/hour 200 Tons/week 8,000 Tons/year 40,000

Emulsified Cold Mix: Tons/hour 200 To ns/week 8,000 Tons/year 40,000

| Dated |
|-------|
|-------|