

# EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Permit Number 56595

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

## AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
DEB	Debarker	PM	0.09	0.17
		PM <sub>10</sub>	0.04	0.08
CHP	Chipper	PM	0.03	0.06
		PM <sub>10</sub>	0.01	0.03
SAW	Saw Mill	PM	0.54	1.01
		PM <sub>10</sub>	0.01	0.02
FUGSCREEN	Chip Screening (4)	PM	0.20	0.03
		PM <sub>10</sub>	0.20	0.03
FUGLOADING	Chip Loading (4)	PM	<0.01	<0.01
		PM <sub>10</sub>	<0.01	<0.01
KLN-1A	Drying Kiln 1A (4)(5)	PM	0.80	1.90
		PM <sub>10</sub>	0.80	1.90
		VOC	10.70	14.25
KLN-1B	Drying Kiln 1B (4)(5)	PM	0.80	1.90
		PM <sub>10</sub>	0.80	1.90
		VOC	10.70	14.25
KLN-2A	Drying Kiln 2A (4)(5)	PM	0.80	1.90
		PM <sub>10</sub>	0.80	1.90
		VOC	10.70	14.25
KLN-2B	Drying Kiln 2B (4)(5)	PM	0.80	1.90
		PM <sub>10</sub>	0.80	1.90
		VOC	10.70	14.25

# EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

CYC-2	Planer Mill 1	PM	0.19	0.36
		PM <sub>10</sub>	0.08	0.15
CYC-3	Planer Mill 2	PM	0.19	0.36
		PM <sub>10</sub>	0.08	0.15
CYC-4	Hog Mill	PM	0.14	0.26
		PM <sub>10</sub>	0.06	0.12
CYC-5	Pattern Machine	PM	0.38	0.72
		PM <sub>10</sub>	0.15	0.30
FUGHOPPER	Shavings Bin	PM	0.04	0.07
		PM <sub>10</sub>	0.01	0.01

- (1) Emission point identification - either specific equipment designation or emission point number from a plot plan.
- (2) Specific point source names. For fugitive sources, use an area name or fugitive source name.
- (3) VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
  - PM - particulate matter, suspended in the atmosphere, including PM<sub>10</sub>
  - PM<sub>10</sub> - particulate matter equal to or less than 10 microns in diameter
- (4) Fugitive emissions are an estimate only.
- (5) Operating schedule for the drying kilns is 24 hour/day, 7 day/week, and 50 week/year.

\* Emission rates are based on and the facilities are limited by the following maximum operating schedule:

16 Hrs/day 7 Days/week 52 Weeks/year for normal operation, except drying kilns.

\*\* Compliance with annual emission limits is based on a rolling 12-month period.

Maximum annual production is based on 60,000,000 board feet of lumber produced.

Emission calculations are based on the following:

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Debarker: 77 tons per hour (TPH) and 288,750 tons per year (TPY) of log processed with 95% (percent) partial enclosure efficiency.

Sawmill: 77 TPH and 288,750 TPY of log processed with 98% partial enclosure efficiency and NC DENR Draft Document dated 7.15.98.

Chipper: 25 TPH and 93,750 TPY of log processed with 95% partial enclosure efficiency.

Planer Mill: 33.8 TPH and 126,750 TPY of log processed for the two mills with 99.5% cyclone efficiency.

Hog Mill: 5.8 TPH and 21,750 TPY of log processed with 99.5% cyclone efficiency.

Pattern Machine: 33.8 TPH and 126,750 TPY of log processed with 99.5% cyclone efficiency.

Shavings Loadout: 5.8 TPH and 21,750 TPY of log processed with 60% two-sided enclosure efficiency and NCDAQ Draft Document dated 7.15.98.

2008

Dated July 15,