

Emission Sources - Maximum Allowable Emission Rates

Permit Number 20851

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities, sources, and related activities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

Air Contaminants Data

| Emission Point No. (1) | Source Name (2) | Air Contaminant Name (3) | Emission Rates (6) | |
|------------------------|---|--------------------------|--------------------|---------|
| | | | lbs/hour | TPY (4) |
| EP2-1F | Outdoor Rock Pile-Stock (4) | PM | 1.03 | 4.50 |
| | | PM ₁₀ | 0.46 | 2.03 |
| EP2-2F | Outdoor Rock Pile-Molding (4) | PM | 0.61 | 2.65 |
| | | PM ₁₀ | 0.28 | 1.24 |
| EP2-3F | Outdoor Rock Pile-Stock (4) | PM | 0.01 | 0.04 |
| | | PM ₁₀ | <0.01 | 0.01 |
| EP2-4F | Outdoor Recycle Pile-Dump (4) | PM | 0.84 | 3.70 |
| | | PM ₁₀ | 0.38 | 1.65 |
| EP2-5F | Outdoor Rock Pile – Oversized Rock (4) | PM | 0.13 | 0.56 |
| | | PM ₁₀ | 0.05 | 0.24 |
| EP2-6F | Outdoor Rock Pile - Processed Rock (4) | PM | 0.16 | 0.71 |
| | | PM ₁₀ | 0.07 | 0.30 |
| EP-3 | Gypsum Unloading to Crusher with Jackhammer | PM | 0.07 | 0.29 |
| | | PM ₁₀ | 0.03 | 0.14 |
| EP-5 | Primary and Secondary Crusher Conveyor | PM | 0.79 | 3.45 |
| | | PM ₁₀ | 0.34 | 1.51 |
| EP-6 | Crusher to Screening Conveyors | PM | 2.75 | 12.06 |
| | | PM ₁₀ | 1.01 | 4.42 |
| EP-7 | Gypsum Screening | PM | 0.75 | 3.29 |
| | | PM ₁₀ | 0.45 | 1.97 |
| EP-8 | Screening Feed Pile Return | PM | 0.17 | 0.76 |
| | | PM ₁₀ | 0.06 | 0.25 |
| EP-9 | Screening and Rock Bin Building Conveyors | PM | 1.98 | 8.67 |
| | | PM ₁₀ | 0.73 | 3.18 |

Emission Sources - Maximum Allowable Emission Rates

| | | | | |
|-------|---|------------------|-------|------|
| EP-11 | Roller Mill Baghouse No. 1 Stack | PM | 1.03 | 4.51 |
| | | PM ₁₀ | 1.03 | 4.51 |
| | | VOC | 0.03 | 0.14 |
| | | NO _x | 0.59 | 2.58 |
| | | SO ₂ | <0.01 | 0.02 |
| | | CO | 0.49 | 2.16 |
| | | Hexane (5) | 0.01 | 0.05 |
| EP-13 | Conveyor Belt and Mill Rock Hopper | PM | 1.80 | 7.88 |
| | | PM ₁₀ | 0.66 | 2.89 |
| EP-14 | Rock Bin Building, Silo and Mill Building Conveyors | PM | 1.80 | 7.88 |
| | | PM ₁₀ | 0.66 | 2.89 |
| EP-16 | Discharge Conveyor to Oversize Stock Pile (Screening) | PM | 0.24 | 1.06 |
| | | PM ₁₀ | 0.12 | 0.50 |
| EP-17 | Discharge Chute from Mill to Ground | PM | 1.22 | 5.32 |
| | | PM ₁₀ | 0.58 | 2.52 |
| EP-19 | Discharge Landplaster Chute to Railcar | PM | 0.06 | 0.24 |
| | | PM ₁₀ | 0.03 | 0.11 |
| EP-20 | Discharge Landplaster Chute to Truck | PM | 0.06 | 0.24 |
| | | PM ₁₀ | 0.03 | 0.11 |
| EP-21 | Mill Kettle Bins and Screw Baghouse No. 6 Stack | PM | 1.71 | 7.51 |
| | | PM ₁₀ | 1.71 | 7.51 |
| EP-22 | Roller Mill Baghouse No. 2 Stack | PM | 0.94 | 4.13 |
| | | PM ₁₀ | 0.94 | 4.13 |
| | | VOC | 0.04 | 0.18 |
| | | NO _x | 0.74 | 3.22 |
| | | SO ₂ | <0.01 | 0.02 |
| | | CO | 0.62 | 2.71 |
| | | Hexane (5) | 0.01 | 0.06 |
| EP-23 | Roller Mill Baghouse No. 3 Stack | PM | 1.03 | 4.51 |
| | | PM ₁₀ | 1.03 | 4.51 |

Emission Sources - Maximum Allowable Emission Rates

| | | | | |
|-------|-------------------------------------|------------------|-------|-------|
| | | VOC | 0.03 | 0.14 |
| | | NO _x | 0.59 | 2.58 |
| | | SO ₂ | <0.01 | 0.02 |
| | | CO | 0.49 | 2.16 |
| | | Hexane (5) | 0.01 | 0.05 |
| EP-24 | Roller Mill Baghouse No. 4 Stack | PM | 0.94 | 4.13 |
| | | PM ₁₀ | 0.94 | 4.13 |
| | | VOC | 0.03 | 0.14 |
| | | NO _x | 0.59 | 2.58 |
| | | SO ₂ | <0.01 | 0.02 |
| | | CO | 0.49 | 2.16 |
| | | Hexane (5) | 0.01 | 0.05 |
| EP-25 | Roller Mill Baghouse No. 5 Stack | PM | 0.94 | 4.13 |
| | | PM ₁₀ | 0.94 | 4.13 |
| | | VOC | 0.03 | 0.14 |
| | | NO _x | 0.59 | 2.58 |
| | | SO ₂ | <0.01 | 0.02 |
| | | CO | 0.49 | 2.16 |
| | | Hexane (5) | 0.01 | 0.05 |
| EP-26 | Landplaster Conveyor Baghouse Stack | PM | 1.71 | 7.51 |
| | | PM ₁₀ | 1.71 | 7.51 |
| EP-27 | Kettle Calciner ESP Stack (7) | PM | 14.14 | 61.95 |
| | | PM ₁₀ | 14.14 | 61.95 |

| | | | | |
|-------|---------------------------------|------------------|------|------|
| EP-28 | No. 1 Kettle Combustion Chamber | PM | 0.10 | 0.42 |
| | | PM ₁₀ | 0.10 | 0.42 |
| | | VOC | 0.07 | 0.31 |
| | | NO _x | 1.27 | 5.58 |

Emission Sources - Maximum Allowable Emission Rates

| | | | | |
|-------|---------------------------------|------------------|------|------|
| | | SO ₂ | 0.01 | 0.03 |
| | | CO | 1.07 | 4.69 |
| | | Hexane (5) | 0.02 | 0.10 |
| EP-29 | No. 2 Kettle Combustion Chamber | PM | 0.10 | 0.42 |
| | | PM ₁₀ | 0.10 | 0.42 |
| | | VOC | 0.07 | 0.31 |
| | | NO _x | 1.27 | 5.58 |
| | | SO ₂ | 0.01 | 0.03 |
| | | CO | 1.07 | 4.69 |
| | | Hexane (5) | 0.02 | 0.10 |
| EP-30 | No. 3 Kettle Combustion Chamber | PM | 0.10 | 0.42 |
| | | PM ₁₀ | 0.10 | 0.42 |
| | | VOC | 0.07 | 0.31 |
| | | NO _x | 1.27 | 5.58 |
| | | SO ₂ | 0.01 | 0.03 |
| | | CO | 1.07 | 4.69 |
| | | Hexane (5) | 0.02 | 0.10 |
| EP-31 | No. 4 Kettle Combustion Chamber | PM | 0.10 | 0.42 |
| | | PM ₁₀ | 0.10 | 0.42 |
| | | VOC | 0.07 | 0.31 |
| | | NO _x | 1.27 | 5.58 |
| | | SO ₂ | 0.01 | 0.03 |
| | | CO | 1.07 | 4.69 |
| | | Hexane (5) | 0.02 | 0.10 |
| EP-32 | No. 5 Kettle Combustion Chamber | PM | 0.10 | 0.42 |
| | | PM ₁₀ | 0.10 | 0.42 |
| | | VOC | 0.07 | 0.31 |
| | | NO _x | 1.27 | 5.58 |
| | | SO ₂ | 0.01 | 0.03 |
| | | CO | 1.07 | 4.69 |

Emission Sources - Maximum Allowable Emission Rates

| | | | | |
|-------|---|------------------|------|------|
| EP-33 | No. 6 Kettle Combustion Chamber | Hexane (5) | 0.02 | 0.10 |
| | | PM | 0.10 | 0.42 |
| | | PM ₁₀ | 0.10 | 0.42 |
| | | VOC | 0.07 | 0.31 |
| | | NO _x | 1.27 | 5.58 |
| | | SO ₂ | 0.01 | 0.03 |
| | | CO | 1.07 | 4.69 |
| | | Hexane (5) | 0.02 | 0.10 |
| EP-34 | No. 7 Kettle Combustion Chamber | PM | 0.10 | 0.42 |
| | | PM ₁₀ | 0.10 | 0.42 |
| | | VOC | 0.07 | 0.31 |
| | | NO _x | 1.27 | 5.58 |
| | | SO ₂ | 0.01 | 0.03 |
| | | CO | 1.07 | 4.69 |
| | | Hexane (5) | 0.02 | 0.10 |
| EP-36 | No. 1 Line Board Stucco Silo Baghouse Stack | PM | 0.64 | 2.82 |
| | | PM ₁₀ | 0.64 | 2.82 |
| EP-37 | Outdoor Stucco Conveyors Baghouse Stack | PM | 1.71 | 7.51 |
| | | PM ₁₀ | 1.71 | 7.51 |
| EP-40 | No. 1 Line Board Dryer Wet End Seal | PM | 0.28 | 1.21 |
| | | PM ₁₀ | 0.28 | 1.21 |

| | | | | |
|-------|--|------------------|-------|--------|
| EP-45 | No. 1 Line Board Dryer Zone Nos. 1 through 5 | PM | 33.67 | 147.50 |
| | | PM ₁₀ | 9.60 | 42.10 |
| | | VOC | 36.98 | 162.00 |
| | | NO _x | 8.60 | 37.67 |
| | | SO ₂ | 0.05 | 0.23 |
| | | CO | 7.22 | 31.64 |
| | | NH ₃ | 6.96 | 30.50 |
| | | Hexane (5) | 0.15 | 0.68 |

Emission Sources - Maximum Allowable Emission Rates

| | | | | |
|-------|---------------------------------------|---------------------|-------|-------|
| | | Glycol Ethers (5) | 0.03 | 0.11 |
| | | Ethylene Glycol (5) | <0.01 | <0.01 |
| | | Formaldehyde (5) | 0.03 | 0.10 |
| | | Acetaldehyde (5) | 0.26 | 1.12 |
| | | 1,2 Ethanediol | 0.80 | 3.52 |
| | | Triethylamine (5) | 0.19 | 0.82 |
| EP-46 | No. 1 Line Board Dryer Dry End Seal | PM | 0.50 | 2.18 |
| | | PM ₁₀ | 0.50 | 2.18 |
| EP-47 | System No. 1 Baghouse Stack | PM | 1.02 | 4.47 |
| | | PM ₁₀ | 1.02 | 4.47 |
| EP-48 | Dens Shield Paint Line Baghouse Stack | PM | 1.07 | 4.69 |
| | | PM ₁₀ | 1.07 | 4.69 |
| | | VOC | 0.18 | 0.78 |
| | | NH ₃ | 0.10 | 0.42 |
| | | Glycol Ethers (5) | 0.06 | 0.26 |
| | | 1,2 Ethanediol | 0.06 | 0.26 |
| | | Triethylamine (5) | 0.06 | 0.26 |

| | | | | |
|--------|--------------------------|-------------------|-------|------|
| EP-48F | Paint Line Fugitives (4) | PM | 0.02 | 0.07 |
| | | PM ₁₀ | 0.02 | 0.07 |
| | | VOC | 0.90 | 3.95 |
| | | NO _x | 0.21 | 0.90 |
| | | SO ₂ | <0.01 | 0.01 |
| | | CO | 0.17 | 0.76 |
| | | NH ₃ | 0.48 | 2.08 |
| | | Hexane (5) | <0.01 | 0.02 |
| | | Glycol Ethers (5) | 0.06 | 0.26 |
| | | 1,2 Ethanediol | 0.30 | 1.30 |

Emission Sources - Maximum Allowable Emission Rates

| | | | | |
|-------|---|-------------------|-------|-------|
| | | Triethylamine (5) | 0.30 | 1.30 |
| EP-54 | No. 2 Board Line Stucco Silo Baghouse Stack | PM | 0.64 | 2.82 |
| | | PM ₁₀ | 0.64 | 2.82 |
| EP-55 | No. 2 Board Line Inline Coating | VOC | 0.73 | 3.19 |
| | | NH ₃ | 1.89 | 8.28 |
| | | 1,2 Ethanediol | 0.22 | 0.96 |
| | | Triethylamine (5) | 0.05 | 0.22 |
| EP-56 | No. 2 Line Mixer Vent | PM | 0.09 | 0.38 |
| | | PM ₁₀ | 0.09 | 0.38 |
| EP-58 | No. 2 Line Board Dryer Infeed Hood | PM | 0.25 | 1.10 |
| | | PM ₁₀ | 0.25 | 1.10 |
| EP-59 | No. 2 Line Board Dryer Germane Jet | PM | <0.01 | <0.01 |
| | | PM ₁₀ | <0.01 | <0.01 |

| | | | | |
|-------|--|---------------------|-------|--------|
| EP-62 | No. 2 Line Board Dryer Zone Nos. 1 - 3 | PM | 30.50 | 133.60 |
| | | PM ₁₀ | 8.70 | 38.10 |
| | | VOC | 34.90 | 152.90 |
| | | NO _x | 7.65 | 33.49 |
| | | SO ₂ | 0.05 | 0.20 |
| | | CO | 6.42 | 28.10 |
| | | NH ₃ | 4.41 | 19.30 |
| | | Hexane (5) | 0.14 | 0.60 |
| | | Glycol Ethers (5) | 0.02 | 0.11 |
| | | Ethylene Glycol (5) | <0.01 | <0.01 |
| | | Formaldehyde (5) | 0.03 | 0.11 |
| | | Acetaldehyde (5) | 0.25 | 1.07 |

Emission Sources - Maximum Allowable Emission Rates

| | | | | |
|---------|---|-------------------|-------|-------|
| | | 1,2 Ethanediol | 0.51 | 2.23 |
| | | Triethylamine (5) | 0.12 | 0.52 |
| EP-62-2 | No. 2 Line Board Dryer Dry End Seal | PM | 0.45 | 1.97 |
| | | PM ₁₀ | 0.45 | 1.97 |
| EP-63 | Fiberglass Line Baghouse Stack | PM | 2.40 | 10.51 |
| | | PM ₁₀ | 2.40 | 10.51 |
| EP-64 | No. 2 Line Riser Baghouse Stack | PM | 0.56 | 2.44 |
| | | PM ₁₀ | 0.56 | 2.44 |
| EP-67 | Railcar Unloading Pit | PM | 0.02 | 0.10 |
| | | PM ₁₀ | 0.01 | 0.04 |
| EP-69F | Natural Gas Space Heaters/Paper Heaters (4) | PM | 0.03 | 0.12 |
| | | PM ₁₀ | 0.03 | 0.12 |
| | | VOC | 0.02 | 0.09 |
| | | NO _x | 0.35 | 1.55 |
| | | SO ₂ | <0.01 | 0.01 |
| | | CO | 0.30 | 1.30 |
| | | Hexane (5) | 0.01 | 0.03 |
| EP-70F | Diesel Space Heaters (4) | PM | 0.02 | 0.10 |
| | | PM ₁₀ | 0.02 | 0.10 |
| | | VOC | <0.01 | 0.02 |
| | | NO _x | 0.13 | 0.56 |
| | | SO ₂ | 0.50 | 2.20 |
| | | CO | 0.04 | 0.15 |
| EP-73 | Joint Production Baghouse Stack | PM | 0.56 | 2.44 |
| | | PM ₁₀ | 0.56 | 2.44 |
| EP-80 | Starch Silo Baghouse Stack | PM | 0.17 | 0.75 |
| | | PM ₁₀ | 0.17 | 0.75 |
| EP-81 | System No. 2 Baghouse Stack | PM | 0.44 | 1.92 |
| | | PM ₁₀ | 0.44 | 1.92 |
| EP-88 | Diesel Storage Tank (2,000 Gallons) | VOC | <0.01 | <0.01 |
| EP-89 | Gasoline Storage Tank (1,000 Gallons) | VOC | 1.36 | 0.54 |

Emission Sources - Maximum Allowable Emission Rates

| | | | | |
|-------|---------------------------------------|-----|-------|-------|
| EP-90 | Diesel Storage Tank (10,000 Gallons) | VOC | 0.01 | 0.01 |
| EP-91 | Gasoline Storage Tank (2,000 Gallons) | VOC | 1.46 | 1.00 |
| EP-92 | Diesel Storage Tank (82 Gallons) | VOC | <0.01 | <0.01 |
| EP-93 | Used Oil Storage Tank (500 Gallons) | VOC | <0.01 | <0.01 |
| EP-94 | Used Oil Storage Tank (500 Gallons) | VOC | <0.01 | <0.01 |
| EP-95 | Soap Tank (7,000 Gallons) | VOC | <0.01 | 0.01 |
| EP-96 | Maintenance Parts Washers (3 total) | VOC | 0.23 | 0.99 |

- (1) Emission point identification - either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources use area name or fugitive source name.
- (3) PM - particulate matter, suspended in the atmosphere, including PM₁₀
PM₁₀ - particulate matter less than 10 microns in diameter
VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code ' 101.1
NO_x - total oxides of nitrogen
SO₂ - sulfur dioxide
CO - carbon monoxide
NH₃ - ammonia
- (4) Fugitive emissions are an estimate only.
- (5) The combination of all Hazardous Air Pollutants (HAPs) shall not exceed 25 tons per year (tpy) and the facility shall emit less than 10 tpy of a single HAP.
- (6) Planned startup and shutdown emissions are included as well as planned maintenance activities identified as part of the permit alteration request submitted on January 3, 2013.
- (7) During startup of the electrostatic precipitator (EPN EP-27), the emission will be authorized by 30 TAC 106.263.

Date: December 12, 2013