

Emission Sources - Maximum Allowable Emission Rates

Permit Numbers 102731 and PSDTX1294

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities, sources, and related activities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

Air Contaminants Data

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
Option 1				
SRB51	GE 7FA (5) Combined Cycle	NO _x	20.4	73.8
		NO _x (MSS)	42.0	-
		CO	24.8	44.9
		CO (MSS)	159.9	-
		VOC	4.4	11.7
		VOC (MSS)	34.6	-
		PM	20.2	70.3
		PM ₁₀	20.2	70.3
		PM _{2.5}	20.2	70.3
		SO ₂	3.9	14.2
		H ₂ SO ₄	2.8	9.8
		NH ₃	26.4	95.6

Emission Sources - Maximum Allowable Emission Rates

SRB51b	GE 7FA (5) Simple Cycle	NO _x	73.2	91.5
		NO _x (MSS)	74.5	-
		CO	35.6	44.5
		CO (MSS)	164.2	-
		VOC	3.4	4.3
		VOC (MSS)	34.2	-
		PM	9.0	11.3
		PM ₁₀	9.0	11.3
		PM _{2.5}	9.0	11.3
		SO ₂	3.0	3.7
		H ₂ SO ₄	0.2	0.3
SRB52	GE 7FA (5) Combined Cycle	NO _x	20.4	73.8
		NO _x (MSS)	42.0	-
		CO	24.8	44.9
		CO (MSS)	159.9	-
		VOC	4.4	11.7
		VOC (MSS)	34.6	-
		PM	20.2	70.3
		PM ₁₀	20.2	70.3
		PM _{2.5}	20.2	70.3
		SO ₂	3.9	14.2
		H ₂ SO ₄	2.8	9.8
SRB52b	GE 7FA (5) Simple Cycle	NO _x	73.2	91.5
		NO _x (MSS)	74.5	-

Emission Sources - Maximum Allowable Emission Rates

		CO	35.6	44.5
		CO (MSS)	164.2	-
		VOC	3.4	4.3
		VOC (MSS)	34.2	-
		PM	9.0	11.3
		PM ₁₀	9.0	11.3
		PM _{2.5}	9.0	11.3
		SO ₂	3.0	3.7
		H ₂ SO ₄	0.2	0.3
AUX-BLR	Auxiliary Boiler	NO _x	1.60	3.20
		CO	2.96	5.92
		VOC	0.43	0.86
		PM	0.60	1.19
		PM ₁₀	0.60	1.19
		PM _{2.5}	0.60	1.19
		SO ₂	0.06	0.11
SRB51, SRB51b, SRB52, SRB52b, and AUX-BLR	Annual Cap	NO _x	-	300.11
		CO	-	160.30
		VOC	-	23.48
		PM	-	140.60
		PM ₁₀	-	140.60
		PM _{2.5}	-	140.60
		SO ₂	-	30.10
		H ₂ SO ₄	-	19.54
Option 2				

Emission Sources - Maximum Allowable Emission Rates

SRB51	Siemens F5 (5) Combined Cycle	NO _x	22.2	83.3
		NO _x (MSS)	39.0	-
		CO	27.0	50.7
		CO (MSS)	284.1	-
		VOC	4.9	11.8
		VOC (MSS)	16.1	-
		PM	21.7	72.2
		PM ₁₀	21.7	72.2
		PM _{2.5}	21.7	72.2
		SO ₂	4.2	15.8
		H ₂ SO ₄	3.0	10.8
		NH ₃	28.7	107.9
SRB51b	Siemens F5 (5) Simple Cycle	NO _x	78.7	98.3
		CO	21.3	26.6
		CO (MSS)	280.5	-
		VOC	3.0	3.8
		VOC (MSS)	14.9	-
		PM	9.0	11.3
		PM ₁₀	9.0	11.3
		PM _{2.5}	9.0	11.3
		SO ₂	3.1	3.9
		H ₂ SO ₄	0.3	0.3
SRB52	Siemens F5 (5) Combined Cycle	NO _x	22.2	83.3
		NO _x (MSS)	39.0	-
		CO	27.0	50.7

Emission Sources - Maximum Allowable Emission Rates

		CO (MSS)	284.1	-
		VOC	4.9	11.8
		VOC (MSS)	16.1	-
		PM	21.7	72.2
		PM ₁₀	21.7	72.2
		PM _{2.5}	21.7	72.2
		SO ₂	4.2	15.8
		NH ₃	28.7	107.9
		H ₂ SO ₄	3.0	10.8
SRB52b	Siemens F5 (5) Simple Cycle	NO _x	78.7	98.3
		CO	21.3	26.6
		CO (MSS)	280.5	-
		VOC	3.0	3.8
		VOC (MSS)	14.9	-
		PM	9.0	11.3
		PM ₁₀	9.0	11.3
		PM _{2.5}	9.0	11.3
		SO ₂	3.1	3.9
AUX-BLR	Auxiliary Boiler	H ₂ SO ₄	0.3	0.3
		NO _x	1.60	3.20
		CO	2.96	5.92
		VOC	0.43	0.86
		PM	0.60	1.19
		PM ₁₀	0.60	1.19
		PM _{2.5}	0.60	1.19

Emission Sources - Maximum Allowable Emission Rates

		SO ₂	0.06	0.11
SRB51, SRB51b, SRB52, SRB52b, and AUX-BLR	Annual Cap	NO _x	-	196.63
		CO	-	137.66
		VOC	-	23.52
		PM	-	144.42
		PM ₁₀	-	144.42
		PM _{2.5}	-	144.42
		SO ₂	-	34.15
		H ₂ SO ₄	-	21.63
Option 3				
SRB51	MHI 501G (5) Combined Cycle	NO _x	24.8	86.9
		NO _x (MSS)	40.3	-
		CO	30.2	52.9
		CO (MSS)	282.6	-
		VOC	4.9	11.7
		VOC (MSS)	17.0	-
		PM	21.7	73.1
		PM ₁₀	21.7	73.1
		PM _{2.5}	21.7	73.1
		SO ₂	4.9	17.2
		H ₂ SO ₄	3.5	11.7
		NH ₃	32.1	112.6

Emission Sources - Maximum Allowable Emission Rates

SRB51b	MHI 501G (5) Simple Cycle	NO _x	92.7	115.9
		CO	62.7	78.4
		CO (MSS)	296.1	-
		VOC	3.6	4.5
		VOC (MSS)	16.5	-
		PM	9.0	11.3
		PM ₁₀	9.0	11.3
		PM _{2.5}	9.0	11.3
		SO ₂	3.9	4.9
		H ₂ SO ₄	0.3	0.4
SRB52	MHI 501G (5) Combined Cycle	NO _x	24.8	86.9
		NO _x (MSS)	40.3	-
		CO	30.2	52.9
		CO (MSS)	282.6	-
		VOC	4.9	11.7
		VOC (MSS)	17.0	-
		PM	21.7	73.1
		PM ₁₀	21.7	73.1
		PM _{2.5}	21.7	73.1
		SO ₂	4.9	17.2
		H ₂ SO ₄	3.5	11.7
		NH ₃	32.1	112.6
SRB52b	MHI 501G (5) Simple Cycle	NO _x	92.7	115.9
		CO	62.7	78.4
		CO (MSS)	296.1	-

Emission Sources - Maximum Allowable Emission Rates

		VOC	3.6	4.5
		VOC (MSS)	16.5	-
		PM	9.0	11.3
		PM ₁₀	9.0	11.3
		PM _{2.5}	9.0	11.3
		SO ₂	3.9	4.9
		H ₂ SO ₄	0.3	0.4
AUX-BLR	Auxiliary Boiler	NO _x	1.60	3.20
		CO	2.96	5.92
		VOC	0.43	0.86
		PM	0.60	1.19
		PM ₁₀	0.60	1.19
		PM _{2.5}	0.60	1.19
		SO ₂	0.06	0.11
SRB51, SRB51b, SRB52, SRB52b, and AUX-BLR	Annual Cap	NO _x	-	364.67
		CO	-	237.73
		VOC	-	23.60
		PM	-	146.15
		PM ₁₀	-	146.15
		PM _{2.5}	-	146.15
		SO ₂	-	36.06
		H ₂ SO ₄	-	23.48
Ancillary Emissions				
SRB51-LOV	Turbine 1 Lube Oil Vent	PM ₁₀	0.02	0.09
		PM _{2.5}	0.01	0.04

Emission Sources - Maximum Allowable Emission Rates

SRB52-LOV	Turbine 2 Lube Oil Vent	PM ₁₀	0.02	0.09
		PM _{2.5}	0.01	0.04
SRBST1-LOV	Steam Turbine 1 Lube Oil Vent	PM ₁₀	0.02	0.09
		PM _{2.5}	0.01	0.04
SRBST2-LOV	Steam Turbine 2 Lube Oil Vent	PM ₁₀	0.02	0.09
		PM _{2.5}	0.01	0.04
C-TOWER1	Cooling Tower 1	PM	4.50	19.73
		PM ₁₀	0.07	0.30
		PM _{2.5}	<0.01	0.01
C-TOWER2	Cooling Tower 2	PM	4.50	19.73
		PM ₁₀	0.07	0.30
		PM _{2.5}	<0.01	0.01
FUG-NGAS	Natural Gas Fugitives (6)	VOC	0.17	0.74
FUG-SCR	SCR Piping Fugitives (6)	NH ₃	0.02	0.10
FUG-MSS	Miscellaneous MSS Activities (6)	NO _x	<0.01	<0.01
		CO	<0.01	<0.01
		VOC	1.97	0.58
		PM	0.05	<0.01
		PM ₁₀	0.02	<0.01
		PM _{2.5}	<0.01	<0.01
		SO ₂	<0.01	<0.01
		NH ₃	<0.01	<0.01

- (1) Emission point identification - either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources, use area name or fugitive source name.
- (3) VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
- NO_x - total oxides of nitrogen
- SO₂ - sulfur dioxide

Emission Sources - Maximum Allowable Emission Rates

PM	- total particulate matter, suspended in the atmosphere, including PM ₁₀ and PM _{2.5} , as represented
PM ₁₀	- total particulate matter equal to or less than 10 microns in diameter, including PM _{2.5} , as represented
PM _{2.5}	- particulate matter equal to or less than 2.5 microns in diameter
CO	- carbon monoxide
H ₂ SO ₄	- sulfuric acid
NH ₃	- ammonia

- (4) Compliance with annual emission limits (tons per year) is based on a 12 month rolling period.
- (5) Planned maintenance, startup and shutdown (MSS) for all pollutants are authorized even if not specifically identified as MSS. During any clock hour that includes one or more minutes of planned MSS that pollutant's maximum hourly emission rate shall apply during that clock hour.
- (6) Emission rate is an estimate and is enforceable through compliance with the applicable special condition(s) and permit application representations.

Date: December 19, 2014