Permit Number 20807

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	<u>Emissio</u> lb/hr	n Rates * TPY**
1A	Preheater/Incinerator (5)	SO ₂ NO _x CO VOC PM/PM ₁₀ HCI Benzene (6) Ethyl Benzene (6) HAPs	19.50 4.73 19.58 4.91 3.05 0.24 0.14 0.28 0.06	85.41 20.72 79.16 5.41 8.82 0.84 0.50 0.98 0.28
3	Boiler (5)	PM/PM ₁₀ NO _x SO ₂ CO VOC HAPs	0.05 0.68 <0.01 0.57 0.04 0.01	0.23 3.00 0.02 2.51 0.16 0.06
29	Loading Rack Fugitives (4)(7)	PM/PM_{10} CO VOC H_2S	0.05 0.08 0.19 0.04	0.22 0.34 0.83 0.19
30	Loading Rack Fugitives (4)(7)	PM/PM_{10} CO VOC H_2S	0.05 0.08 0.19 0.04	0.22 0.34 0.83 0.19
31	BD Oil Loading (4)	VOC	0.13	0.56
33	Asphalt Solvent Cold Cleaner (4)	VOC	0.12	0.50

8	Tank 5 Heater (5)	PM/PM_{10} NO_x SO_2 CO VOC $HAPs$	0.01 0.08 <0.01 0.07 <0.01 <0.01	0.03 0.34 <0.01 0.29 0.02 0.01
10	Tank 100 Heater (5)	PM/PM_{10} NO_x SO_2 CO VOC $HAPs$	0.01 0.15 <0.01 0.12 0.01 <0.01	0.05 0.64 <0.01 0.54 0.04 0.01
12	Tank 202 Heater (5)	PM/PM_{10} NO_x SO_2 CO VOC $HAPs$	0.01 0.15 <0.01 0.12 0.01 <0.01	0.05 0.64 <0.01 0.54 0.04 0.01
63	Tank 401A Heater (5)	PM/PM_{10} NO_{x} SO_{2} CO VOC $HAPs$	0.01 0.15 <0.01 0.12 0.01 <0.01	0.05 0.64 <0.01 0.54 0.04 0.01
64	Tank 401B Heater (5)	PM/PM ₁₀ NO _x SO ₂ CO VOC HAPs	0.01 0.15 <0.01 0.12 0.01 <0.01	0.05 0.64 <0.01 0.54 0.04 0.01
65	Tank 402A Heater (5)	PM/PM_{10} NO_x SO_2	0.01 0.15 <0.01	0.05 0.64 <0.01

		CO	0.12	0.54
		VOC	0.01	0.04
		HAPs	< 0.01	0.01
66	Tank 402B Heater (5)	PM/PM ₁₀	0.01	0.05
	• •	NO_x	0.15	0.64
		SO_2	< 0.01	< 0.01
		CO	0.12	0.54
		VOC	0.01	0.04
		HAPs	< 0.01	0.01

- (1) Emission point identification either specific equipment designation or emission point number from a plot plan.
- (2) Specific point source names. For fugitive sources, use an area name or fugitive source name.
- (3) VOC volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1

NO_x - total oxides of nitrogen

SO₂ - sulfur dioxide

PM - particulate matter, suspended in the atmosphere, including PM₁₀ PM₁₀ - particulate matter equal to or less than 10 microns in diameter PM_{2.5} - particulate matter equal to or less than 2.5 microns in diameter

CO - carbon monoxide H₂S - hydrogen sulfide

HCl - hydrogen chloride/hydrochloric acid

HAP - any air contaminant (pollutant) listed in § 112(b) of the Federal Clean Air Act or Title 40 Code of Federal Regulations Part 63, Subpart C

- (4) Fugitive emissions are an estimate only.
- (5) Hazardous air pollutant (HAP) emissions are included in the PM and VOC allowable emission rates, and the speciated values are reflected on the Table 1(a) submitted with the permit amendment application. When a HAP compound hourly emission rate exceeded 0.04 pound per hour, the compound and its emission rate were listed on the maximum allowable emission rates table; however, the HAP compound emissions are also included in the PM and VOC emission rates.
- (6) Included in PM and VOC emission rates.
- (7) Emission rates are the sum of the emissions for all the listed emission points.
- * Emission rates are based on and the facilities are limited by the following maximum operating schedule:

24 Hrs/day 7 Days/week 52 Weeks/year or 8,760 Hrs/year

** Compliance with annual emission limits is based on a rolling 12-month period.

Maximum Asphalt Throughput Rates:

Total Asphalt Plant Site Input and Output: 260,000 TPY

Two Asphalt Blowing Stills/Convertors: 21.64 TPH 189,566 TPY
Truck Loading Racks: 21.64 GPH 60,000,000 GPY

Dated October 15, 2009