Emission Sources - Maximum Allowable Emission Rates

Permit Number 21101 and PSDTX1248

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities, sources, and related activities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

Air Contaminants Data

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
CA-1	Carbon Adsorption Unit	VOC	7.48	3.01
DEG-1	Degreaser-1	VOC	0.08	0.33
DEG-2	Degreaser-2	VOC	0.08	0.33
E-01-1544	Cracking Furnaces BA-101/102 Common Stack (6)	VOC	2.14	9.40
		NO_x	22.36	97.90
		CO	82.54	361.54
		SO_2	10.74	17.14
		PM	2.08	9.12
		PM_{10}	2.08	9.12
		$PM_{2.5}$	2.08	9.12
E-01A-1544	Economizer (6)	VOC	14.05	61.71
		NO_x	143.64	628.92
		CO	508.25	2,226.23
		SO_2	70.51	112.53
		PM	13.66	59.88
		PM_{10}	13.66	59.88
		$PM_{2.5}$	13.66	59.88

Emission Sources - Maximum Allowable Emission Rates

E-02-1544	Cracking Furnaces BA-103/104 Common Stack (6)	VOC	2.14	9.40
		NO_x	22.36	97.90
		CO	82.54	361.54
		SO_2	10.74	17.14
		PM	2.08	9.12
		PM_{10}	2.08	9.12
		$PM_{2.5}$	2.08	9.12
E-02A-1544	Cracking Furnace BA-115	VOC	1.86	8.13
		NO_x	130.00	95.40
		CO	150.00	42.40
		SO_2	9.30	14.85
		PM	1.80	7.90
		PM_{10}	1.80	7.90
		$PM_{2.5}$	1.80	7.90
E-03-1544	Cracking Furnaces BA-105/106 Common Stack (6)	VOC	2.14	9.40
		NO_x	22.36	97.90
		CO	82.54	361.54
		SO_2	10.74	17.14
		PM	2.08	9.12
		PM_{10}	2.08	9.12
		$PM_{2.5}$	2.08	9.12
E-03A-1544	Cracking Furnace BA-116	VOC	1.86	8.13
		NO_x	130.00	95.40
		CO	150.00	42.40
		SO_2	9.30	14.85
		PM	1.80	7.90
		PM_{10}	1.80	7.90
		$PM_{2.5}$	1.80	7.90
E-04-1544	Cracking Furnaces BA-107/108 Common Stack (6)	VOC	2.14	9.40
		NO_x	22.36	97.90
		CO	82.54	361.54

Emission Sources - Maximum Allowable Emission Rates

		SO_2	10.74	17.14
		PM	2.08	9.12
		PM_{10}	2.08	9.12
		$PM_{2.5}$	2.08	9.12
E-04A-1544	Cracking Furnace BA-117	VOC	1.86	8.13
		NO_x	130.00	95.40
		CO	150.00	42.40
		SO_2	9.30	14.85
		PM	1.80	7.90
		PM_{10}	1.80	7.90
		$PM_{2.5}$	1.80	7.90
E-05-1544	Cracking Furnaces BA-109/110 Common Stack (6)	VOC	2.14	9.40
		NO_x	22.36	97.90
		CO	82.54	361.54
		SO_2	10.74	17.14
		PM	2.08	9.12
		PM_{10}	2.08	9.12
		$PM_{2.5}$	2.08	9.12
E-05A-1544	Cracking Furnace BA-118	VOC	1.86	8.13
		NO_x	130.00	95.40
		CO	150.00	42.40
		SO_2	9.30	14.85
		PM	1.80	7.90
		PM_{10}	1.80	7.90
		$PM_{2.5}$	1.80	7.90
E-06-1544	Cracking Furnaces BA-111/112 Common Stack (6)	VOC	2.14	9.40
		NO_x	22.36	97.90
		CO	82.54	361.54
		SO_2	10.74	17.14
		PM	2.08	9.12
		PM_{10}	2.08	9.12

Emission Sources - Maximum Allowable Emission Rates

		$PM_{2.5}$	2.08	9.12
E-06A-1544	Decoke Drum	CO	114.00	35.08
		PM	61.00	0.96
		PM_{10}	61.00	0.96
		$PM_{2.5}$	61.00	0.96
E-07-1544	Steam Superheater BA-113 (6)	VOC	1.21	5.31
		NO_x	9.48	41.52
		CO	13.01	56.99
		SO_2	6.07	9.69
		PM	1.18	5.16
		PM_{10}	1.18	5.16
		$PM_{2.5}$	1.18	5.16
E-CAP	Emission Cap (6) Includes: E-01-1544 E-02-1544 E-03-1544 E-04-1544 E-05-1544 E-06-1544 E-07-1544 E-01A-1544	VOC	14.05	61.71
		NO_x	143.64	628.92
		CO	508.25	2,226.23
		SO_2	70.51	112.53
		PM	13.66	59.88
		PM_{10}	13.66	59.88
		$PM_{2.5}$	13.66	59.88
E-08-1544	Heater BA-301	VOC	0.13	0.57
		NO_x	1.68	7.35
		CO	1.41	6.17
		SO_2	0.66	1.05
		PM	0.13	0.56
		PM_{10}	0.13	0.56
		$PM_{2.5}$	0.13	0.56
E-09-1544	Heater BA-401	VOC	0.14	0.59
		NO_x	1.73	7.56
		CO	1.45	6.35
		SO_2	0.68	1.08

Emission Sources - Maximum Allowable Emission Rates

		PM	0.13	0.57
		PM_{10}	0.13	0.57
		$PM_{2.5}$	0.13	0.57
E-10-1544	Diesel Engine – Primary	VOC	0.08	0.34
		NO_x	2.99	13.07
		CO	2.45	10.74
		SO_2	0.01	0.04
		PM	0.10	0.42
		PM_{10}	0.10	0.42
		$PM_{2.5}$	0.10	0.42
E-11-1544	Diesel Engine - Secondary	VOC	0.08	0.34
		NO_x	2.99	13.07
		CO	2.45	10.74
		SO_2	0.01	0.04
		PM	0.10	0.42
		PM_{10}	0.10	0.42
		$PM_{2.5}$	0.10	0.42
E-24-FLARE	Process Flare - Normal Operation	VOC	416.50	33.96
		NO_x	90.68	38.34
		CO	362.11	148.24
		SO_2	0.33	0.83
		H_2S	0.01	0.01
	Process Flare - Normal Operation Contribution from Acetylene Converter Regeneration (7)	VOC	83.54	0.48
		NO_x	20.98	2.98
		CO	83.99	11.90
		SO_2	0.01	0.01
F-N1-VDU	Vapor Destruction Unit N1 for Storage Tanks 815 and 816	VOC	0.16	0.19
		NO_x	1.31	1.24
		CO	11.24	10.62
		SO_2	0.01	0.01
F-40-FLARE	Process Flare	VOC	476.58	23.19

Emission Sources - Maximum Allowable Emission Rates

		NO_x	71.49	7.02
		CO	364.28	35.79
		SO_2	1.41	0.11
		H_2S	0.01	0.01
F-17-FLARE	Back-Up Flare for Flare 40 (8)	VOC	-	-
		NO_x	-	-
		CO	-	-
		SO_2	-	-
		H_2S	-	-
E-137-CT	Cooling Tower 137 (5)	VOC	5.73	25.11
		PM	3.42	14.96
		PM_{10}	1.02	4.48
		$PM_{2.5}$	0.01	0.03
F-294PS	Cooling Tower 294 (5)	VOC	2.77	12.14
		PM	3.30	14.47
		PM_{10}	2.10	9.19
		$PM_{2.5}$	0.01	0.03
E-AN-1544	EU-1544 Analyzer Vents Routed to Atmosphere	VOC	0.16	0.65
		NO_x	0.01	0.01
		CO	0.01	0.01
E-AN-1740	Flame Ionization Detector	VOC	0.01	0.01
		NO_x	0.01	0.01
		CO	0.01	0.01
E-TNK-1544	EU-1544 Miscellaneous Storage Tanks	VOC	4.30	0.03
EU-CATSTACK	Silencer Stack - Normal Operation Emissions from Acetylene Converter Regeneration (7)	VOC	1.00	0.24
		CO	6.00	1.44
		SO_2	5.83	1.40
		PM	0.25	0.06
		PM_{10}	0.25	0.06
		$PM_{2.5}$	0.25	0.06

Emission Sources - Maximum Allowable Emission Rates

J-3	Firewater Pump Engine J-3	VOC	0.27	0.01
		NO_x	9.82	0.49
		CO	2.02	0.10
		SO_2	0.01	0.01
		PM	0.21	0.01
		PM_{10}	0.21	0.01
		$PM_{2.5}$	0.21	0.01
J-4	Firewater Pump Engine J-4	VOC	0.27	0.01
		NO_x	9.82	0.49
		CO	2.02	0.10
		SO_2	0.01	0.01
		PM	0.21	0.01
		PM_{10}	0.21	0.01
		$PM_{2.5}$	0.21	0.01
J-3-TNK	Firewater Engine J-3 Diesel Fuel Tank	VOC	0.02	0.01
J-4-TNK	Firewater Engine J-4 Diesel Fuel Tank	VOC	0.02	0.01
T-500	Gasoline Storage Tank	VOC	3.37	0.73
T-502	Diesel Storage Tank	VOC	0.25	0.01
T-FB-203	Wash Oil Tank	VOC	0.74	0.04

Emission Sources - Maximum Allowable Emission Rates

800	Storage Tank T-800	VOC	1.98	5.38
809	Storage Tank T-809	VOC	1.49	3.53
822	Storage Tank T-822	VOC	1.69	4.52
2158	Storage Tank T-2158	VOC	1.23	2.42
2176	Storage Tank T-2176	VOC	1.38	2.90
2177	Storage Tank T-2177	VOC	1.47	3.29
F-1746-CU	Cumene Unit Process Fugitives (5)	VOC	0.03	0.11
F-1741	Cyclohexane Unit Process Fugitives (5)	VOC	2.00	8.78
		Freon	2.23	9.77
F-8841	HVRU Process Fugitives (5)	VOC	0.66	2.90
F-138PS	Pump House 138 Fugitives (5)	VOC	0.05	0.22
F-229PS	Pump House 229 Fugitives (5)	VOC	0.22	0.98
F-382PS	Pump House 382 Fugitives (5)	VOC	0.22	0.96
F-1741OFFP	1741 Off Plot Fugitives (5)	VOC	0.25	1.08
F-1740	Fugitive Emissions from CFPU-1740 (5)	VOC	1.04	4.55
F-508	Fugitive Emissions from PS-508 (5)	VOC	0.33	1.43
F-1544	Process Fugitives (5)	VOC	37.81	165.62
		1,3-Butadiene	0.46	2.00
MSSTANK	MSS Tanks	VOC	25.44	4.64
		NO_X	1.25	0.36
		CO	1.46	0.42
		SO_2	0.04	0.01
		PM	0.34	0.05
		PM_{10}	0.34	0.05
		$PM_{2.5}$	0.34	0.05
		Benzene	12.68	1.80
MSS1544FLR	MSS Flare 24	VOC	2,933.17	112.11
		NO_X	464.93	23.62
		CO	3,057.24	148.31
		SO_2	254.36	16.96

Emission Sources - Maximum Allowable Emission Rates

	H_2S	2.71	0.18	
(1) Emission point identification - either specific equipment designation or emission point number from plot plan.		Benzene	139.54	5.99
(2) Specific point source name. For fugitive sources, use area name or fugitive source name.				
MSSATM	Atmospheric MSS Emissions	VOC	131.03	1.85
(3) VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1				
NO_x - total oxides of nitrogen		Benzene	9.67	0.28
SO_2 - sulfur dioxide				
PM - total particulate matter, suspended in the atmosphere, including PM_{10} and $PM_{2.5}$, as represented		H_2S	0.01	0.01
PM_{10} - total particulate matter equal to or less than 10 microns in diameter, including $PM_{2.5}$, as represented		PM	10.84	0.27
$PM_{2.5}$ - particulate matter equal to or less than 2.5 microns in diameter		PM_{10}	10.84	0.27
CO - carbon monoxide		$PM_{2.5}$	10.84	0.27
H_2S - hydrogen sulfide				
MSSCTRL	MSS Controlled Emissions	VOC	68.85	3.41
BD - butadiene		Benzene	20.65	1.02
(4) Compliance with annual emission limits (tons per year) is based on a 12 month rolling period.				
(5) Emission rate is an estimate and is enforceable through compliance with the applicable special condition(s) and permit application representations.				
MSSAROMFLR	MSS Flare 40 (or Flare 17)	VOC	166.26	8.42
(6) Emission Cap (EPN E-CAP) includes EPNs E-01-1544, E-02-1544, E-03-1544, E-04-1544, E-05-1544, E-06-1544, E-07-1544 and E-01A-1544.				
		NOx	15.21	1.39
(7) Routine emissions attributed to acetylene converter regeneration activities. These emissions were previously referred to as maintenance, startup, and shutdown (MSS) emissions.		CO	77.53	7.07
		SO2	0.29	0.02
(8) During periods when Flare 40 (EPN F-40-FLARE) is undergoing maintenance or is otherwise unavailable, Flare 17 (EPN F-17-FLARE) or a temporary flare meeting the requirements of 40 CFR §60.18 shall be used as the control device for all streams normally routed to Flare 40. Simultaneous operation of Flare 40 and Flare 17 or the temporary flare is prohibited. Emissions from Flare 40, Flare 17, and any associated temporary flare shall be limited to the MAERT limits established for Flare 40.		H_2S	0.01	0.01
		Benzene	10.45	0.51

Date: May 13, 2016