EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Permit Number 3386

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

AIR CONTAMINANTS DATA

Emission	Source	Air Contaminant	Emission Rates *	
Point No. (1)	Name (2)	Name (3)	lb/hr	TPY
RT001	Storage Tank, RT001 Petroleum Oil (10-825)	VOC	0.01	0.01
RT002	Storage Tank, RT002 Heavy Paraffin Distillate (10-480)	VOC	0.01	0.01
RT003	Storage Tank, RT003 Triethanolamine (08-120)	VOC	0.67	0.05
RT004	Storage Tank, RT004 Naphtha Distillate (10-580)	VOC	0.01	0.01
RT005	Storage Tank, RT005 Heavy Naphtha Distillate (10-460)	VOC	0.01	0.01
RT006	Storage Tank, RT006 Hexylene Glycol (10-175)	VOC	0.02	0.01
RT007	Storage Tank, RT007 Petroleum Distillate (10-475)	VOC	0.30	0.02
RT008	Storage Tank, RT008 Naphtha Distillate (10-505)	VOC	2.07	0.09
RT009	Storage Tank, RT009 Naphtha Distillate (10-250)	VOC	0.01	0.01

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

AIR CONTAMINANTS DATA

Emission	Source	Air Contaminant	Emission Rates *	
Point No. (1)	Name (2)	Name (3)	lb/hr	TPY
RT010	Storage Tank, RT010	VOC	0.01	0.01
DT011	Heavy Paraffin Distillate (10-480)	V00	0.01	0.01
RT011	Storage Tank, RT011 Mastigum (13-640)	VOC	0.01	0.01
RT012	Storage Tank, RT012 Heavy Naphtha Distillate (10-645)	VOC	0.08	0.01
RT013	Storage Tank, RT013 Petroleum Distillate (10-140)	VOC	0.69	0.03
RT014	Storage Tank, RT014 Potassium Hydroxide (06-105)	КОН	4.03	0.08
RT015	Storage Tank, RT015 Ethyl Hexyl Nitrate (16-115)	VOC	0.07	0.01
RT016	Storage Tank, RT016 Ethyl Hexyl Nitrate (16-115)	VOC	0.07	0.01
RT018	Storage Tank, RT018 Light Naphtha Distillate (10-210)	VOC	0.01	0.01
RT019	Storage Tank, RT019 Petroleum Distillate (10-140)	VOC	0.71	0.03
RT020	Storage Tank, RT020 Perchloroetheylene (10-370)	VOC	3.71	0.12

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

AIR CONTAMINANTS DATA

Emission	Source	Air Contaminant	<u>Emissio</u>	Emission Rates *	
Point No. (1)	Name (2)	Name (3)	lb/hr	TPY	
DT001	Ctorogo Tordy DT021	LICI	1.04	0.04	
RT021	Storage Tank, RT021 Hydrogen Chloride (01-120)	HCl	1.94	0.04	
RT022	Storage Tank, RT022 Phosphoric Acid (01-135)	H ₃ PO ₄	0.01	0.01	
RT023	Pressure Tank, RT023 Methylene Chloride (01-220)	VOC	0.01	0.01	
FUG	Fugitives (4)	VOC	0.67	2.94	
		KOH	80.0	0.36	
		HCI	0.01	0.02	
		H_3PO_4	0.01	0.02	
PROD	Production Operations	VOC	11.24	20.00(5)	
		KOH	0.22	0.01	
		NaOH 0.69	0.01	0.04	
		HCI	0.03	0.01	
		H ₃ PO ₄ PM 0.01	0.01 0.01	0.01	
		LINI O'OT	0.01		

- (1) Emission point identification either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. Each compound approved for storage is followed by the company's product code in parentheses. For fugitive sources use area name or fugitive source name.
- (3) VOC volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1

KOH - potassium hydroxide

NaOH - sodium hydroxide

HCl - hydrogen chloride H₃PO₄ - phosphoric acid

 $\,$ PM $\,$ - particulate matter, suspended in the atmosphere, including PM_{10}

	PM_{10} - particulate matter equal to or less than 10 microns in diameter. Where PM is not listed, it shall be assumed that no particulate matter greater than 10 microns is emitted.
Perr Pag	mit Number 3386 e 4
	EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES
(4)	Fugitive emissions are an estimate only and should not be considered as a maximum allowable emission rate.
(5)	Emission rate includes exempt solvents.
*	Emission rates are based on and the facilities are limited by the following maximum operating schedule:
	Hrs/dayDays/weekWeeks/year or Hrs/year_8,760_
	Dated April 3, 2004