

# Emission Sources - Maximum Allowable Emission Rates

Permit Number 2718

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities, sources, and related activities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

## Air Contaminants Data

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates (5)	
			lbs/hour	TPY (4)
CHF	Cullet Handling Fugitives (Rail and Truck Unloading, Stockpile, and Transfer to Crusher Feed Hopper) (6)	PM	0.12	0.53
		PM <sub>10</sub>	0.05	0.24
		PM <sub>2.5</sub>	0.05	0.24
TRACKBLDG	Track Shed Building Fugitives (Bulk Bag Unloader Dust Collector, Premix Material Batch Scale Dust Sock, and Premix Blending Dust Collector) (6)	PM	<0.01	<0.01
		PM <sub>10</sub>	<0.01	<0.01
		PM <sub>2.5</sub>	<0.01	<0.01
BATCHHOUSE	Batch House Fugitives for Minor Raw Material Ingredients (Premix Transport Dust Collector) (6)	PM	<0.01	<0.01
		PM <sub>10</sub>	<0.01	<0.01
		PM <sub>2.5</sub>	<0.01	<0.01
1	Furnace A Stack	PM	8.38	36.72
		PM <sub>10</sub>	8.32	36.45
		PM <sub>2.5</sub>	8.32	36.45
		VOC	0.40	1.80
		CO	5.50	24.10
		NO <sub>x</sub>	24.64	92.56
		SO <sub>2</sub>	30.27	61.71
		H <sub>2</sub> SO <sub>4</sub>	2.64	11.56
		HCl	0.50	2.20
		Pb	0.03	0.11
		NH <sub>3</sub>	0.68	2.97
55A	Furnace A Refiner Fugitives (6)	PM	0.03	0.13
		PM <sub>10</sub>	0.03	0.13
		PM <sub>2.5</sub>	0.03	0.13

Emission Sources - Maximum Allowable Emission Rates

		VOC	0.02	0.09
		CO	0.32	1.41
		NO <sub>x</sub>	0.38	1.67
		SO <sub>2</sub>	0.01	0.01
56A	Furnace A Alcoves and Forehearth Fugitives (6)	PM	0.07	0.30
		PM <sub>10</sub>	0.07	0.30
		PM <sub>2.5</sub>	0.07	0.30
		VOC	0.05	0.22
		CO	0.76	3.34
		NO <sub>x</sub>	0.91	3.98
		SO <sub>2</sub>	0.01	0.02
58A	Furnace A Forming Machines Fugitives (6)	PM	0.88	3.87
		PM <sub>10</sub>	0.88	3.87
		PM <sub>2.5</sub>	0.88	3.87
		VOC	0.88	3.87
		HF	0.01	0.05
2	Furnace B Stack	PM	7.81	34.15
		PM <sub>10</sub>	7.75	33.90
		PM <sub>2.5</sub>	7.75	33.90
		VOC	2.63	11.50
		CO	2.76	12.09
		NO <sub>x</sub>	22.96	86.08
		SO <sub>2</sub>	28.21	57.39
		H <sub>2</sub> SO <sub>4</sub>	2.99	13.07
		HCl	0.36	1.58
		Pb	0.02	0.10
		NH <sub>3</sub>	0.64	2.81
55B	Furnace B Refiner Fugitives (6)	PM	0.03	0.11

Emission Sources - Maximum Allowable Emission Rates

		PM <sub>10</sub>	0.03	0.11
		PM <sub>2.5</sub>	0.03	0.11
		VOC	0.02	0.08
		CO	0.29	1.26
		NO <sub>x</sub>	0.34	1.50
		SO <sub>2</sub>	0.01	0.01
56B	Furnace B Alcoves and Forehearths Fugitives (6)	PM	0.06	0.28
		PM <sub>10</sub>	0.06	0.28
		PM <sub>2.5</sub>	0.06	0.28
		VOC	0.05	0.21
		CO	0.72	3.14
		NO <sub>x</sub>	0.85	3.74
		SO <sub>2</sub>	0.01	0.02
58B	Furnace B Forming Machines Fugitives (6)	PM	0.85	3.73
		PM <sub>10</sub>	0.85	3.73
		PM <sub>2.5</sub>	0.85	3.73
		VOC	0.85	3.73
4	Furnace D Stack	PM	9.28	40.60
		PM <sub>10</sub>	9.21	40.30
		PM <sub>2.5</sub>	9.21	40.30
		VOC	0.20	0.90
		CO	3.90	17.10
		NO <sub>x</sub>	27.30	102.30
		SO <sub>2</sub>	33.54	68.20
		H <sub>2</sub> SO <sub>4</sub>	3.40	14.90
		HCl	0.53	2.30
		Pb	0.02	0.09
		NH <sub>3</sub>	0.75	3.30

Emission Sources - Maximum Allowable Emission Rates

55D	Furnace D Refiner Fugitives (6)	PM	0.03	0.13
		PM <sub>10</sub>	0.03	0.13
		PM <sub>2.5</sub>	0.03	0.13
		VOC	0.02	0.10
		CO	0.34	1.48
		NO <sub>x</sub>	0.40	1.76
		SO <sub>2</sub>	0.01	0.01
56D	Furnace D Alcoves and Forehearths Fugitives (6)	PM	0.06	0.27
		PM <sub>10</sub>	0.06	0.27
		PM <sub>2.5</sub>	0.06	0.27
		VOC	0.05	0.20
		CO	0.69	3.03
		NO <sub>x</sub>	0.82	3.61
		SO <sub>2</sub>	0.01	0.02
58D	Furnace D Forming Machines Fugitives (6)	PM	0.98	4.28
		PM <sub>10</sub>	0.98	4.28
		PM <sub>2.5</sub>	0.98	4.28
		VOC	0.98	4.28
		HF	0.02	0.06
7	Grit Blast Fugitives (6)	PM	0.02	0.10
		PM <sub>10</sub>	0.02	0.10
		PM <sub>2.5</sub>	0.02	0.10
8	Grit Blast Fugitives (6)	PM	0.02	0.10
		PM <sub>10</sub>	0.02	0.10
		PM <sub>2.5</sub>	0.02	0.10
18A - 18D	Raw Material Receiving Batch and Mixing Baghouse Stacks	PM	2.48	12.00
		PM <sub>10</sub>	2.48	12.00
		PM <sub>2.5</sub>	2.48	12.00

Emission Sources - Maximum Allowable Emission Rates

18E	Minor Raw Material Surge Hopper Baghouse Stack	PM	0.02	<0.01
		PM <sub>10</sub>	0.02	<0.01
		PM <sub>2.5</sub>	0.02	<0.01
57	Shear Spray Fugitives (6)	VOC	2.00	8.75
59A	Lehr Fugitives (6)	PM	0.30	1.31
		PM <sub>10</sub>	0.30	1.31
		PM <sub>2.5</sub>	0.30	1.31
		VOC	0.22	0.94
		CO	3.29	14.43
		NO <sub>x</sub>	3.92	17.18
		SO <sub>2</sub>	0.02	0.10
59B	Belt Heater Fugitives (6)	PM	0.01	0.07
		PM <sub>10</sub>	0.01	0.07
		PM <sub>2.5</sub>	0.01	0.07
		VOC	0.01	0.05
		CO	0.16	0.72
		NO <sub>x</sub>	0.20	0.86
		SO <sub>2</sub>	0.01	0.01
19	Hot End Surface Treatment Baghouses Stack	PM	0.46	2.07
		PM <sub>10</sub>	0.46	2.07
		PM <sub>2.5</sub>	0.46	2.07
		NH <sub>3</sub>	2.86	12.50
		HCl	0.04	0.17
		VOC	0.72	3.15
71	Bottle Coder Fugitives (6)	VOC	0.21	0.93
72	Glue Pot Fugitives (6)	VOC	0.45	1.97
73	Carton Coder Fugitives (6)	VOC	0.15	0.66
30	Reagent Silo Dust Collector Stack	PM	0.12	0.01

Emission Sources - Maximum Allowable Emission Rates

		PM <sub>10</sub>	0.12	0.01
		PM <sub>2.5</sub>	0.12	0.01
31	ESP Dust Silo Dust Collector Stack	PM	0.02	0.09
		PM <sub>10</sub>	0.02	0.09
		PM <sub>2.5</sub>	0.02	0.09
35	Emergency Generator Stack	PM	0.85	0.04
		PM <sub>10</sub>	0.71	0.04
		PM <sub>2.5</sub>	0.69	0.04
		VOC	0.58	0.03
		CO	13.50	0.68
		NO <sub>x</sub>	24.11	1.21
		SO <sub>2</sub>	0.03	<0.01
70	Oil/Water Separator Fugitives (6)	VOC	1.2	5.26
74	Cooling Tower Vents	PM	0.40	1.75
		PM <sub>10</sub>	0.30	1.31
		PM <sub>2.5</sub>	0.30	1.31
75	Parts Washer Fugitives (6)	VOC	0.22	0.97
MSS-A	Furnace A MSS	PM	12.41	2.00
		PM <sub>10</sub>	11.80	2.00
		PM <sub>2.5</sub>	11.31	2.00
		NO <sub>x</sub>	73.75	36.00
		SO <sub>2</sub>	78.67	38.00
		H <sub>2</sub> SO <sub>4</sub>	8.60	5.00
MSS-B	Furnace B MSS	PM	7.00	1.00
		PM <sub>10</sub>	6.60	1.00
		PM <sub>2.5</sub>	6.30	1.00
		NO <sub>x</sub>	68.60	33.00
		SO <sub>2</sub>	36.60	21.00

Emission Sources - Maximum Allowable Emission Rates

		H <sub>2</sub> SO <sub>4</sub>	4.80	2.30
MSS-D	Furnace D MSS	PM	31.07	4.00
		PM <sub>10</sub>	29.51	4.00
		PM <sub>2.5</sub>	28.25	4.00
		NO <sub>x</sub>	116.43	56.00
		SO <sub>2</sub>	124.27	60.00
		H <sub>2</sub> SO <sub>4</sub>	13.59	7.00

- (1) Emission point identification - either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources, use area name or fugitive source name.
- (3) VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1  
 NO<sub>x</sub> - total oxides of nitrogen  
 SO<sub>2</sub> - sulfur dioxide  
 PM - total particulate matter, suspended in the atmosphere, including PM<sub>10</sub> and PM<sub>2.5</sub>, as represented  
 PM<sub>10</sub> - total particulate matter equal to or less than 10 microns in diameter, including PM<sub>2.5</sub>, as represented  
 PM<sub>2.5</sub> - particulate matter equal to or less than 2.5 microns in diameter  
 CO - carbon monoxide  
 H<sub>2</sub>SO<sub>4</sub> - sulfuric acid  
 HCl - hydrogen chloride  
 Pb - lead as particulate matter  
 NH<sub>3</sub> - ammonia  
 HF - hydrogen fluoride
- (4) Compliance with annual emission limits (tons per year) is based on a 12-month rolling period.
- (5) Planned startup and shutdown emissions are included. Maintenance activities, except as specified in Special Condition Nos. 28 through 32, are not authorized by this permit and will need separate authorization, unless the activity can meet the conditions of 30 TAC § 116.119.
- (6) Emission rate is an estimate and is enforceable through compliance with the applicable special condition(s) and permit application representations.

Date: June 3, 2021