

# Emission Sources - Maximum Allowable Emission Rates

Permit Number 48196

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities, sources, and related activities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

## Air Contaminants Data

| Emission Point No. (1) | Source Name (2)                            | Air Contaminant Name (3) | Emission Rates (6) |         |
|------------------------|--|--------------------------|--------------------|---------|
|                        |  |                          | lbs/hour           | TPY (4) |
| BH-D1                  | Rotary Dryer Baghouse Stack (Plant 1)      | PM                       | 1.60               | 7.00    |
|                        |  | PM <sub>10</sub>         | 1.60               | 7.00    |
|                        |  | PM <sub>2.5</sub>        | 0.80               | 3.50    |
|                        |  | NO <sub>x</sub>          | 3.34               | 14.60   |
|                        |  | CO                       | 2.10               | 9.20    |
|                        |  | VOC                      | 0.14               | 0.60    |
|                        |  | SO <sub>2</sub>          | 2.51               | 11.00   |
| BH—S1                  | Scavenger Baghouse Stack (Plant 1)         | PM                       | 1.60               | 7.00    |
|                        |  | PM <sub>10</sub>         | 1.60               | 7.00    |
|                        |  | PM <sub>2.5</sub>        | 0.80               | 3.50    |
| BH-D2                  | Rotary Dryer Baghouse Stack (Plant 4)      | PM                       | 2.30               | 10.00   |
|                        |  | PM <sub>10</sub>         | 2.30               | 10.00   |
|                        |  | PM <sub>2.5</sub>        | 1.15               | 5.00    |
|                        |  | NO <sub>x</sub>          | 5.86               | 25.70   |
|                        |  | CO                       | 3.70               | 16.20   |
|                        |  | VOC                      | 0.24               | 1.06    |
|                        |  | SO <sub>2</sub>          | 4.40               | 19.00   |
| BH-S2                  | Scavenger Baghouse Stack (Plant 4)         | PM                       | 1.60               | 7.00    |
|                        |  | PM <sub>10</sub>         | 1.60               | 7.00    |
|                        |  | PM <sub>2.5</sub>        | 0.80               | 3.50    |
| BH-4                   | Scavenger Loadout Baghouse Stack (Plant 4) | PM                       | 0.46               | 2.00    |
|                        |  | PM <sub>10</sub>         | 0.46               | 2.00    |

## Emission Sources - Maximum Allowable Emission Rates

|       |  |                   |      |      |
|-------|--|-------------------|------|------|
|       |  | PM <sub>2.5</sub> | 0.23 | 1.00 |
| BH-RM | Mills Flash Dryer<br>Baghouse Stack (Plant<br>3) | PM                | 1.00 | 4.40 |
|       |  | PM <sub>10</sub>  | 1.00 | 4.40 |
|       |  | PM <sub>2.5</sub> | 0.50 | 2.20 |
|       |  | NO <sub>x</sub>   | 1.20 | 5.26 |
|       |  | CO                | 0.76 | 3.31 |
|       |  | VOC               | 0.05 | 0.22 |
|       |  | SO <sub>2</sub>   | 0.90 | 3.90 |
| BV-1  | Storage Silo Bin Vent                            | PM                | 0.08 | 0.34 |
|       |  | PM <sub>10</sub>  | 0.08 | 0.34 |
|       |  | PM <sub>2.5</sub> | 0.04 | 0.17 |
| BV-2  | Storage and Loadout<br>Silo Bin Vent             | PM                | 0.08 | 0.34 |
|       |  | PM <sub>10</sub>  | 0.08 | 0.34 |
|       |  | PM <sub>2.5</sub> | 0.04 | 0.17 |
| BV-8  | Bagging, Storage and<br>Loadout Silo Bin Vent    | PM                | 0.23 | 1.00 |
|       |  | PM <sub>10</sub>  | 0.23 | 1.00 |
|       |  | PM <sub>2.5</sub> | 0.12 | 0.50 |
| BV-12 | Storage and Loadout<br>Silo Bin Vent             | PM                | 0.23 | 1.00 |
|       |  | PM <sub>10</sub>  | 0.23 | 1.00 |
|       |  | PM <sub>2.5</sub> | 0.12 | 0.50 |
| BV-13 | Storage and Loadout<br>Silo Bin Vent             | PM                | 0.23 | 1.00 |
|       |  | PM <sub>10</sub>  | 0.23 | 1.00 |
|       |  | PM <sub>2.5</sub> | 0.12 | 0.50 |
| BV-14 | Storage and Loadout<br>Silo Bin Vent             | PM                | 0.31 | 1.40 |
|       |  | PM <sub>10</sub>  | 0.31 | 1.40 |
|       |  | PM <sub>2.5</sub> | 0.16 | 0.70 |

## Emission Sources - Maximum Allowable Emission Rates

|         |                                    |                   |      |      |
|---------|------------------------------------|-------------------|------|------|
| BV-15   | Storage and Loadout Silo Bin Vent  | PM                | 0.31 | 1.40 |
|         |                                    | PM <sub>10</sub>  | 0.31 | 1.40 |
|         |                                    | PM <sub>2.5</sub> | 0.16 | 0.70 |
| BV-16   | Storage and Loadout Silo Bin Vent  | PM                | 0.39 | 1.70 |
|         |                                    | PM <sub>10</sub>  | 0.39 | 1.70 |
|         |                                    | PM <sub>2.5</sub> | 0.20 | 0.85 |
| BV-17   | Storage and Loadout Silo Bin Vents | PM                | 0.39 | 1.70 |
|         |                                    | PM <sub>10</sub>  | 0.39 | 1.70 |
|         |                                    | PM <sub>2.5</sub> | 0.20 | 0.85 |
| BH-LO   | Loadout Baghouse Stack             | PM                | 1.00 | 4.40 |
|         |                                    | PM <sub>10</sub>  | 1.00 | 4.40 |
|         |                                    | PM <sub>2.5</sub> | 0.50 | 2.20 |
| DC-1553 | Dust Collection Baghouse Stack     | PM                | 0.34 | 1.50 |
|         |                                    | PM <sub>10</sub>  | 0.34 | 1.50 |
|         |                                    | PM <sub>2.5</sub> | 0.17 | 0.75 |
| DC-1559 | Loadout Spout Baghouse Stack       | PM                | 0.12 | 0.53 |
|         |                                    | PM <sub>10</sub>  | 0.12 | 0.53 |
|         |                                    | PM <sub>2.5</sub> | 0.06 | 0.27 |
| 17      | Primary Crusher (5)                | PM                | 0.13 | 0.55 |
|         |                                    | PM <sub>10</sub>  | 0.06 | 0.26 |
|         |                                    | PM <sub>2.5</sub> | 0.03 | 0.13 |
| BH-D3   | Baghouse for Rotary Dryer Stack    | PM                | 0.86 | 3.80 |
|         |                                    | PM <sub>10</sub>  | 0.86 | 3.80 |
|         |                                    | PM <sub>2.5</sub> | 0.13 | 0.57 |
|         |                                    | NO <sub>x</sub>   | 1.06 | 4.63 |
|         |                                    | CO                | 2.04 | 8.95 |
|         |                                    | VOC               | 1.01 | 4.44 |

## Emission Sources - Maximum Allowable Emission Rates

|      |                     |                   |       |      |
|------|---------------------|-------------------|-------|------|
|      |                     | SO <sub>2</sub>   | 0.07  | 0.30 |
| TR-1 | Transfer Points (5) | PM                | 0.05  | 0.22 |
|      |                     | PM <sub>10</sub>  | 0.02  | 0.08 |
|      |                     | PM <sub>2.5</sub> | <0.01 | 0.02 |

- (1) Emission point identification - either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources, use area name or fugitive source name.
- (3) VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
- NO<sub>x</sub> - total oxides of nitrogen
- SO<sub>2</sub> - sulfur dioxide
- PM - total particulate matter, suspended in the atmosphere, including PM<sub>10</sub> and PM<sub>2.5</sub>, as represented
- PM<sub>10</sub> - total particulate matter equal to or less than 10 microns in diameter, including PM<sub>2.5</sub>, as represented
- PM<sub>2.5</sub> - particulate matter equal to or less than 2.5 microns in diameter
- CO - carbon monoxide
- (4) Compliance with annual emission limits (tons per year) is based on a 12 month rolling period.
- (5) Emission rate is an estimate and is enforceable through compliance with the applicable special condition(s) and permit application representations.
- (6) Planned startup and shutdown emissions are included. Maintenance activities are not authorized by this permit.

Date: May 08, 2017