EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Permit Number 9423

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	<u>Emissio</u> lb/hr	n Rates * TPY**
EPNs Common	to C-Line, D-Line, and E-I	Line		
30 + 34	LOG Flare (EPN 30) and Elevated Flare (EPN 34) (6)	VOC (5) Ethylene Propylene NO _x CO	81.24 81.24 81.24 11.21 90.64	61.56 61.56 61.56 8.50 68.69
98	D-885 Waste Oil Loading Drum	VOC	2.02	0.06
Cooling Towers	3			
99	West Marley Cooling Tower	VOC (4) (5) Ethylene Propylene PM ₁₀ /PM _{2.5}	1.08 1.08 1.08 0.33	4.73 4.73 4.73 1.46
146	East Marley Cooling Tower	VOC (4) (5) Ethylene Propylene PM ₁₀ /PM _{2.5}	0.57 0.57 0.57 0.18	2.49 2.49 2.49 0.77
151	Excel Marley 3 Cooling Tower	VOC (4) (5) Ethylene Propylene PM ₁₀ /PM _{2.5}	1.0 1.0 1.0 0.30	4.4 4.4 4.4 1.32

Emission	Source	Air Contaminant	Emission Rates *	
Point No. (1)	Name (2)	Name (3)	lb/hr	TPY**
C-Line EPNs				
39	D-3106 Catalyst Handling Drum	VOC	0.01	0.01
40	D-3504 Stabilizer Addition Drum	PM ₁₀ VOC	0.01 0.01	0.01 0.01
109	D-3103 TEAL Seal Pot Drum	VOC	0.04	0.01
110	D-3105 Oil and Grease Mixing	VOC	0.21	0.01
111	D-3107 Hydraulic Oil Drum	VOC	0.04	0.01
112	D-3110A Donor Storage Drum	VOC	0.02	0.01
113	D-3110B Donor Storage Drum	VOC	0.02	0.01
114	TK-3111 Donor Storage Drum	VOC	0.02	0.01
115	T-3501 Scrubber Wastewater	VOC	0.07	0.31
35	Fugitives (4)	VOC NH₃	4.89 0.11	21.40 0.50
143	Mineral Oil Tank	VOC	0.01	0.01
144	Mineral Oil Tank	VOC	0.01	0.01
149	D-3106B Catalyst Handling Drum	VOC	0.62	0.03

Emission Point No.	Source (1) Name (2)	Air Contaminant Name (3)	<u>Emission Rates *</u> lb/hr	
1 01111 110.	(1) Name (2)	rvaine (5)	10/111	
150	CLX Cooling Tower (8)	PM ₁₀ /PM _{2.5}	0.15	0.66
D-Line EF	PNs			
37	D-4106 Catalyst Unloading	VOC	0.01	0.01
38	D-4504 Stabilizer Addition	VOC PM ₁₀	0.08 0.01	0.01 0.01
41	Fugitives (4)	VOC NH₃	3.38 0.11	14.81 0.50
103	D-4105 Oil and Grease Mixing	VOC	0.02	0.01
104	D-4110A Donor Storage Drum	VOC	0.02	0.01
105	D-4110B Donor Storage Drum	VOC	0.02	0.01
106	TK-4111 Donor Storage Drum	VOC	0.02	0.01
107	D-4103 TEAL Seal Pot	VOC	0.01	0.01
108	T-4501 Scrubber Wastewater	VOC	0.23	1.00
155	DLX Cooling Tower (8)	PM ₁₀ /PM _{2.5}	0.15	0.66
156	D4107 Hydraulic Oil Drum	VOC	0.02	0.02
E-Line EPNs				
50A	Catalyst Handling	VOC	0.42	0.03
50B	Catalyst Handling	VOC	0.42	0.04
51	Stabilizer Addition	VOC	0.01	0.01
124	TEAL Seal Pot	VOC	0.01	0.01

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	<u>Emissio</u> lb/hr	n Rates * TPY**
125	Oil and Grease Mixing	VOC	0.01	0.01
126	Hydraulic Oil Drum	VOC	0.01	0.01
127	Donor Storage Drum	VOC	0.02	0.01
128	Donor Storage Drum	VOC	0.02	0.01
129	Donor Storage Drum	VOC	0.02	0.01
130	Scrubber Wastewater	VOC	0.07	0.31
135	Additive Surge Drum	VOC	0.01	0.01
52	Fugitives (4)	VOC NH₃	6.86 0.11	30.03 0.48
147	Additive Storage	VOC	0.06	0.01
148	Additive Storage	VOC	0.02	0.01
EPNs Common	to C-Line, D-Line, and E-	Line Polymer Transfer,	Extrusion and L	oading
120	M-574 Bag Filter	VOC PM ₁₀	(7) 0.21	(7) 0.90
122	M-2574 Bag Filter	VOC PM ₁₀	(7) 0.21	(7) 0.90
116	Railcar Loading (Flake)	VOC	(7)	(7)
152	DLX Flake Transfer	VOC PM ₁₀	(7) 0.13	(7) 0.56
102	Railcar Loading/VOC Residual	VOC	(7)	(7)
153	DLX Pellet Silos	VOC	(7)	(7)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	<u>Emissio</u> lb/hr	n Rates * TPY**
154	Railcar Loading DLX	VOC PM ₁₀	(7) 0.20	(7) 0.88
14C	Pellet Transfer System	VOC PM ₁₀	(7) 0.06	(7) 0.26
131	Pellet Transfer System	VOC PM ₁₀	(7) 0.10	(7) 0.43
132	Railcar Loading CLX	VOC PM ₁₀	(7) 0.05	(7) 0.20
133	Railcar Loading ELX	VOC	(7)	(7)
	MAINTENANCE, STAF	RTUP, AND SHUTDOWN	I ACTIVITIES	
30 + 34	LOG Flare and Elevated Flare MSS Activities (6)	VOC (5)	540.00	(9)
		Ethylene Propylene NO _x CO	265.00 540.00 75.00 605.00	
MSS41	C-Line Maintenance Shutdown	VOC	15.18	0.06
MSS42	D-Line Maintenance Shutdown	VOC	15.18	0.06
MSS43	E-Line Maintenance Shutdown	VOC	26.22	0.10

Emission	Source	Air Contaminant	Emission Rates *	
Point No. (1)	Name (2)	Name (3)	lb/hr	TPY**
MSS44	Bullets Area Maintenance Shutdown	VOC	26.22	0.01
MSS45	Monomer Supplier Proving	VOC	0.01	0.01
MSS46	C-Line Compressor Maintenance	VOC	0.01	0.01
MSS47	D-Line Compressor Maintenance	VOC	0.01	0.01
MSS48	E-Line Compressor Maintenance	VOC	0.01	0.01
MSS49	C-Line Pump Maintenance	VOC	0.06	0.01
MSS50	D-Line Pump Maintenance	VOC	0.06	0.01
MSS51	E-Line Pump Maintenance	VOC	0.06	0.01
MSS52	Bullet Pump Maintenance	VOC	0.06	0.01
MSS53	C-Line Commercial Shutdown	VOC	15.18	0.06
MSS54	D-Line Commercial Shutdown	VOC	15.18	0.06
MSS55	E-Line Commercial Shutdown	VOC	26.22	0.10
MSS56	E-Line Gas Phase Reactor Cleaning	VOC	11.04	0.14

Emission	Source	Air Contaminant	Emission Rates *	
Point No. (1)	Name (2)	Name (3)	lb/hr	TPY**
MSS57	C-Line Filter Changes	VOC	0.03	0.01
MSS58	D-Line Filter Changes	VOC	0.03	0.01
MSS59	E-Line Filter Changes	VOC	0.03	0.01
MSS60	C/D/E Instrument Maintenance (repair/replace)	VOC	0.01	0.01

FOOTNOTES:

- (1) Emission point identification either specific equipment designation or emission point number (EPN) from a plot plan.
- (2) Specific point source names. For fugitive sources, use an area name or fugitive source name.
- (3) VOC volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1

NO_x - total oxides of nitrogen

PM₁₀ - particulate matter equal to or less than 10 microns in diameter

PM_{2.5} - particulate matter equal to or less than 2.5 microns in diameter

CO - carbon monoxide

NH₃ - ammonia

- (4) Emission rate is an estimate and compliance is demonstrated by meeting the requirements of the applicable special conditions and permit application representations.
- (5) The allowable emission rates for individual VOC species from this EPN are included in the total VOC emission rates.
- (6) Emission rates shown are combined totals for EPN 30 and EPN 34.
- (7) The combined total VOC emissions for all EPNs with this note shall not exceed 3.02 pounds per hour (lbs/hr) and 9.29 tons per year (TPY).
- (8) The CLX and DLX cooling towers are authorized by unregistered permit by rule 106.371 and are incorporated by reference into the permit.
- (9) The combined annual allowable emission limits for these EPNs are specified on Page one.

*	Emission rates are based on and the facilities are limited by the following maximum operating schedule:
	Hrs/day Days/weekWeeks/year or <u>8,760</u> Hrs/year

** Compliance with annual emission limits is based on a rolling 12-month period.

Dated December 29, 2010