

Emission Sources - Maximum Allowable Emission Rates

Permit Numbers 36644, PSDTX903M5, and N007M1

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities, sources, and related activities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

Air Contaminants Data

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
N-1	Recycle Ethane Cracking Furnace H-0100	NO _x (7) (10)	48.32	-
		NO _x (7)	24.16	79.37
		SO ₂ (7)	2.21	4.83
		CO (7) (11)	46.50	-
		CO (7)	23.25	101.85
		PM (7)	1.51	6.61
		PM ₁₀ (7)	1.51	6.61
		PM _{2.5} (7)	1.51	6.61
		VOC (7)	0.57	2.51
N-2	Fresh Feed Cracking Furnace H-0200	NO _x (7) (10)	70.68	-
		NO _x (7)	35.34	116.08
		SO ₂ (7)	3.22	7.07
		CO (7) (11)	68.02	-
		CO (7)	34.01	148.97
		PM (7)	2.21	9.67
		PM ₁₀ (7)	2.21	9.67
		PM _{2.5} (7)	2.21	9.67
		VOC (7)	0.84	3.68
N-3	Fresh Feed Cracking Furnace H-0300	NO _x (7) (10)	70.68	-
		NO _x (7)	35.34	116.08
		SO ₂ (7)	3.22	7.07
		CO (7) (11)	68.02	-
		CO (7)	34.01	148.97
		PM (7)	2.21	9.67

Emission Sources - Maximum Allowable Emission Rates

		PM ₁₀ (7)	2.21	9.67
		PM _{2.5} (7)	2.21	9.67
		VOC (7)	0.84	3.68
N-4	Fresh Feed Cracking Furnace H-0400	NO _x (7) (10)	70.68	-
		NO _x (7)	35.34	116.08
		SO ₂ (7)	3.22	7.07
		CO (7) (11)	68.02	-
		CO (7)	34.01	148.97
		PM (7)	2.21	9.67
		PM ₁₀ (7)	2.21	9.67
		PM _{2.5} (7)	2.21	9.67
		VOC (7)	0.84	3.68
N-5	Fresh Feed Cracking Furnace H-0500	NO _x (7) (10)	70.68	-
		NO _x (7)	35.34	116.08
		SO ₂ (7)	3.22	7.07
		CO (7) (11)	68.02	-
		CO (7)	34.01	148.97
		PM (7)	2.21	9.67
		PM ₁₀ (7)	2.21	9.67
		PM _{2.5} (7)	2.21	9.67
		VOC (7)	0.84	3.68

Emission Sources - Maximum Allowable Emission Rates

N-6	Fresh Feed Cracking Furnace H-0600	NO _x (7) (10)	70.68	-
		NO _x (7)	35.34	116.08
		SO ₂ (7)	3.22	7.07
		CO (7) (11)	68.02	-
		CO (7)	34.01	148.97
		PM (7)	2.21	9.67
		PM ₁₀ (7)	2.21	9.67
		PM _{2.5} (7)	2.21	9.67
		VOC (7)	0.84	3.68
N-7	Fresh Feed Cracking Furnace H-0700	NO _x (7) (10)	70.68	-
		NO _x (7)	35.34	116.08
		SO ₂ (7)	3.22	7.07
		CO (7) (11)	68.02	-
		CO (7)	34.01	148.97
		PM (7)	2.21	9.67
		PM ₁₀ (7)	2.21	9.67
		PM _{2.5} (7)	2.21	9.67
		VOC (7)	0.84	3.68
N-8	Fresh Feed Cracking Furnace H-0800	NO _x (7) (10)	70.68	-
		NO _x (7)	35.34	116.08
		SO ₂ (7)	3.22	7.07
		CO (7) (11)	68.02	-
		CO (7)	34.01	148.97
		PM (7)	2.21	9.67
		PM ₁₀ (7)	2.21	9.67
		PM _{2.5} (7)	2.21	9.67
		VOC (7)	0.84	3.68
N-9	Fresh Feed Cracking Furnace H-0900 (487.5 MMBtu/hr maximum)	NO _x (7) (10)	48.75	-
		NO _x (7)	12.19	21.35
		SO ₂ (7)	5.60	24.53

Emission Sources - Maximum Allowable Emission Rates

		CO (7) (11)	34.13	-
		CO (7)	17.06	74.73
		PM (7)	3.63	15.91
		PM ₁₀ (7)	3.63	15.91
		PM _{2.5} (7)	3.63	15.91
		VOC (7)	2.63	11.51
		NH ₃	1.98	8.68
N-16	Fresh Feed Cracking Furnace H-1000 (498 MMBtu/hr maximum)	NO _x (7) (10)	49.80	-
		NO _x (7)	12.45	21.81
		SO ₂ (7)	4.48	8.72
		CO (7) (11)	69.72	-
		CO (7)	17.43	76.34
		PM (7)	2.49	10.91
		PM ₁₀ (7)	2.49	10.91
		PM _{2.5} (7)	2.49	10.91
		VOC (7)	2.69	11.76
		NH ₃	1.98	8.68
N-10	Catalyst Regeneration Effluent	VOC (7)	15.83	0.08
		CO	373.33	1.89
N-11	Reactor Regeneration Effluent (Startup, Shutdown, and Maintenance)	CO	161.43	135.57
		VOC (7)	0.13	0.11
N-12	DP Reactor Feed Heater	NO _x (7)	5.01	13.71
		SO ₂ (7)	0.44	0.95
		CO (7)	4.40	12.26
		PM (7)	0.38	1.64
		PM ₁₀ (7)	0.38	1.64
		PM _{2.5} (7)	0.38	1.64
		VOC (7)	0.17	0.74
	DP Reactor Feed Heater Startup Emission Rate	CO (7)	14.50	1.74
N-13	DP Reactor Regeneration Heater	NO _x (7)	1.73	1.42

Emission Sources - Maximum Allowable Emission Rates

		SO ₂ (7)	0.14	0.10
		CO (7)	2.37	3.13
		PM (7)	0.13	0.17
		PM ₁₀ (7)	0.13	0.17
		PM _{2.5} (7)	0.13	0.17
		VOC (7)	0.06	0.08
N-14	Auxiliary Boiler	NO _x	13.60	-
		SO ₂	1.24	-
		CO	15.60	-
		PM	1.58	-
		PM ₁₀	1.58	-
		PM _{2.5}	1.58	-
		VOC	1.58	-

Emission Sources - Maximum Allowable Emission Rates

N-20A	GTG HRSG Unit 1 GE Frame 6B, 310.4 MMBtu/hr Duct Burner (with SCR)	NO _x	17.65	-
		SO ₂	4.53	-
		CO	89.51	-
		PM	5.55	-
		PM ₁₀	5.55	-
		PM _{2.5}	5.55	-
		VOC	4.09	-
		NH ₃	7.61	28.20
N-20B	GTG HRSG Unit 2 GE Frame 6B, 310.4 MMBtu/hr Duct Burner (with SCR)	NO _x	17.65	-
		SO ₂	4.53	-
		CO	89.51	-
		PM	5.55	-
		PM ₁₀	5.55	-
		PM _{2.5}	5.55	-
		VOC	4.09	-
		NH ₃	7.61	28.20
Emission Point Nos. N-14, N-20A, and N-20B are subject to the following combined annual emission caps for the specified pollutants:				
N-14, N-20A, and N-20B	Annual Emission Caps	NO _x	-	102.96
		SO ₂	-	8.27
		CO	-	349.85
		PM	-	46.78
		PM ₁₀	-	46.78
		PM _{2.5}	-	46.78
		VOC	-	32.17
N-18	Decoking Drum	CO (7)	3,360.00	204.09
		PM (7)	78.73	3.98
		PM ₁₀ (7)	78.73	3.98
		PM _{2.5} (7)	78.73	3.98
N-19	Thermal Oxidizer	NO _x (7)	0.24	0.89

Emission Sources - Maximum Allowable Emission Rates

		SO ₂ (7)	0.08	0.28
		CO (7)	0.21	0.78
		PM (7)	0.04	0.13
		PM ₁₀ (7)	0.04	0.13
		PM _{2.5} (7)	0.04	0.13
		VOC (7)	0.03	0.14
N-15 and N-15A	Flare System Emission Limits Applicable During Routine Operations exclusive of planned turnarounds	NO _x (7)	252.70	45.57
		CO (7)	1,046.49	176.01
		SO ₂ (7)	0.56	1.32
		H ₂ S	<0.01	<0.01
		VOC (7)	631.15	170.37
	Flare System Emission Limits Applicable to MSS Activities, Including Planned Major and Minor Plant Turnarounds	NO _x (7)	1,068.91	35.83
		CO (7)	5,276.94	174.20
		SO ₂ (7)	17.12	1.46
		H ₂ S	0.19	0.02
		VOC (7)	6,788.14	169.10
	Acetylene Converter Swaps	NO _x (7) (15)	364.76	-
		CO (7) (15)	2,634.43	-
		VOC (7) (15)	2,778.73	-
	Flare System Emission Limits Applicable to all operations	VOC	-	241.07

Emission Sources - Maximum Allowable Emission Rates

N-21A	Fire Pump Diesel Engine (6)	NO _x (7)	15.81	1.23
		SO ₂ (7)	1.05	0.08
		CO (7)	3.41	0.27
		PM (7)	1.12	0.09
		PM ₁₀ (7)	1.12	0.09
		PM _{2.5} (7)	1.12	0.09
		VOC (7)	1.26	0.10
N-21B	Fire Pump Diesel Engine (6)	NO _x (7)	15.81	1.23
		SO ₂ (7)	1.05	0.08
		CO (7)	3.41	0.27
		PM (7)	1.12	0.09
		PM ₁₀ (7)	1.12	0.09
		PM _{2.5} (7)	1.12	0.09
		VOC (7)	1.26	0.10
N-22	Carbon Bed Adsorber	VOC (5)	0.03	<0.01
		Benzene	0.03	<0.01
N-23	Ammonia Scrubber	NH ₃	0.12	0.51

Emission Sources - Maximum Allowable Emission Rates

N-24A	Boiler B-7280 (425.4 MMBtu/hr)	VOC (7)	1.70	6.66
		NO _x (Routine)	4.25	16.64
		NO _x (Startup)(17)	17.02	1.23
		CO (7)	14.89	18.31
		SO ₂	7.91	16.67
		PM (7)	2.13	8.32
		PM ₁₀ (7)	2.13	8.32
		PM _{2.5} (7)	2.13	8.32
		NH ₃	1.87	7.33
N-24B	Boiler B-7290 (425.4 MMBtu/hr)	VOC (7)	1.70	6.66
		NO _x (Routine)	4.25	16.64
		NO _x (Startup) (17)	17.02	1.23
		CO (7)	14.89	18.31
		SO ₂	7.91	16.67
		PM(7)	2.13	8.32
		PM ₁₀ (7)	2.13	8.32
		PM _{2.5} (7)	2.13	8.32
		NH ₃	1.87	7.33
N-24A and N-24B	Annual Cap - Boilers B-7280 and B-7290	SO ₂	-	23.42
N-1 through N-9, N-14, N-15, N-15A, N-16, N-19, N-20A, and N-20B	Fresh Feed Cracking Furnaces, Auxiliary Boiler, Flare System, Cogeneration Facility, and Thermal Oxidizer (9)	Mercury (9)	0.63	0.04
TK-2501	IFR Spent Caustic	VOC (7)	0.31	(16)
TK-2501B	Tank TK-2501B	VOC	0.41	(16)
TK-2501/TK-2501B Annual Cap	Spent Caustic Tank Cap	VOC	-	0.44
TK-8001	IFR WW Equalization	VOC (7)	0.39	0.62
TK-8101	EFR Contaminated Storm water	VOC (7)	0.51	0.47
TK-7702	Sulfuric Acid Tank	H ₂ SO ₄	0.01	0.01
		SO ₃	0.01	0.01

Emission Sources - Maximum Allowable Emission Rates

TK1701	Tank TK1701	VOC	4.58	0.01
TK1702	Tank TK1702	VOC	1.65	0.01
TK1703	Tank TK1703	VOC	1.12	0.01
TK1704	Tank TK1704	VOC	1.55	0.01
TK-CWT	Water Treatment Chemicals Storage	VOC	0.75	0.01
F-1	Fugitives (12)	VOC (7)	11.96	52.41
F-2 and F-2A	Cooling Tower System	PM(7)	1.19	4.60
		PM ₁₀ (7)	0.88	3.41
		PM _{2.5} (7)	0<0.01	0.01
		VOC (5) (7)	23.53	42.45
		Benzene	0.46	1.77
F-4	Benzene/Toluene Process Fugitives (12)	VOC (7)	0.71	3.12
		H ₂ S	0.01	0.02
F-5	C4 Huntsman Pipeline Fugitives (12)	VOC	0.01	0.05
FUG-AMM	Ammonia Fugitives	NH ₃	0.05	0.20
AH-98002	Analyzer Vent	VOC	< 0.01	< 0.01
		SO ₂	< 0.01	< 0.01
AH-009A	Analyzer Vent	VOC	< 0.01	< 0.01
AH-009B	Analyzer Vent	VOC	< 0.01	< 0.01
AH-007	Analyzer Vent	VOC	< 0.01	< 0.01
PLANNED TURNAROUND AND MSS CAPS				
TA CAP	Turnaround CAP (Non-Flare)	VOC	16.03	4.61
		PM	0.30	1.03
		PM ₁₀	0.02	0.06
		PM _{2.5}	<0.01	0.01
MSS Cap	MSS CAP (Non-Flare)	VOC	19.12	4.76
		PM	0.74	1.02
		PM ₁₀	0.24	0.06
		PM _{2.5}	0.03	0.01
N-1	Recycle Ethane Cracking Furnace H-0100 Startup	NO _x	48.32	(13)

Emission Sources - Maximum Allowable Emission Rates

		CO	93.02	(13)
N-2	Fresh Feed Cracking Furnace H-0200 Startup	NO _x	70.68	(13)
		CO	136.04	(13)
N-3	Fresh Feed Cracking Furnace H-0300 Startup	NO _x	70.68	(13)
		CO	136.04	(13)
N-4	Fresh Feed Cracking Furnace H-0400 Startup	NO _x	70.68	(13)
		CO	136.04	(13)
N-5	Fresh Feed Cracking Furnace H-0500 Startup	NO _x	70.68	(13)
		CO	136.04	(13)
N-6	Fresh Feed Cracking Furnace H-0600 Startup	NO _x	70.68	(13)
		CO	136.04	(13)
N-7	Fresh Feed Cracking H-0700 Startup	NO _x	70.68	(13)
		CO	136.04	(13)
N-8	Fresh Feed Cracking H-0800 Startup	NO _x	70.68	(13)
		CO	136.04	(13)
N-9	Fresh Feed Cracking H-0900 Startup	NO _x	48.75	(13)
		CO	34.13	(13)
N-16	Fresh Feed Cracking H-1000 Startup	NO _x	49.80	(13)
		CO	69.72	(13)
N-12	DP Reactor Feed Heater Startup	NO _x	15.02	(13)
		CO	14.52	(13)
N-13	DP Reactor Regeneration Heater	NO _x	3.45	(13)
		CO	4.74	(13)
N-14	Auxiliary Boiler Startup	NO _x	27.12	(13)
		CO	31.19	(13)
N-20A	GTG HRSG Unit 1 Startup	NO _x	123.53	(13)
		CO	716.12	(13)
N-20B	GTG HRSG Unit 2 Startup	NO _x	123.53	(13)
		CO	716.12	(13)

Emission Sources - Maximum Allowable Emission Rates

N-24A	Boiler B-7280 Startup	NO _x	17.02	(13)
		CO	29.78	(13)
N-24B	Boiler B-7290 Startup	NO _x	17.02	(13)
		CO	29.78	(13)
GTGENG-1	Cogen Starting Engine Unit #20A (14)	VOC	0.01	0.01
		NO _x	16.48	0.79
		CO	5.17	0.25
		SO ₂	0.01	0.01
		PM	0.71	0.03
		PM ₁₀	0.71	0.03
		PM _{2.5}	0.71	0.03
GTGENG-2	Cogen Starting Engine Unit #20B (14)	VOC	0.01	0.01
		NO _x	16.48	0.79
		CO	5.17	0.25
		SO ₂	0.01	0.01
		PM	0.71	0.03
		PM ₁₀	0.71	0.03
		PM _{2.5}	0.71	0.03

Emission Sources - Maximum Allowable Emission Rates

- (1) Emission point identification - either specific equipment designation or EPN from plot plan.
- (2) Specific point source name. For fugitive sources, use area name or fugitive source name.
- (3) VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
CO - carbon monoxide
NO_x - total oxides of nitrogen
SO₂ - sulfur dioxide
SO₃ - sulfur trioxide
PM - total particulate matter (PM), suspended in the atmosphere, including PM₁₀ and PM_{2.5}, as represented
PM₁₀ - total PM equal to or less than 10 microns in diameter, including PM_{2.5}, as represented
PM_{2.5} - PM equal to or less than 2.5 microns in diameter
H₂S - hydrogen sulfide
H₂SO₄ - sulfuric acid
NH₃ - ammonia
- (4) Compliance with annual emission limits (tons per year) is based on a 12-month rolling period.
- (5) The VOC emission rate is for total VOC, including benzene.
- (6) Emissions from the fire pump diesel engines are based on 156 hours per year operation. Non-emergency fire pump operations shall only occur between the hours of 8:00 a.m. and 5:00 p.m. (one engine at any one time.)
- (7) These emissions are permitted under PSD or Nonattainment review in addition to State.
- (9) Mercury shall be calculated and expressed as elemental mercury in any form or phase and shall include the mercury contained in any compound.
- (10) Emissions from startups and spikes in the short-term rate are authorized at this rate for up to 150 total hours in any 12-month period during which emissions from one or more furnaces (EPNs N-1 through N-8, N-9, and N-16) exceed the routine lbs/hr emission limit. Annual emissions are included in the rates of normal operations. These hours are included with the 1,400 hours per year authorized for hot-standby mode.
- (11) Emissions from startups and spikes in the short-term rate are authorized at this rate for up to 876 total hours in any 12-month period. Annual emissions are included in the rates of normal operations. These hours are included with the 1,400 hours per year authorized for hot-standby mode.
- (12) Emission rate is an estimate and compliance is demonstrated by meeting the requirements of the applicable special conditions and permit application representations.
- (13) Annual emission rates are included in each EPN's respective routine emission rates.
- (14) Each engine is authorized to operate for up to 96 total hours in any 12-month period.
- (15) Annual emissions are included in the Flare Systems' annual Emission Limits.
- (16) Annual emissions are included in the Caustic Tank Cap Annual Emission Limits.
- (17) Emissions from startups in the short-term rate are authorized at this rate for up to 144 hours per 12-month rolling period.

Date: May 8, 2020