Permit Numbers 45586 and PSD-TX-1055

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

AIR CONTAMINANTS DATA

Emission	Source	Air Contaminant	Emission Rates *	
Point No. (1)	Name (2)	Name (3)	lb/hr	TPY**
ESJ-1A	CFB Boiler	NO_x	185.54	812.60
	Normal Operations	CO	397.58	1741.38
		VOC	13.25	58.05
		PM/PM ₁₀	136.29	379.62
		SO_2	472.80	2070.86
		H_2SO_4	96.53	422.80
		HCI	2.03	8.87
		HF	0.27	1.18
		Pb	0.01	0.026
		Hg	0.01	0.007
		NH_3	16.47	36.08
ESJ-1A	CFB Boiler	NO_x	207.84	
	Start-Up	CO	397.58	
		VOC	13.25	
		PM/PM ₁₀	136.29	
		SO_2	2393.88	
		H_2SO_4	254.79	
		HCI	20.11	
		HF	2.68	
		Pb	0.01	
		Hg	0.01	
		NH_3	16.47	
ESJ-2A	Emergency Generator	NO _x	30.56	7.64
		CO	37.65	9.41
		VOC	4.43	1.11
		PM/PM ₁₀	1.77	0.44
		SO_2	0.04	0.01

AIR CONTAMINANTS DATA

Emission	Source	Air Contaminant	Emission Rates *	
Point No. (1)	Name (2)	Name (3)	lb/hr	TPY**
ESJ-3A	Diesel Fire Pump Engine	NO_x CO VOC PM/PM_{10} SO_2	2.31 2.85 0.33 0.13 0.003	0.58 0.71 0.08 0.03 0.001
ESJ-4A	Auxiliary Boiler	NO_x CO VOC PM/PM_{10} SO_2	2.32 5.30 0.36 0.46 0.04	0.93 2.12 0.14 0.19 0.02
ESJ-5A	Acid Tank	H_2SO_4	<0.01	<0.01
ESJ-6A	Caustic Tank	NaOH	<0.01	<0.01
ESJ-7A	Fly Ash Silo	PM ₁₀	0.34	1.50
ESJ-8A	Bottom Ash Silo	PM ₁₀	0.17	0.75
ESJ-9A	Coke Silo	PM ₁₀	0.34	1.50
ESJ-10A	Limestone Silo	PM ₁₀	0.34	1.50
ESJ-11A	Sand Silo	PM ₁₀	0.17	0.27
ESJ-12A	Bottom Ash Transfer Hopper	PM ₁₀	0.17	0.75
PCPREPST	Petcoke Preparation Building Stack	PM ₁₀	0.60	2.63
PC-FUG	Petcoke Preparation Building (4)	PM/PM ₁₀	0.05	0.05

AIR CONTAMINANTS DATA

Emission	Source	Air Contaminant	Emission Rates *	
Point No. (1)	Name (2)	Name (3)	lb/hr	TPY**
CO-31	Conveyor CO-31 (4)	PM/PM ₁₀	0.07	0.07
TR-30	CO-31 to CO-32 (4)	PM/PM ₁₀	0.03	0.03
CO-32	Conveyor CO-32 (4)	PM/PM ₁₀	0.03	0.03
TR-31	CO-32 to Coke Silo (4)	PM/PM ₁₀	0.03	0.03
LSPREPST	Limestone Preparation Building Stack	PM ₁₀	0.60	2.63
LS-FUG	Limestone Preparation Building (4)	PM PM ₁₀	0.13 0.06	0.09 0.05
CO-35	Conveyor 35 (4)	PM PM ₁₀	0.004 0.002	0.003 0.002
TR-32	CO-35 to CO-36 (4)	PM PM ₁₀	0.002 0.001	0.002 0.001
CO-36	Conveyor 36 (4)	PM PM ₁₀	0.002 0.001	0.002 0.001
TR-33	CO-36 to Limestone Silo (4)	PM PM ₁₀	0.002 0.001	0.002 0.001
FUG-AMM	Ammonia Fugitives (4)	NH₃	0.05	0.21

⁽¹⁾ Emission point identification - either specific equipment designation or emission point number from a plot plan.

⁽²⁾ Specific point source names. For fugitive sources, use an area name or fugitive source name.

⁽³⁾ NO_x - total oxides of nitrogen

	CO VOC PM PM ₁₀	-	carbon monoxide volatile organic compounds as defined in Title 30 Texas Administrative Code ' 101.1 particulate matter, suspended in the atmosphere, including PM_{10} particulate matter equal to or less than 10 microns in diameter. Where PM is not listed, it shall be assumed that no PM greater than 10 microns is emitted.
	SO_2	-	sulfur dioxide
	H_2SO_4	-	sulfuric acid
	HCI	-	hydrogen chloride
	HF	-	hydrogen fluoride
	Pb	-	lead
	Hg	-	mercury
	-		ammonia
			sodium hydroxide
(4)	Fugitive emission		missions are an estimate only and should not be considered as a maximum allowable ate.
*	Emission schedu		rates are based on and the facilities are limited by the following maximum operating
**	Compli	and	e with annual emission limits is based on a rolling 12-month period.
	Н	Irs/o	day Days/week Weeks/year or 8.760 Hrs/year

Dated April 29, 2009