

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Permit Number 8136A

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

Emission Point No. (1)	Source Name (2)	AIR CONTAMINANTS DATA		
		Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY
1	Baghouse Stack	PM	13.20	8.23
		PM ₁₀	9.20	5.73
		VOC(a)	12.80	7.98
		VOC(b)	420.00	79.92
		NO _x	22.00	13.71
		SO ₂	23.20	14.46
		CO	52.00	32.41
4	Asphalt Heater Vent (4)	PM ₁₀	0.05	0.22
		VOC	<0.01	0.02
		NO _x	0.30	1.31
		SO ₂	1.28	5.60
		CO	0.02	0.08
5	Storage Silo Filling (4)	PM	0.23	0.15
		VOC	4.87	3.04
		CO	0.47	0.29
6	Truck Load-Out	PM	0.42	0.13
		VOC	3.13	0.97
		CO	1.08	0.34
3A	Aggregate Stockpiles (4)	PM		2.89
		PM ₁₀		1.38
3B	Cold Mix Stockpiles (4)	VOC(b)	2.73	7.98
2	Material Handling (4)	PM	1.51	0.91
		PM ₁₀	0.71	0.43

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

- (1) Emission point identification - either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources use area name or fugitive source name.
- (3) PM - particulate matter, suspended in the atmosphere, including PM₁₀
PM₁₀ - particulate matter equal to or less than 10 microns in diameter. Where PM is not listed, it shall be assumed that no particulate matter greater than 10 microns is emitted.
VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
VOC(a) - asphalt vapors from standard mix and fuel combustion vapors
VOC(b) - diesel or kerosene vapors from cold mix, asphalt vapors, and fuel combustion vapors
NO_x - total oxides of nitrogen
SO₂ - sulfur dioxide
CO - carbon monoxide
- (4) Fugitive emissions are an estimate only.

* Emission rates are based on and the facilities are limited by the following maximum operating schedule and production rates:

24 Hrs/day 7 Days/week 52 Weeks/year or 8,760 Hrs/year

Standard Hot Mix: Tons/hour 400 Tons/year 380,000

Cold Mix Asphalt Concrete production and storage are limited as outlined in Special Condition 6.H. and 6.I.

Dated April 26, 2006