

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Permit Number 49737

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	<u>Emission Rates *</u>	
			<u>lb/hr</u>	<u>TPY</u>
10	Drum Dryer Baghouse Stack	PM	13.20	7.26
		PM ₁₀	9.20	5.06
		VOC(a)	12.80	6.40
		VOC(b)	175.00	4.38
		VOC(c)	73.45	3.39
		NO _x	22.00	12.10
		SO ₂	23.20	12.76
		CO	52.00	28.60
6	Lime Silo Baghouse Stack	PM ₁₀	0.05	0.03
11	Asphalt Storage Tank	VOC	0.01	0.01
12	Hot Oil Heater Vent (4)	PM ₁₀	0.08	0.19
		VOC	<0.01	0.01
		NO _x	0.20	0.45
		SO ₂	0.46	1.01
		CO	0.05	0.11
13	Fuel Oil Storage Tank (4)	VOC	<0.01	<0.01
14	Diesel Storage Tank (4)	VOC	0.01	0.01
17	Storage Silo Filling (4)	PM ₁₀	0.17	0.09
		VOC	1.14	0.62
		CO	0.39	0.22
18	Truck Load-Out (4)	PM ₁₀	0.14	0.09
		VOC	0.88	0.55
		CO	0.30	0.19

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	<u>Emission Rates *</u>	
			lb/hr	TPY
Fug	Aggregate Stockpiles (4)	PM	----	1.10
		PM ₁₀	----	0.52
Fug	Cold Mix Stockpiles (4)	VOC	2.10	4.38
Fug	Material Handling (4)	PM	1.92	0.96
		PM ₁₀	0.91	0.46
23	RAP Crusher (4)	PM	0.14	0.08
		PM ₁₀ 0.07	0.04	
24	RAP Screen (4)	PM	0.21	0.12
		PM ₁₀	0.10	0.06
Fug	RAP Handling (4)	PM	0.02	0.01
		PM ₁₀	0.01	<0.01

(1) Emission point identification - either specific equipment designation or emission point number from plot plan.

(2) Specific point source name. For fugitive sources use area name or fugitive source name.

(3) PM - particulate matter, suspended in the atmosphere, including PM₁₀

PM₁₀ - particulate matter equal to or less than less than 10 microns in diameter. Where PM is not listed, it shall be assumed that no PM greater than 10 microns is emitted.

VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1

VOC(a) - for standard hot mix asphalt

VOC(b) - emulsified cold mix asphalt

VOC(c) - additional VOC due to the use of rubber modified hot mix asphalt

NO_x - total oxides of nitrogen

SO₂ - sulfur dioxide

CO - carbon monoxide

(4) Fugitive emissions are an estimate only.

Permit Number 49737
Page 3

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

- * Emission rates are based on and the facilities are limited by the following maximum operating schedule and production rates:

24 Hrs/day 7 Days/week 52 Weeks/year or _____Hrs/year

Standard Hot Mix: 400 tons/hour; 400,000 tons/year

Emulsified Cold Mix: 200 tons/hour; 10,000 tons/year

\ Rubber Modified Mix: 400 tons/hour; 30,000 tons/year

Dated _____