

Emission Sources - Maximum Allowable Emission Rates

Permit Number 108113 and PSDTX1344

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities, sources, and related activities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

Air Contaminants Data

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates (6)	
			lbs/hour	TPY (4)
1	Dock Ore Unloading and Product Loading Gantry Crane (5)	PM	0.28	1.22
		PM ₁₀	0.13	0.58
		PM _{2.5}	0.02	0.09
4	Oxide Unloading Bin and Dedusting Fabric Filter Stack	PM	0.11	0.49
		PM ₁₀	0.11	0.49
		PM _{2.5}	0.08	0.36
5	Oxide Pellet Pile Transfer and Dedusting (Pre-Enclosed Storage) Fabric Filter Stack	PM	0.25	1.10
		PM ₁₀	0.25	1.10
		PM _{2.5}	0.19	0.83
6	Oxide Transfer and Dedusting (Post-Enclosed Storage) Fabric Filter Stack	PM	0.11	0.49
		PM ₁₀	0.11	0.49
		PM _{2.5}	0.08	0.36
7	Oxide and Remet Screening and Dedusting Fabric Filter Stack	PM	0.71	3.09
		PM ₁₀	0.71	3.09
		PM _{2.5}	0.53	2.32
16	Furnace Charge Hopper Loading Silos Fabric Filter Stack	PM	0.01	<0.01
		PM ₁₀	0.01	<0.01
		PM _{2.5}	0.01	<0.01
17	Charge Hopper Fabric Filter Stack	PM	0.10	0.44
		PM ₁₀	0.10	0.44

Emission Sources - Maximum Allowable Emission Rates

		PM _{2.5}	0.08	0.33
		NO _x	2.02	8.84
		SO ₂	0.24	1.05
		CO	2.82	12.36
		VOC	0.18	0.81
29	Reformer Main Flue Ejector Stack	PM	8.06	35.30
		PM ₁₀	8.06	35.30
		PM _{2.5}	8.06	35.30
		NO _x	88.64	388.25
		SO ₂	10.51	32.20
		CO	123.97	542.98
		VOC	8.12	35.55
		n-Hexane	0.41	1.81
8	Furnace Dedusting (BSG Dust Collection) Wet Scrubber Stack	PM	2.50	10.95
		PM ₁₀	2.50	10.95
		PM _{2.5}	1.25	5.48
		NO _x	2.02	8.84
		SO ₂	0.24	1.05
		CO	2.82	12.36
		VOC	0.18	0.81
38	Hot Pressure Relief Vent (Flare)	PM	0.51	0.08
		PM ₁₀	0.51	0.08
		PM _{2.5}	0.51	0.08
		NO _x	20.26	2.96
		SO ₂	0.02	<0.01

Emission Sources - Maximum Allowable Emission Rates

		CO	248.93	33.02
		VOC	0.04	0.02
		Pb	<0.01	<0.01
9	Briquetter Dedusting Scrubber Stack	PM	3.97	17.38
		PM ₁₀	3.97	17.38
		PM _{2.5}	1.98	8.69
		NO _x	1.01	4.42
		SO ₂	0.12	0.52
		CO	1.41	6.18
		VOC	0.09	0.40
11A	HBI Cooling Conveyer 1 Scrubber Stack	PM	1.90	8.34
		PM ₁₀	1.90	8.34
		PM _{2.5}	0.95	4.17
11B	HBI Cooling Conveyer 2 Scrubber Stack	PM	1.90	8.34
		PM ₁₀	1.90	8.34
		PM _{2.5}	0.95	4.17
12	Transfer & Product Screening Station No. 1 (Pre Pile) Fabric Filter Stack	PM	0.40	1.77
		PM ₁₀	0.40	1.77
		PM _{2.5}	0.36	1.59
13	Transfer & Product Screening Station No. 2 (Post Pile) Fabric Filter Stack	PM	0.40	1.77
		PM ₁₀	0.40	1.77
		PM _{2.5}	0.36	1.59
14	HBI Pile (5)	PM	0.32	1.39
		PM ₁₀	0.13	0.56
		PM _{2.5}	0.04	0.16

Emission Sources - Maximum Allowable Emission Rates

36	Remet/Fines Storage (5)	PM	0.17	0.74
		PM ₁₀	0.04	0.20
		PM _{2.5}	0.01	0.02
30	Process Water Degasser (5)	CO	24.26	106.24
33	Salt Water Cooling Tower (5)	PM	2.61	11.44
		PM ₁₀	0.08	0.34
		PM _{2.5}	0.08	0.34
39	Paved Road Fugitive Dust (5)	PM	-	1.08
		PM ₁₀	-	0.21
		PM _{2.5}	-	0.03
34	Emergency Generator	PM	0.47	0.02
		PM ₁₀	0.47	0.02
		PM _{2.5}	0.47	0.02
		NO _x	32.09	1.60
		SO ₂	0.04	<0.01
		CO	3.80	0.19
		VOC	0.99	0.05
35	Fire Pump	PM	0.03	<0.01
		PM ₁₀	0.03	<0.01
		PM _{2.5}	0.03	<0.01
		NO _x	2.25	0.11
		SO ₂	<0.01	<0.01
		CO	0.27	0.01
		VOC	0.07	<0.01
ALL	All Sources	All HAPS	-	2.05

Emission Sources - Maximum Allowable Emission Rates

- (1) Emission point identification - either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources, use area name or fugitive source name.
- (3)

VOC	- volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
NO _x	- total oxides of nitrogen
SO ₂	- sulfur dioxide
PM	- total particulate matter, suspended in the atmosphere, including PM ₁₀ and PM _{2.5} , as represented
PM ₁₀	- total particulate matter equal to or less than 10 microns in diameter, including PM _{2.5} , as represented
PM _{2.5}	- particulate matter equal to or less than 2.5 microns in diameter
CO	- carbon monoxide
n-Hexane	- n-Hexane
Pb	lead
HAP	- hazardous air pollutant as listed in § 112(b) of the Federal Clean Air Act or Title 40 Code of Federal Regulations Part 63, Subpart C
- (4) Compliance with annual emission limits (tons per year) is based on a 12 month rolling period.
- (5) Emission rate is an estimate and is enforceable through compliance with the applicable special condition(s) and permit application representations.
- (6) Planned startup and shutdown emissions are included. Maintenance activities are not authorized by this permit and will need separate authorization unless the activity can meet the conditions of 30 TAC 116.119

Date: March 18, 2014