

## Emission Sources – Maximum Allowable Emission Rates

Permit Number 21918

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities, sources, and related activities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

### Air Contaminants Data

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
Compliance Caps	Emission Caps	VOC	(5)	389.14
		Group A VOC Cap (6)	154.30	(7)
		Group B VOC Cap (8)	27.90	(7)
		Group C VOC Cap (9)	36.60	(7)
		Group D VOC Cap (10)	0.81	(7)
		Ethyl Mercaptan (11)	5.34	(7)
		Isopropyl Mercaptan (11)	3.64	(7)
		n-Propyl Mercaptan (11)	3.52	(7)
		n-Butyl Mercaptan (11)	2.55	(7)
		t-Butyl Mercaptan (11)	3.02	(7)
		s-Butyl Mercaptan (11)	3.23	(7)
		Benzyl Mercaptan (11)	0.42	(7)
		1,2-Ethanedithiol (11)	0.74	(7)
		Dimethyl Sulfide (11)	2.80	(7)
		Methyl Ethyl Sulfide (11)	2.55	(7)
		Acetone (12)	1.81	(7)
F-M2A	Sulfolene Handling	SO <sub>2</sub>	4.88	10.88
		VOC	2.99	6.67
F-M2A-MSS	Sulfolene - MSS (13)	SO <sub>2</sub>	1.31	0.01
		VOC	0.81	0.01

### Cooling Towers

Project Number: 173357

## Emission Sources - Maximum Allowable Emission Rates

F-CT1	Main Cooling Tower	VOC	0.84	3.68
		H <sub>2</sub> S	0.84	3.68
F-CT2	Unit 5 Cooling Tower	VOC	0.13	0.55
Flares				
FL-1	North (H <sub>2</sub> S) Flare	VOC	8.74	28.42
		H <sub>2</sub> S	4.14	5.33
		NO <sub>x</sub>	2.87	4.26
		SO <sub>2</sub>	398.04	513.17
		CO	27.03	36.55
FL-2	South Flare (Hydrocarbon)	VOC	52.86	44.25
		H <sub>2</sub> S	0.80	0.19
		NO <sub>x</sub>	3.26	3.46
		SO <sub>2</sub>	75.18	17.70
		CO	16.63	31.32
FL-1/FL-2	Flare Subcap	VOC	60.87	70.28
		H <sub>2</sub> S	4.80	5.10
		NO <sub>x</sub>	5.50	7.71
		SO <sub>2</sub>	449.12	480.19
		CO	15.07	59.58
Fugitives				
F-SP4	Fugitive Emissions (14)	VOC	2.67	11.70
		H <sub>2</sub> S	0.05	0.23
F-C1	CPU Soltrol Fugitives (14)	VOC	2.10	9.20
F-C10	CPU Col 10 Fugitives (14)	VOC	0.06	0.27
		H <sub>2</sub> S	0.04	0.16
F-C11	CPU Col 11 Fugitives (14)	VOC	0.09	0.40
		H <sub>2</sub> S	0.06	0.24
F-C12	CPU Col 12 Fugitives (14)	VOC	0.01	0.05
F-C2	CPU H <sub>2</sub> S Purification (14)	VOC	0.01	0.05
		H <sub>2</sub> S	0.50	2.20

## Emission Sources - Maximum Allowable Emission Rates

F-C3	CPU No. 2UV Fugitives (14)	VOC	0.10	0.46
		H <sub>2</sub> S	0.11	0.47
F-C4	CPU No. 2 Filtrol Fugitives (14)	VOC	0.57	2.51
		H <sub>2</sub> S	0.15	0.67
F-C5	CPU No. 1 Filtrol Fugitives (14)	VOC	0.41	1.78
		H <sub>2</sub> S	0.08	0.36
F-C6	CPU IC3SH (14)	VOC	0.03	0.11
		H <sub>2</sub> S	0.02	0.10
F-C8	CPU No. 1 UV Fugitives (14)	VOC	0.05	0.21
		H <sub>2</sub> S	0.15	0.67
F-C9	CPU Col 3 & 4 Fugitives (14)	VOC	0.05	0.23
		H <sub>2</sub> S	0.02	0.08
F-M2	MPU Sulfolane Fugitives (14)	VOC	4.90	21.48
		H <sub>2</sub> S	0.39	1.72
F-M5	MPU R-17 Fugitives (14)	VOC	0.63	2.75
		H <sub>2</sub> S	0.02	0.09
F-M8	Unit 5.1 Fugitives (14)	VOC	4.55	19.92
F-M9	MPU Unit 5.2 Fugitives (14)	VOC	10.59	46.37
F-S1	SU R2 Fugitives (14)	VOC	0.67	2.92
F-S3	SU R1 Fugitives (14)	VOC	0.68	2.99
F-SP1	Shipping/Blending Fugitives (14)	VOC	4.09	17.92
F-SP2	Blending Fugitives (14)	VOC	5.70	24.98
F-U45	MeSH Fugitives (14)	VOC	0.51	2.19
		H <sub>2</sub> S	0.29	1.25
Wastewater				
FWW1	WW Sump East of Services Building	VOC	0.36	1.58
FWW2	WW Secondary Waste Sump	VOC	0.24	1.04
FWW3	WW Final Separator	VOC	2.53	11.08
FWW4	WW Philtex	VOC	0.16	0.67

## Emission Sources - Maximum Allowable Emission Rates

	Stormwater Pond			
FWW6	WW Unit 5 Oil/Water Separator	VOC	1.17	5.12
FWW7	WW Drains & Trenches	VOC	0.56	2.44
FWW10	WW Pace's Pit	VOC	0.14	0.63
<b>Heaters</b>				
H-1	MPU Dutch Oven	VOC	0.01	0.02
		NO <sub>x</sub>	0.10	0.43
		SO <sub>2</sub>	0.03	0.01
		CO	0.08	0.36
		PM	0.01	0.03
H-2	CPU Dutch Oven	VOC	0.01	0.02
		NO <sub>x</sub>	0.10	0.43
		SO <sub>2</sub>	0.03	0.01
		CO	0.08	0.36
		PM	0.01	0.03
H-3	CPU East Downtherm Furnace	VOC	0.15	0.65
		NO <sub>x</sub>	2.70	11.81
		SO <sub>2</sub>	0.75	0.38
		CO	2.26	9.92
		PM	0.20	0.90

**Vents**

M2A1	Sulfolene Flaker Scrubber RTO	VOC	0.01	0.04
		NO <sub>x</sub>	1.02	4.26
		SO <sub>2</sub>	0.04	0.17
		CO	0.05	0.19
		PM	0.01	0.05
M2C	Sulfolane Heavy Column Vent	VOC	0.01	0.01
M2D	Sulfolane Sludge	VOC	0.01	0.01

## Emission Sources - Maximum Allowable Emission Rates

	Tank Vent			
M2E	Sulfolane Sludge Filter	VOC	0.01	0.01
C2A	CPU H2S Vent Stack	VOC	0.04	0.15
		H <sub>2</sub> S	4.44	19.46
C2B	CPU Soltrol Coolant	VOC	0.03	0.12
		H <sub>2</sub> S	1.00	4.40
S3A	SU R-1 Oxygen Analyzer Vent	VOC	0.23	0.01
<b>Loading</b>				
SP1	Dock 2 Drum Loading Vent	VOC	35.03	3.86
SP2	Dock 2 Tank Vent	VOC	11.03	0.71
SP3	Mercaptan Dock Scrubber	VOC	0.33	0.93
SP4	Dock 1 Small Packaging	VOC	2.70	0.59
SP5A	Rail Loading	VOC	15.54	12.55
SP5B	Truck Loading	VOC	0.34	43.18
SP5C	Vapor Combustor	VOC	7.01	5.06
		NO <sub>x</sub>	3.42	0.05
		CO	6.85	0.09
		SO <sub>2</sub>	0.01	0.01
SP6B	Dock 1 Cylinder	VOC	9.69	1.94
TB-13	SO <sub>2</sub> Unloading Hose Vent	SO <sub>2</sub>	0.64	0.01
<b>Internal Floating Roof Tanks</b>				
TE-03	Tank Storage	VOC	0.35	2.01
TE-04	Tank Storage	VOC	0.35	2.01
TE-05	Tank Storage	VOC	0.35	2.01
TF-04	Tank Storage	VOC	0.33	2.26
TF-09	Tank Storage	VOC	0.33	2.26
TF-24	Tank Storage	VOC	0.35	2.01
TH-06	Tank Storage	VOC	0.24	1.88
TH-20	Tank Storage	VOC	0.21	2.00

Emission Sources - Maximum Allowable Emission Rates

<b>Atmospheric Tanks</b>				
TB-32	Storage Tank	VOC	1.31	0.07
TB-33	Storage Tank	VOC	1.09	0.04
TB-40	Storage Tank	VOC	0.58	0.08
TB-41	Storage Tank	VOC	0.56	0.08
TB-44	Storage Tank	VOC	0.59	0.04
TB-48	Storage Tank	VOC	0.65	0.13
TE-01	Tank Storage	VOC	18.59	4.40
TE-02	Tank Storage	VOC	18.59	4.40
TE-06	Tank Storage	VOC	18.59	4.40
TF-01	Tank Storage	VOC	0.73	0.45
TF-02	Tank Storage	VOC	0.73	6.01
TF-03	Tank Storage	VOC	0.73	3.30
TF-05	Tank Storage	VOC	0.45	0.13
TF-06	Tank Storage	VOC	0.73	0.23
TF-08	Tank Storage	VOC	0.73	0.66
TF-10	Tank Storage	VOC	0.73	0.24
TF-11	Tank Storage	VOC	5.24	0.76
TF-12	Tank Storage	VOC	0.72	0.60
TF-13	Tank Storage	VOC	0.73	0.23
TF-14	Tank Storage	VOC	0.73	0.14
TF-23	Tank Storage	VOC	7.85	1.45
TF-28	Tank Storage	VOC	1.17	0.06
TH-01	Tank Storage	VOC	1.11	0.33
TH-03	Tank Storage	VOC	1.11	0.33
TH-04	Tank Storage	VOC	0.33	1.10
TH-08	Tank Storage	VOC	1.04	0.64
TJ-36	Tank Storage	VOC	0.01	0.01
TJ-37	Tank Storage	VOC	0.01	0.01
TK-17	Tank Storage	VOC	0.75	0.04
TK-35	Tank Storage	VOC	0.65	0.12
TL-01	Tank Storage	VOC	0.73	0.05
TL-02	Tank Storage	VOC	0.73	0.09

Emission Sources - Maximum Allowable Emission Rates

TL-03	Tank Storage	VOC	1.11	0.28
T-95-4067/4069	Downtherm Holding	VOC	0.01	0.01

Emission Sources - Maximum Allowable Emission Rates

- (1) Emission point identification - either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources, use area name or fugitive source name.
- (3) VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1  
NO<sub>x</sub> - total oxides of nitrogen  
SO<sub>2</sub> - sulfur dioxide  
PM - total particulate matter, suspended in the atmosphere, including PM<sub>10</sub> and PM<sub>2.5</sub>, as represented  
CO - carbon monoxide  
H<sub>2</sub>S - hydrogen sulfide
- (4) Compliance with annual emission limits (tons per year) is based on a 12 month rolling period.
- (5) The VOC hourly caps are restricted on a pollutant by pollutant basis.
- (6) Total hourly emissions of any single compound listed on Approved Chemical List, Group A from the sources listed on Attachment C, Emission Caps List, are restricted to this emission rate.
- (7) Total VOC emissions from all sources listed on Attachment C, Emissions Caps List, are restricted to the annual value represented under the VOC cap.
- (8) Total hourly emissions of any single compound listed on Approved Chemical List, Group B from the sources listed on Attachment C, Emissions Cap List, are restricted to this emission rate.
- (9) Total hourly emissions of any single compound listed on Approved Chemical List, Group C from the sources listed on Attachment C, Emissions Cap List, are restricted to this emission rate.
- (10) Total hourly emissions of any single compound listed on Approved Chemical List, Group D from the sources listed on Attachment C, Emissions Cap List, are restricted to this emission rate.
- (11) Total hourly emissions of this compound from the sources listed on Attachment C, Emissions Caps List, are restricted to this emission rate.
- (12) Acetone is used as part of an automatic cleaning sequence for certain types of on-line analyzers employed in various locations throughout the facility.
- (13) This permit authorizes emissions which the company has represented for maintenance, startup, and shutdown activities associated with Sulfolene processing: Shutdown of Sulfolene unit. These shutdown events shall not exceed 12 events per rolling 12 months, or a total of 3 hours per year. A record shall be made of each shutdown event.
- (14) Emission rate is an estimate and compliance is demonstrated by meeting the requirements of the applicable special conditions and permit application representations.

Date: October 11, 2013