#### Permit Numbers 18999, PSDTX755M1, and N216

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities, sources, and related activities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

#### Air Contaminants Data

Emission Point No. (1)	Source Name (2)	Air Contaminant	Emission Rates	
Politi No. (1)		Name (3)	lbs/hour	TPY (4)
4061-JT	Gas Turbine 4061 MSS	NO <sub>x</sub>	70.00	2.16
		СО	30.00	0.72
		SO <sub>2</sub>	0.68	0.02
		PM (13)	1.32	0.05
		PM <sub>10</sub>	1.32	0.05
		PM <sub>2.5</sub>	0.94	0.03
		VOC	0.42	0.06
4062-JT	Gas Turbine 4062 MSS	NO <sub>x</sub>	70.00	2.16
		СО	30.00	0.72
		SO <sub>2</sub>	0.68	0.02
		PM (13)	1.32	0.05
		PM <sub>10</sub>	1.32	0.05
		PM <sub>2.5</sub>	0.94	0.03
		VOC	0.42	0.06
4063-JT	Gas Turbine 4063 MSS	NO <sub>x</sub>	70.00	2.16
		СО	30.00	0.72
		SO <sub>2</sub>	0.68	0.02
		PM (13)	1.32	0.05
		PM <sub>10</sub>	1.32	0.05
		PM <sub>2.5</sub>	0.94	0.03
		VOC	0.42	0.06

4064-JT	Gas Turbine 4064 MSS	NO <sub>x</sub>	70.00	2.16
		СО	30.00	0.72
		SO <sub>2</sub>	0.68	0.02
		PM (13)	1.32	0.05
		PM <sub>10</sub>	1.32	0.05
		PM <sub>2.5</sub>	0.94	0.03
		VOC	0.42	0.06
4065-JT	Gas Turbine 4065 MSS	NO <sub>x</sub>	87.50	2.70
		СО	37.50	0.90
		SO <sub>2</sub>	0.85	0.03
		PM (13)	1.65	0.06
		PM <sub>10</sub>	1.65	0.06
		PM <sub>2.5</sub>	1.65	0.06
		VOC	0.53	0.02
4061-JT	Gas Turbine 4061 Bypass Valve	NO <sub>x</sub>	0.23	0.87
		CO	0.10	0.29
		SO <sub>2</sub>	0.01	0.01
		PM	0.01	0.01
		PM <sub>10</sub>	0.01	0.01
		PM <sub>2.5</sub>	0.01	0.01
		VOC	1.52	0.01
		Ethylene	0.01	0.01
		Propylene	0.01	0.01
4062-JT	Gas Turbine 4062 Bypass Valve	NO <sub>x</sub>	0.23	0.87
		СО	0.10	0.29
		SO <sub>2</sub>	0.01	0.01
		PM	0.01	0.01
		PM <sub>10</sub>	0.01	0.01
		PM <sub>2.5</sub>	0.01	0.01
		VOC	1.52	0.01
		Ethylene	0.01	0.01

		Propylene	0.01	0.01
4063-JT	Gas Turbine 4063 Bypass Valve	NO <sub>x</sub>	0.23	0.87
		СО	0.10	0.29
		SO <sub>2</sub>	0.01	0.01
		PM	0.01	0.01
		$PM_{10}$	0.01	0.01
		PM <sub>2.5</sub>	0.01	0.01
		VOC	1.52	0.01
		Ethylene	0.01	0.01
		Propylene	0.01	0.01
4064-JT	Gas Turbine 4064 Bypass Valve	NO <sub>x</sub>	0.23	0.87
		СО	0.10	0.29
		SO <sub>2</sub>	0.01	0.01
		PM	0.01	0.01
		PM <sub>10</sub>	0.01	0.01
		PM <sub>2.5</sub>	0.01	0.01
		VOC	1.52	0.01
		Ethylene	0.01	0.01
		Propylene	0.01	0.01
4065-JT	Gas Turbine 4065 Bypass Valve	NO <sub>x</sub>	0.23	0.87
		CO	0.10	0.29
		SO <sub>2</sub>	0.01	0.01
		PM	0.01	0.02
		$PM_{10}$	0.01	0.02
		PM <sub>2.5</sub>	0.01	0.02
		VOC	<0.01	0.01
4026-U	Waste Heat Boiler/SCR1 Normal	NO <sub>x</sub>	44.04	107.16
	Operations	СО	53.61	143.51
		VOC (6)	10.77	32.80
		SO <sub>2</sub>	20.42	29.82
		PM (13)	16.68	58.17

		PM <sub>10</sub>	16.68	58.17
		PM <sub>2.5</sub>	16.68	58.17
		NH₃	18.08	55.45
		Ethylene	10.77	24.60
		Propylene	10.77	8.20
4026-U	Waste Heat Boiler/SCR1	NO <sub>x</sub>	73.40	-
	Maintenance, Startup, and Shutdown (MSS) Activities	СО	119.14	-
	Shataown (WSS) Activities	NH <sub>3</sub>	54.25	-
1-103B	Regenerator Heater	NO <sub>x</sub>	0.25	0.33
		СО	0.22	0.29
		VOC (6)	0.01	0.01
		SO <sub>2</sub>	0.04	0.05
		PM <sub>10</sub>	0.02	0.02
		PM <sub>2.5</sub>	0.02	0.02
		Ethylene	0.01	0.01
		Propylene	0.01	0.01
2205-1	Process Water Tanks	VOC	2.43	0.06
		Benzene	0.07	0.01
2205-2	Process Water Tanks	VOC	1.21	0.01
		Benzene	0.04	0.01
2300-1	Process Water Tanks	VOC	4.44	0.12
		Benzene	0.13	0.01
2300-2	Outfall Water Tanks	VOC	1.28	0.01
		Benzene	0.04	0.01
M-222	Storage Tank	VOC	0.10	0.16
		Butadiene	0.01	0.02
		Benzene	0.03	0.05
M-223	Storage Tank	VOC	0.15	0.16
		Butadiene	0.02	0.02
		Benzene	0.04	0.05
M-1002	Storage Tank	VOC	0.76	1.92

		Butadiene	0.24	0.61
		Benzene	0.46	1.15
T-136A	Storage Tank	VOC	1.89	0.08
T-136B	Storage Tank	VOC	1.21	0.04
4000-B	Charge Gas Heater/SCR2	NO <sub>x</sub>	3.70	13.25
		СО	17.83	18.92
		VOC (6)	0.69	2.84
		SO <sub>2</sub>	6.48	18.92
		PM (13)	1.24	3.22
		PM <sub>10</sub>	1.19	3.07
		$PM_{2.5}$	1.19	3.07
		NH₃	2.18	8.89
		Ethylene	0.49	2.0
		Propylene	0.12	0.50
4000-B	Charge Gas Heater/SCR2 MSS	$NO_x$	37.04	-
	Activities	NH₃	6.02	-
1-104BD	Auxiliary Boiler (227.5 MMBtu/hr, LHV)	NO <sub>x</sub> (8) (PSD)	30.24	105.96
		CO (PSD)	20.74	72.67
		VOC (6)	1.92	6.71
		SO <sub>2</sub>	1.26	4.42
		PM <sub>10</sub> (PSD)	2.10	7.36
		PM <sub>2.5</sub>	2.10	7.36
		Ethylene	1.35	4.73
		Propylene	0.24	0.83
1-105A	Main Flare Normal Operations	NO <sub>x</sub>	171.51	2.71
		CO	883.53	15.57
		VOC (12)	809.89	11.72
		SO <sub>2</sub>	46.41	0.07
		H₂S	0.50	0.01
		Ethylene	84.03	1.54
		Propylene	419.90	6.22

DC-TANK	Fuel Tank	VOC	0.06	0.01
		PM <sub>10</sub>	0.01	0.01
		SO <sub>2</sub>	0.01	0.01
		VOC	5.21	0.01
		СО	0.08	0.01
	RTO Stack (10) MSS Activities	NO <sub>x</sub>	0.10	0.01
		PM <sub>10</sub>	0.15	0.58
		SO <sub>2</sub>	0.01	0.05
		VOC	0.13	0.48
	Operations	СО	0.08	0.23
TO-STK	RTO Stack (10) Normal	NO <sub>x</sub>	0.10	0.28
		Benzene		0.01
		Butadiene		0.01
		Butene		0.01
		Propylene		0.07
		VOC		0.22
109MSS	Splitter Project	СО		0.15
1-105A-	Main Flare MSS Activities-109	NO <sub>x</sub>	(14)	0.03
		Benzene	30.50	0.80
		Butadiene	40.26	0.80
		Butene	48.80	6.38
		Propylene	488.00	19.94
		Ethylene	62.22	3.99
		H₂S	0.27	0.02
		SO <sub>2</sub>	24.00	2.77
		VOC (12)	670.00	44.88
		СО	447.00	58.60
	Main Flare MSS Activities	NO <sub>x</sub>	87.70	11.50
		Benzene	28.49	0.08
		Butadiene	33.51	0.08
		Butene	50.27	0.48

TO-TANK	Fuel Tank	VOC	0.06	0.01
185-F	Fuel Tank	VOC	0.02	0.01
187-F	Fuel Tank	VOC	0.02	0.01
F-1-101-U	Cooling Tower (8 cell) (5)	VOC (12)	3.70	3.86
		PM	0.55	1.93
		PM <sub>10</sub>	0.31	1.24
		PM <sub>2.5</sub>	<0.01	0.02
		Ethylene	0.93	0.39
		Propylene	3.66	1.93
		Butene	0.01	0.01
		Butadiene	0.01	0.01
		Benzene	0.01	0.01
F-2401-UL	Cooling Tower (3 cell) (5)	VOC (12)	1.39	1.45
		PM	0.21	0.72
		PM <sub>10</sub>	0.12	0.46
		PM <sub>2.5</sub>	<0.01	<0.01
		Ethylene	0.14	0.15
		Propylene	0.70	0.73
		Butene	0.01	0.01
		Butadiene	0.01	0.01
		Benzene	0.01	0.01
F-1-L4	Loading Flare K/O	VOC	0.57	0.01
LD-SLUDGE	Loading CPI Sludge	VOC	0.24	0.01
LD-TAR	Loading Tar	VOC	2.63	0.08
ENG-R	RTO Compressor	NO <sub>x</sub>	2.43	10.62
		СО	0.24	2.12
		VOC	0.08	0.34
		SO <sub>2</sub>	0.49	0.99
		PM <sub>10</sub>	0.23	1.06
BLOW-VENT	Blow Down Vents (11)	VOC	4.94	0.98
ANA-VENT	Process Analyzers Vent (9)	NO <sub>x</sub>	0.01	0.01
Project Numbers: 233	124, 233149 and 233151	•	•	

	1	1		
		СО	0.01	0.01
		VOC (6)	0.05	0.23
		Propylene	0.02	0.08
V-1-L4	Propylene Truck Loading	VOC	0.24	0.40
V-2-L4	Propylene Rail Loading	VOC	0.12	0.03
267-F	Storage Tank	VOC	0.02	0.01
M-102A	Storage Tank	VOC	0.19	0.01
M-102B	Storage Tank	VOC	0.26	0.01
137-F	Storage Tank	VOC	0.01	0.01
179-F/797F	Fuel Tank	VOC	0.21	0.01
F-1-GB	Stormwater System	VOC	5.43	1.25
MAINT- METER	Meter Calibrations	VOC	0.01	0.01
PLANT	Plant Fugitives (5)	VOC (12)	11.58	49.41
		Ethylene	0.58	2.47
		Propylene	5.79	24.71
		Butene	0.12	0.49
		Butadiene	0.01	0.05
		Benzene	0.12	0.49
PLANT-109	Plant Fugitives – 109 Splitter	VOC	0.05	0.23
		Propylene	0.02	0.09
		Butene	0.01	0.01
		Butadiene	0.01	0.01
		Benzene	0.01	0.01
A-206	Regenerator Scrubber	VOC	0.67	0.01
TOTES	Containers	VOC	1.51	0.15
WTC	Containers	Caustic	1.39	0.14
LD-CAT	Catalyst Handling	PM <sub>10</sub>	0.04	0.03
		PM <sub>2.5</sub>	0.03	0.02
CAT-	Catalyst Transfer	PM <sub>10</sub>	0.09	0.02
TRANSFER1		PM <sub>2.5</sub>	0.06	0.02

CAT-CLEAR1	Catalyst Clearing	PM <sub>10</sub>	11.14	0.13
		PM <sub>2.5</sub>	8.35	0.10
PLANT NH <sub>3</sub>	Ammonia Handling	NH <sub>3</sub>	0.18	0.57
DEGR	Cold Solvent Cleaner	VOC	0.01	0.05
PLANT MSS	Process Systems MSS	VOC (12)	43.84	8.00
		Ethylene	2.83	0.52
		Propylene	18.84	3.44
		Butene	12.50	0.05
		Butadiene	0.50	0.01
		Benzene	1.00	0.01
PLANT-109	Plant-109 Splitter Process	VOC	(15)	0.44
MSS	Systems MSS	Propylene		0.13
		Butene		0.01
		Butadiene		0.01
		Benzene		0.01
PLANT MSS	Transfer System MSS	VOC	0.19	0.01
PLANT MSS	Storage System MSS	VOC	2.29	1.03
PLANT MSS	Tank M-1002 MSS	VOC	294.39	0.69
PLANT MSS	Tank M-223 MSS	VOC	31.25	0.04
PLANT MSS	Tank M-224 MSS	VOC	31.25	0.04
PLANT MSS	Blasting	PM (13)	0.12	0.02
		PM <sub>10</sub>	0.03	0.01
		PM <sub>2.5</sub>	0.01	0.01
PLANT MSS	Painting	VOC	13.01	1.59
		PM	0.25	0.06
		PM10	0.25	0.06
		PM <sub>2.5</sub>	0.25	0.06

Steam Eductor Normal Operation and Maintenance, Startup, and Shutdown (MSS)		NO <sub>x</sub>	2.54	2.39
	СО	191.11	1.61	
	SO <sub>2</sub>	0.10	0.01	
		VOC (12)	260.81	5.10
		Ethylene	13.17	0.81
		Propylene	39.24	1.27
		Butene	2.60	0.02
	Butadiene	0.13	0.01	
		Benzene	0.26	0.01

- (1) Emission point identification either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources, use area name or fugitive source name.
- (3) NO<sub>X</sub> total oxides of nitrogen
  - CO carbon monoxide
  - VOC volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
  - SO<sub>2</sub> sulfur dioxide
  - PM total particulate matter, suspended in the atmosphere, including PM<sub>10</sub> and PM<sub>2.5</sub>, as represented
  - PM<sub>10</sub> total particulate matter equal to or less than 10 microns in diameter, including PM<sub>2.5</sub>, as represented
  - PM<sub>2.5</sub> particulate matter equal to or less than 2.5 microns in diameter
  - NH<sub>3</sub> ammonia
  - H<sub>2</sub>S hydrogen sulfide
- (4) Compliance with annual emission limits (tons per year) is based on a 12-month rolling period.
- (5) Emission rate is an estimate and is enforceable through compliance with the applicable special condition(s) and permit application representations.
- (6) The VOC includes HRVOC chemicals; ethylene and propylene.
- (7) Emissions vent to carbon canister when RTO is not in operation.
- (8) The  $NO_X$  emission rate is based on the boiler firing plant fuel gas containing hydrogen.
- (9) Emissions for analyzer vents AT9056, AT9057, AT9058, AT9059, AT9090, and AT9095 are included in EPN ANA-VENT.
- (10) The following vents are routed to the RTO when the RTO is in operation: 2004-1 and 2004-2.
- (11) The EPN BLOW-VENT (Facility Identification Nos 102C, 116J, 117J, 157F, and 210F) emissions represent normal operation values. Startup, shutdown, and maintenance emissions are not authorized from this EPN.
- (12) The VOC includes HRVOC chemicals; ethylene, propylene, butene, and butadiene.
- (13) The PM includes PM<sub>10</sub> and PM<sub>25</sub>.
- (14) Hourly allowable emission rates for 109 Splitter project are included in the emission rates for Main Flare MSS Activities at EPN 1-105A.
- (15) Hourly allowable emission rates for the 109 Splitter project are included in the emission rates for Process Systems MSS at EPN PLANT MSS.

Date: July 12, 2016