

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Permit Numbers 22377 and PSD-TX-832M3

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY
RTOEAST and RTOWEST**	Dryer RTOs	PM ₁₀	9.17	21.90
		VOC	5.25	12.53
		NO _x	81.75	195.16
		SO ₂	2.18	9.55
		CO	186.43	445.03
		HCHO	0.82	1.95
DRYER MSS***	Dryers 1-5 Bypass	PM	28.00	2.86
		PM ₁₀	20.00	2.06
		VOC	40.50	4.09
		NO _x	4.12	1.10
		CO	26.50	3.28
		HCHO	2.27	0.23
RTOPRESS/RCOPRESS 13.69	Press RTO/RCO	PM ₁₀		4.02
		VOC	4.64	15.81
		NO _x	14.83	50.57
		SO ₂	0.01	0.04
		CO	50.45	172.05
		HCHO	1.64	5.58
		MDI	0.10	0.44
		C ₆ H ₅ OH	1.36	4.64
		MeOH	2.73	9.30
PRESSVENT MSS	Press Bypass	PM	4.66	0.12
		PM ₁₀	2.33	0.06
		VOC	25.27	0.63
		NO _x	0.37	0.01
		SO ₂	0.33	0.01
		CO	0.90	0.02
		HCHO	0.68	0.02

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY
S-1	Saw Line Collector	MDI	0.03	<0.01
		C ₆ H ₅ OH	0.34	0.01
		PM ₁₀ #	1.34	5.89
		VOC	3.27	11.14
S-1 MSS ##	Saw Line Bypass	PM ₁₀ #	4.03	0.20
S-2	Aspiration System Baghouse	PM ₁₀ #	0.62	2.71
		VOC	14.96	51.03
		HCHO	0.42	1.43
		MDI	<0.01	0.01
		C ₆ H ₅ OH	0.01	0.02
		MeOH	6.88	23.47
S-3/4	Raw Fuel Bin Collector	PM ₁₀ #	0.58	2.52
		VOC	7.67	26.16
		HCHO	0.05	0.18
		MeOH	0.12	0.41
S-3/4 MSS##	Raw Fuel Bypass	PM ₁₀ #	3.46	0.35
S-5	Material Reject Collector	PM ₁₀ #	1.43	6.28
		VOC	2.54	8.65
		HCHO	0.07	0.23
		MDI	<0.01	<0.01
		C ₆ H ₅ OH	<0.01	0.01
		MeOH	0.34	1.16
S-6	Tongue and Grove Sanderdust Collector	PM ₁₀ #	1.12	4.93
		VOC	1.47	5.02
S-7	T & G/Sander Transfer Bin Baghouse	PM ₁₀ #	0.02	0.08
		VOC	1.47	5.02
S-8	Finish Fuel Bin Collector	PM ₁₀ #	0.71	3.10
		VOC	5.72	19.51
		MeOH	0.11	0.37

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY
S-9	Thermal Fuel Re grind Collector	PM ₁₀ #	0.39	1.69
		VOC	0.95	3.26
		MeOH	0.02	0.06
R-1	PF Tank 1	HCHO	0.02	0.01
R-2	PF Tank 2	HCHO	0.02	0.01
R-3	MDI Tank 1	MDI	<0.01	<0.01
R-4	MDI Tank 2	MDI	<0.01	<0.01
T-1	Gasoline Tank	VOC###	0.30	0.66
T-3	Diesel Tank	VOC	0.10	<0.01
F-1	Fuel Pile (4)	PM ₁₀	0.04	0.17
		VOC	0.40	1.76
F-2	Roadways (4)	PM	10.77	23.59
		PM ₁₀	2.10	4.60
F-3	Wet Deck (4)	PM	14.38	6.31
		PM ₁₀	4.47	1.96
BARK	Bark Handling System (4)	PM	0.47	1.02
		PM ₁₀	0.16	0.36
FINES	Excess Fuel System (4)	PM	0.06	0.13
		PM ₁₀	0.02	0.04
TOH-1****	Thermal Oil Heater Bypass Stack	PM ₁₀	0.24	1.04
		VOC	0.17	0.76
		NO _x	3.14	13.74
		SO ₂	0.02	0.08
		CO	2.64	11.54

GEN-1	Emergency Generator	PM ₁₀	4.50	0.34
		VOC	0.15	0.01
		NO _x	11.84	0.89
		SO ₂	3.24	0.24
		CO	5.42	0.41
FWP-1	Fire Water Pump	PM ₁₀	1.58	0.08
		VOC	0.18	0.01
		NO _x	4.54	0.23
		SO ₂	1.18	0.06
		CO	4.54	0.23
PB-1	Paint Booth	PM ₁₀	0.68	1.49
		VOC	1.54	3.37
PB-2	T & G Paint Booth	PM ₁₀	0.65	1.42
		VOC	1.46	3.19

- (1) Emission point identification - either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources use area name or fugitive source name.
- (3)
 - PM - particulate matter, suspended in the atmosphere, including PM₁₀
 - PM₁₀ - particulate matter equal or less than 10 microns in diameter. Where PM is not listed, it shall be assumed that no PM greater than 10 microns is emitted.
 - VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1 (VOC quantified as Propane).
 - NO_x - total oxides of nitrogen
 - SO₂ - sulfur dioxide
 - CO - carbon monoxide
 - HCHO - formaldehyde
 - MDI - methylene-diphenyl-diisocyanate
 - C₆H₅OH - phenol
 - MeOH - methanol

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

(4) Fugitive emissions are an estimate.

- * Emission rates are based on and the facilities are limited by the following maximum operating schedule:

Hrs/day 24 Days/week 7 Weeks/year 52 or Hrs/year 8,760

A total maximum press daily throughput of 1,636,250 ft² of waferboard (on 3/8-inch basis), and a total maximum annual plant throughput of 465,000,000 ft² of 3/8-inch oriented strand board processed as calculated in Special Condition No. 26.

** Maximum combined emissions for both RTOs.

*** Represent total emissions from all 5 dryers. The total emissions for the 5 dryers were used in the modeling.

**** The thermal oil heaters vent to the atmosphere through this bypass stack only when these thermal oil heaters use natural gas as fuel.

Also counted as wood dust.

These are not additional EPNs but represent emissions from EPNs S-1 to S-3/4 during emergency shutdown.

VOC includes benzene.

VOCs are quantified as propane.

Dated August 4, 2005