

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Permit Nos. 3611D and PSD-TX-194M4

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

### AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates (*)	
			lb/hr	TPY
DC-1A	Raw Crusher	PM <sub>10</sub>	3.24	14.16
DC-1B	Belt 104/105	PM <sub>10</sub>	0.24	1.10
DC-1C	Belt 202B/213	PM <sub>10</sub>	0.16	0.71
DC-2 and DC-9	Kiln Exhaust (4)			
	Sum of 2 EPNs:			
	Kiln Stack No. 1	NO <sub>x</sub> (30-day rolling average lb/hr)	420	1840.***
	Kiln Stack No. 2	SO <sub>2</sub> (24-hour rolling average)	416.	1822.****
		PM*	41.7*	178.3*
		PM**	95.**	360.**
		CO	5298.	5528.
DC-3A	Blend Silo Nos. 1 and 2	PM <sub>10</sub>	2.43	10.60
DC-3B	Kiln Feed System	PM <sub>10</sub>	0.71	3.10
DC-3C	Blend Silo No. 3	PM <sub>10</sub>	2.43	10.60
DC-3D1	Kiln Feed Pump	PM <sub>10</sub>	0.16	0.71
DC-3D2	Kiln Feed Pump	PM <sub>10</sub>	0.16	0.71
DC-3D3	Kiln Feed Pump	PM <sub>10</sub>	0.16	0.71

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	<u>Emission Rates *</u>	
			<u>lb/hr</u>	<u>TPY</u>
DC-4	Clinker Cooler (4)	PM <sub>10</sub>	10.00	43.80
DC-4A-1	Conveyor 413/448	PM <sub>10</sub>	0.45	2.00
DC-5	Finish Mill No. 1	PM <sub>10</sub>	7.8	34.2
DC-5A-1	Finish Feed No. 1 Feed Belt 806	PM <sub>10</sub>	0.81	3.5
DC-6A	Finish Cement Silos A 1-9	PM <sub>10</sub>	1.43	6.3
DC-6B	Rail Bulk Loadout - A Silos	PM <sub>10</sub>	0.32	1.4
DC-6C	Truck Bulk Loadout - A Silos	PM <sub>10</sub>	0.32	1.4
DC-6D	Masonry Cement Loading	PM <sub>10</sub>	0.32	1.4
DC-7B	Finish Mill No. 1 Feed Silos	PM <sub>10</sub>	3.0	13.0
DC-8	Cement Bag Packhouse No. 1	PM <sub>10</sub>	1.84	8.1
DC-10A	Finish Mill No. 2	PM <sub>10</sub>	1.5	6.6
DC-10B	Finish Mill No. 2	PM <sub>10</sub>	5.3	23.0
DC-10C-1	Finish Mill No. 2 Feed Belt 806B	PM <sub>10</sub>	0.81	3.5
DC-11A	Finish Cement Silos B 4-7	PM <sub>10</sub>	1.43	6.3

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	<u>Emission Rates *</u>	
			<u>lb/hr</u>	<u>TPY</u>
DC-11B	Finish Cement Silos B 1, 2, 3, and 8	PM <sub>10</sub>	1.43	6.3
DC-11C	Truck Bulk Loadout No. 1 B Silos	PM <sub>10</sub>	0.32	1.4
DC-11D	Truck Bulk Loadout No. 2 B Silos	PM <sub>10</sub>	0.32	1.4
DC-11E	Clinker Loadout Silos	PM <sub>10</sub>	1.0	4.3
DC-11F	Clinker Loadout	PM <sub>10</sub>	0.73	3.2
DC-13	Clinker Storage Building	PM <sub>10</sub>	3.0	13.0
DC-13A	Fringe Bin	PM <sub>10</sub>	0.65	2.8
DC-20	Clinker Fines Dust Bin	PM <sub>10</sub>	0.22	0.95
FUG-1	Coal Stockpile and Material Handling (5)	PM	-	1.82
		PM <sub>10</sub>	-	0.91
FUG-2	Iron Stockpile and Material Handling (5)	PM	-	0.84
		PM <sub>10</sub>	-	0.44
FUG-3	Sand Stockpile and Material Handling (5)	PM	-	1.39
		PM <sub>10</sub>	-	0.70
FUG-4	Road Emissions (5)	PM <sub>10</sub>	-	2.43
FUG-5	Street Sweeper Dump and Material Handling (5)	PM	-	0.40
		PM <sub>10</sub>	-	0.20

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

- (1) Emission point identification - either specific equipment designation or emission point number from a plot plan.
- (2) Specific point source names. For fugitive sources use area name or fugitive source name.
- (3) PM - particulate matter, suspended in the atmosphere, including PM<sub>10</sub>.  
PM<sub>10</sub> - particulate matter equal to or less than 10 microns in diameter. Where PM is not listed, it shall be assumed that no PM greater than 10 microns is emitted.  
NO<sub>x</sub> - total oxides of nitrogen  
SO<sub>2</sub> - sulfur dioxide  
CO - carbon monoxide
- (4) Emissions from DC-4 must comply with New Source Performance Standard, Subpart F. Combined emissions from DC-2 and DC-9 must also comply with New Source Performance Standard, Subpart F.
- (5) Fugitive emissions are an estimate only.

Hrs/day 24 Days/week 7 Weeks/year 52 or Hrs/year 8,760

- \* PM allowables for prevention of significant deterioration permit, based on front-half PM emissions only, as measured by the U.S. Environmental Protection Agency Method 5.
- \*\* PM allowables for State permit, for PM emissions as defined in 30 TAC Section 101.1.
- \*\*\* The holder of this permit has committed to achieve a NO<sub>x</sub> limitation of 2.8 lbs/ton of clinker and 420 lbs/hour (1840 tons/year) based on a 30-day rolling average, as measured by CEM, no later than May 1, 2003. Until May 1, 2003 NO<sub>x</sub> emissions are limited to 600 lbs/hour (2628 tons/year) based on a 30-day rolling average.
- \*\*\*\* The holder of this permit has committed to achieve a SO<sub>2</sub> limitation of 416 lbs/hr based on a 24-hour rolling average as measured by CEM no later than May 1, 2001.

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Dated\_\_\_\_\_